EXHIBIT 1

US010218606B2

(12) **United States Patent**
Perreault et al.

(10) **Patent No.: US 10,218,606 B2**
(45) **Date of Patent: *Feb. 26, 2019**

(54) **PRODUCING ROUTING MESSAGES FOR VOICE OVER IP COMMUNICATIONS**

(71) Applicant: **VoIP-Pal.com, Inc.**, Bellevue, WA (US)

(72) Inventors: **Clay Perreault**, Panama (PA); **Steve Nicholson**, Hamilton (NZ); **Rod Thomson**, North Vancouver (CA); **Johan Emil Viktor Björsell**, Vancouver (CA); **Fuad Arafa**, Vancouver (CA)

(73) Assignee: **VoIP-Pal.com, Inc.**, Bellevue, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/942,282**

(22) Filed: **Mar. 30, 2018**

(65) **Prior Publication Data**

US 2018/0227222 A1 Aug. 9, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/730,600, filed on Oct. 11, 2017, now Pat. No. 9,935,872, which is a (Continued)

(51) **Int. Cl.**
H04L 12/725 (2013.01)
H04L 9/32 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H04L 45/3065*** (2013.01); ***A61K 39/39558*** (2013.01); ***A61K 45/06*** (2013.01);
(Continued)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,747,124 A 5/1988 Ladd
4,916,491 A 4/1990 Katoh
(Continued)

FOREIGN PATENT DOCUMENTS

BR PI 0718312-7 A2 11/2013
BR PI 0719682-2 A2 1/2014
(Continued)

OTHER PUBLICATIONS

Abrazhevich, Dennis. "Electronic Payment Systems: a User-Centered Perspective and Interaction Design," *Thesis under the auspices of the J.F. Schouten School for User-System Interaction Research*, Technische Universiteit Eindhoven, Netherlands, 2004, pages Cover page—p. 189.
(Continued)

Primary Examiner — Kodzovi Acolatse
(74) *Attorney, Agent, or Firm* — Thorpe North & Western, LLP

(57) **ABSTRACT**

A process and apparatus to facilitate communication between callers and callees in a system comprising a plurality of nodes with which callers and callees are associated is disclosed. In response to initiation of a call by a calling subscriber, a caller identifier and a callee identifier are received. Call classification criteria associated with the caller identifier are used to classify the call as a public network call or a private network call. A routing message identifying an address, on the private network, associated with the callee is produced when the call is classified as a private network call and a routing message identifying a gateway to the public network is produced when the call is classified as a public network call.

49 Claims, 32 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/396,344, filed on Dec. 30, 2016, now Pat. No. 9,813,330, which is a continuation of application No. 14/877,570, filed on Oct. 7, 2015, now Pat. No. 9,537,762, which is a continuation of application No. 13/966,096, filed on Aug. 13, 2013, now Pat. No. 9,179,005, which is a continuation of application No. 12/513,147, filed as application No. PCT/CA2007/001956 on Nov. 1, 2007, now Pat. No. 8,542,815.

(60) Provisional application No. 60/856,212, filed on Nov. 2, 2006.

(51) **Int. Cl.**

H04L 12/14	(2006.01)
H04L 12/66	(2006.01)
H04Q 3/66	(2006.01)
H04Q 3/70	(2006.01)
H04M 7/00	(2006.01)
H04M 15/00	(2006.01)
H04M 15/02	(2006.01)
H04M 3/42	(2006.01)
A61K 39/395	(2006.01)
A61K 45/06	(2006.01)
C07K 16/18	(2006.01)
H04L 29/12	(2006.01)
H04L 29/06	(2006.01)

(52) **U.S. Cl.**

CPC ***C07K 16/18*** (2013.01); ***H04L 9/3226*** (2013.01); ***H04L 12/14*** (2013.01); ***H04L 12/1439*** (2013.01); ***H04L 12/1496*** (2013.01); ***H04L 12/66*** (2013.01); ***H04L 61/2007*** (2013.01); ***H04L 65/1033*** (2013.01); ***H04L 65/1069*** (2013.01); ***H04M 3/4211*** (2013.01); ***H04M 7/006*** (2013.01); ***H04M 7/0075*** (2013.01); ***H04M 15/51*** (2013.01); ***H04M 15/56*** (2013.01); ***H04M 15/8083*** (2013.01); ***H04M 15/8228*** (2013.01); ***H04M 15/887*** (2013.01); ***H04M 15/888*** (2013.01); ***H04Q 3/66*** (2013.01); ***H04Q 3/70*** (2013.01); *H04Q 2213/1322* (2013.01); *H04Q 2213/13091* (2013.01); *H04Q 2213/13141* (2013.01); *H04Q 2213/13196* (2013.01); *H04Q 2213/13384* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,992,971	A	2/1991	Hayashi
5,146,491	A	9/1992	Silver et al.
5,247,571	A	9/1993	Kay et al.
5,303,297	A	4/1994	Hillis
5,325,421	A	6/1994	Hou et al.
5,359,642	A	10/1994	Castro
5,425,085	A	6/1995	Weinberger et al.
5,440,621	A	8/1995	Castro
5,454,030	A	9/1995	de Oliveira et al.
5,469,497	A	11/1995	Pierce et al.
5,506,893	A	4/1996	Buscher et al.
5,519,769	A	5/1996	Weinberger et al.
5,559,871	A	9/1996	Smith
5,561,707	A	10/1996	Katz
5,590,133	A	12/1996	Billstrom et al.
5,602,907	A	2/1997	Hata et al.
5,608,786	A	3/1997	Gordon
5,621,787	A	4/1997	McKoy et al.
5,633,913	A	5/1997	Talarmo
5,661,790	A	8/1997	Hsu
5,677,955	A	10/1997	Doggett et al.
5,712,907	A	1/1998	Wegner et al.
5,719,926	A	2/1998	Hill
5,722,067	A	2/1998	Fougnies et al.
5,724,355	A	3/1998	Bruno et al.
5,726,984	A	3/1998	Kubler et al.
5,737,414	A	4/1998	Walker et al.
5,742,596	A	4/1998	Baratz et al.
5,751,961	A	5/1998	Smyk
5,768,521	A	6/1998	Dedrick
5,793,762	A	8/1998	Penners et al.
5,799,072	A	8/1998	Vulcan et al.
5,802,502	A	9/1998	Gell et al.
5,825,863	A	10/1998	Walker
5,828,740	A	10/1998	Khuc et al.
5,838,682	A	11/1998	Dekelbaum et al.
5,845,267	A	12/1998	Ronen
5,850,433	A	12/1998	Rondeau
5,864,610	A	1/1999	Ronen
5,867,495	A	2/1999	Elliott et al.
5,883,810	A	3/1999	Franklin et al.
5,883,891	A	3/1999	Williams et al.
5,889,774	A	3/1999	Mirashrafi et al.
5,905,736	A	5/1999	Ronen et al.
5,907,547	A	5/1999	Foladare et al.
5,910,946	A	6/1999	Csapo
5,915,005	A	6/1999	He
5,915,093	A	6/1999	Berlin et al.
5,917,899	A	6/1999	Moss et al.
5,923,659	A	7/1999	Curry et al.
5,930,343	A	7/1999	Vasquez
5,937,045	A	8/1999	Yaoya et al.
5,940,598	A	8/1999	Strauss et al.
5,953,504	A	9/1999	Sokal et al.
5,956,391	A	9/1999	Melen et al.
5,970,477	A	10/1999	Roden
5,974,043	A	10/1999	Solomon
5,991,291	A	11/1999	Asai et al.
5,991,378	A	11/1999	Apel
6,005,870	A	12/1999	Leung et al.
6,005,926	A	12/1999	Mashinsky
6,014,379	A	1/2000	White et al.
6,021,126	A	2/2000	White et al.
6,029,062	A	2/2000	Hanson
6,036,090	A	3/2000	Rahman et al.
6,052,445	A	4/2000	Bashoura et al.
6,058,300	A	5/2000	Hanson
6,069,890	A	5/2000	White et al.
6,073,013	A	6/2000	Agre et al.
6,078,647	A	6/2000	D'Eletto
6,104,704	A	8/2000	Buhler et al.
6,104,711	A	8/2000	Voit
6,115,737	A	9/2000	Ely et al.
6,128,304	A	10/2000	Gardell et al.
6,137,869	A	10/2000	Voit et al.
6,141,404	A	10/2000	Westerlage et al.
6,151,385	A	11/2000	Reich et al.
6,173,272	B1	1/2001	Thomas et al.
6,185,414	B1	2/2001	Brunner et al.
6,188,752	B1	2/2001	Lesley
6,192,123	B1	2/2001	Grunsted et al.
6,236,851	B1	5/2001	Fougnies et al.
6,240,449	B1	5/2001	Nadeau
6,243,689	B1	6/2001	Norton
6,249,573	B1	6/2001	Hudson
6,282,574	B1	8/2001	Voit
6,292,547	B1	9/2001	Katz
6,298,062	B1	10/2001	Gardell et al.
6,298,250	B1	10/2001	Nilsson
6,310,859	B1	10/2001	Morita et al.
6,327,351	B1	12/2001	Walker et al.
6,351,464	B1	2/2002	Galvin et al.
6,359,880	B1	3/2002	Curry et al.
6,430,275	B1	8/2002	Voit et al.
6,434,143	B1	8/2002	Donovan
6,445,694	B1	9/2002	Swartz
6,507,644	B1	1/2003	Henderson et al.
6,553,025	B1	4/2003	Kung et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,560,224 B1 5/2003 Kung et al.
6,574,328 B1 6/2003 Wood et al.
6,594,254 B1 7/2003 Kelly
6,597,686 B1 7/2003 Smyk
6,597,783 B1 7/2003 Tada et al.
6,603,977 B1 8/2003 Walsh et al.
6,636,833 B1 10/2003 Flitcroft et al.
6,650,641 B1 11/2003 Albert et al.
6,674,745 B1 1/2004 Schuster et al.
6,674,850 B2 1/2004 Vu et al.
6,724,860 B2 4/2004 Stumer et al.
6,744,858 B1 6/2004 Ryan et al.
6,760,324 B1 7/2004 Scott et al.
6,766,159 B2 7/2004 Lindholm
6,772,188 B1 8/2004 Cloutier
6,772,210 B1 8/2004 Edholm
6,775,534 B2 8/2004 Lindgren et al.
6,785,266 B2 8/2004 Swartz
6,798,767 B1 9/2004 Alexander et al.
6,819,929 B2 11/2004 Antonucci et al.
6,873,599 B1 3/2005 Han
6,892,184 B1 5/2005 Komen et al.
6,934,279 B1 8/2005 Sollee et al.
6,937,713 B1 8/2005 Kung et al.
6,947,531 B1 9/2005 Lewis et al.
6,954,453 B1 10/2005 Schindler
6,961,334 B1 11/2005 Kaczmarczyk
6,963,557 B2 11/2005 Knox
6,963,739 B2 11/2005 Dorenbosch et al.
6,985,440 B1 1/2006 Albert et al.
6,993,015 B2 1/2006 Kobayashi
7,006,508 B2 2/2006 Bondy et al.
7,010,727 B1 3/2006 Stucker
7,027,564 B2 4/2006 James
7,042,985 B1 5/2006 Wright
7,046,658 B1 5/2006 Kundaje
7,047,561 B1 5/2006 Lee
7,051,072 B2 5/2006 Stewart et al.
7,055,174 B1 5/2006 Cope et al.
7,068,668 B2 6/2006 Feuer
7,068,772 B1 6/2006 Widger et al.
7,079,526 B1 7/2006 Wipliez et al.
7,120,682 B1 10/2006 Salama
7,151,772 B1 12/2006 Kalmanek, Jr. et al.
7,174,156 B1 2/2007 Mangal
7,177,399 B2 2/2007 Dawson et al.
7,203,478 B2 4/2007 Benco et al.
7,212,522 B1 5/2007 Shankar et al.
7,218,722 B1 5/2007 Turner et al.
7,277,528 B2 10/2007 Rao et al.
7,330,835 B2 2/2008 Deggendorf
7,346,156 B1 3/2008 Choupak et al.
7,366,157 B1 4/2008 Valentine et al.
7,400,881 B2 7/2008 Kallio
7,426,492 B1 9/2008 Bishop et al.
7,436,835 B2 10/2008 Castleberry et al.
7,437,665 B2 10/2008 Perham
7,440,441 B2 10/2008 Lakhani et al.
7,440,442 B2 10/2008 Grabelsky et al.
7,447,707 B2 11/2008 Gaurav et al.
7,454,200 B2 11/2008 Cai et al.
7,454,510 B2 11/2008 Kleyman et al.
7,457,865 B2 11/2008 Ramakrishnan et al.
7,477,843 B1 * 1/2009 Peeters H04Q 11/0062 398/49
7,486,664 B2 2/2009 Swartz
7,486,667 B2 2/2009 Feuer
7,486,684 B2 2/2009 Chu et al.
7,512,117 B2 3/2009 Swartz
7,545,761 B1 6/2009 Kalbag
7,565,131 B2 7/2009 Rollender
7,573,982 B2 8/2009 Breen et al.
7,580,886 B1 8/2009 Schulz
7,587,036 B2 9/2009 Wood et al.
7,593,390 B2 9/2009 Lebizay
7,593,884 B2 9/2009 Rothman et al.
7,599,944 B2 10/2009 Gaurav et al.
7,639,792 B2 12/2009 Qiu et al.
7,644,037 B1 1/2010 Ostrovsky
7,647,500 B2 1/2010 Machiraju et al.
7,657,011 B1 2/2010 Zielinski et al.
7,664,495 B1 2/2010 Bonner et al.
7,676,215 B2 3/2010 Chin et al.
7,676,431 B2 3/2010 O'Leary et al.
7,680,114 B2 3/2010 Yazaki et al.
7,680,737 B2 3/2010 Smith et al.
7,702,308 B2 4/2010 Rollender
7,715,413 B2 5/2010 Vaziri et al.
7,715,821 B2 5/2010 Rollender
7,734,544 B2 6/2010 Schleicher
7,738,384 B2 6/2010 Pelletier
7,764,777 B2 7/2010 Wood et al.
7,764,944 B2 7/2010 Rollender
7,765,261 B2 7/2010 Kropivny
7,765,266 B2 7/2010 Kropivny
7,774,711 B2 8/2010 Valeski
7,797,459 B1 9/2010 Roy et al.
7,882,011 B2 2/2011 Sandhu et al.
7,894,441 B2 2/2011 Yazaki et al.
7,899,742 B2 3/2011 Berkert et al.
7,907,551 B2 3/2011 Croy et al.
7,907,714 B2 3/2011 Baniak et al.
7,929,955 B1 4/2011 Bonner
7,944,909 B2 5/2011 James
7,950,046 B2 5/2011 Kropivny
7,958,233 B2 6/2011 Gutierrez
7,965,645 B2 6/2011 Pelletier
7,979,529 B2 7/2011 Kreusch et al.
7,995,589 B2 8/2011 Sollee et al.
8,024,785 B2 9/2011 Andress et al.
8,027,333 B2 9/2011 Grabelsky et al.
8,036,366 B2 10/2011 Chu
8,041,022 B1 10/2011 Andreasen et al.
8,050,273 B2 11/2011 Gass
8,060,887 B2 11/2011 Kropivny
8,078,164 B2 12/2011 Ganesan
8,111,690 B2 2/2012 Hussain et al.
8,116,307 B1 2/2012 Thesayi et al.
8,125,982 B2 2/2012 Feuer
8,127,005 B2 2/2012 Gutierrez
8,145,182 B2 3/2012 Rudolf et al.
8,161,078 B2 4/2012 Gaurav et al.
8,166,533 B2 4/2012 Yuan
8,166,547 B2 4/2012 Bevan et al.
8,189,568 B2 5/2012 Qiu et al.
8,190,739 B2 5/2012 Gutierrez
8,200,575 B2 6/2012 Torres et al.
8,204,044 B2 6/2012 Lebizay
8,219,115 B1 7/2012 Nelissen
8,223,927 B2 7/2012 Di Serio et al.
8,228,837 B2 7/2012 Sheriff et al.
8,228,897 B2 7/2012 Mitchell
8,243,730 B1 8/2012 Wong et al.
8,244,204 B1 8/2012 Chen et al.
8,275,404 B2 9/2012 Berger et al.
8,300,632 B2 10/2012 Davis et al.
8,306,021 B2 11/2012 Lawson et al.
8,306,063 B2 11/2012 Erdal et al.
8,315,521 B2 11/2012 Leiden et al.
8,363,647 B2 1/2013 Fangman et al.
8,364,172 B2 1/2013 Guanfeng et al.
8,396,445 B2 3/2013 Crawford et al.
8,410,907 B2 4/2013 Twitchell, Jr.
8,417,791 B1 4/2013 Peretz et al.
8,422,507 B2 4/2013 Björsell et al.
8,423,791 B1 4/2013 Yu et al.
8,427,981 B2 4/2013 Wyss et al.
8,437,340 B2 5/2013 James
8,462,915 B2 6/2013 Breen et al.
8,468,196 B1 6/2013 Roskind et al.
8,493,931 B1 7/2013 Nix
8,509,225 B2 8/2013 Grabelsky et al.
8,526,306 B2 9/2013 Jungck et al.
8,532,075 B2 9/2013 Rassool et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,537,805	B2	9/2013	Björsell et al.
8,542,815	B2	9/2013	Perreault et al.
8,543,477	B2	9/2013	Love et al.
8,594,298	B2	11/2013	Klein et al.
8,599,747	B1	12/2013	Saleem et al.
8,599,837	B2	12/2013	Kyle
8,605,714	B2	12/2013	Lebizay
8,605,869	B1	12/2013	Mobarak et al.
8,607,323	B2	12/2013	Yuan
8,611,354	B2	12/2013	Keränen et al.
8,625,578	B2	1/2014	Roy et al.
8,627,211	B2	1/2014	Kropivny
8,630,234	B2	1/2014	Björsell et al.
8,634,838	B2	1/2014	Hellwig et al.
8,675,566	B2	3/2014	Huttunen et al.
8,682,919	B1	3/2014	Golliher
8,702,505	B2	4/2014	Kropivny
8,713,098	B1	4/2014	Adya et al.
8,724,643	B2	5/2014	Feuer
8,738,051	B2	5/2014	Nowack et al.
8,749,610	B1	6/2014	Gossweiler et al.
8,750,290	B2	6/2014	Vance et al.
8,755,376	B2	6/2014	Lawson et al.
8,763,081	B2	6/2014	Bogdanovic et al.
8,767,717	B2	7/2014	Siegel et al.
8,768,951	B2	7/2014	Crago
8,774,171	B2	7/2014	Mitchell
8,774,378	B2	7/2014	Björsell et al.
8,774,721	B2	7/2014	Hertel et al.
8,780,703	B1	7/2014	Eidelson et al.
8,792,374	B1	7/2014	Jain et al.
8,792,905	B1	7/2014	Li et al.
8,804,705	B2	8/2014	Fangman et al.
8,805,345	B2	8/2014	Ling et al.
8,810,392	B1	8/2014	Teller et al.
8,819,566	B2	8/2014	Mehin et al.
8,837,360	B1	9/2014	Mishra et al.
8,837,465	B2	9/2014	Lawson et al.
8,838,539	B1	9/2014	Ashcraft et al.
8,848,887	B2	9/2014	Willman et al.
8,862,701	B2	10/2014	Havriluk
8,885,609	B2	11/2014	Nix
8,903,051	B2	12/2014	Li et al.
8,903,360	B2	12/2014	Celi, Jr. et al.
8,909,556	B2	12/2014	Huxham
8,938,209	B2	1/2015	Crawford et al.
8,938,534	B2	1/2015	Le et al.
8,948,061	B2	2/2015	Sridhar
8,972,612	B2	3/2015	Le et al.
8,982,719	B2	3/2015	Seetharaman et al.
8,995,428	B2	3/2015	Haster
9,003,306	B2	4/2015	Mehin et al.
9,137,385	B2	9/2015	Björsell et al.
9,143,608	B2	9/2015	Björsell et al.
9,154,417	B2	10/2015	Huttunen et al.
9,179,005	B2	11/2015	Perreault et al.
9,432,830	B2	8/2016	Lahtiranta et al.
9,537,762	B2	1/2017	Perrault et al.
9,549,071	B2	1/2017	Björsell et al.
9,565,307	B2	2/2017	Björsell et al.
9,813,330	B2	11/2017	Perreault et al.
9,826,002	B2	11/2017	Perreault et al.
9,935,872	B2	4/2018	Perreault et al.
9,948,549	B2	4/2018	Perreault et al.
9,998,363	B2	6/2018	Björsell et al.
10,021,729	B2	7/2018	Huttunen et al.
10,038,779	B2	7/2018	Björsell et al.
2001/0027478	A1	10/2001	Meier et al.
2001/0052081	A1	12/2001	McKibben et al.
2002/0002041	A1	1/2002	Lindgren et al.
2002/0018445	A1	2/2002	Kobayashi
2002/0051518	A1	5/2002	Bondy et al.
2002/0057764	A1	5/2002	Salvucci et al.
2002/0068545	A1	6/2002	Oyama et al.
2002/0116464	A1	8/2002	Mak
2002/0122391	A1	9/2002	Shalit
2002/0122547	A1	9/2002	Hinchey et al.
2002/0141352	A1	10/2002	Fangman et al.
2002/0150080	A1*	10/2002	Bhattacharya H04L 29/06027 370/351
2003/0008635	A1	1/2003	Ung et al.
2003/0012196	A1	1/2003	Ramakrishnan
2003/0043974	A1	3/2003	Emerson, III
2003/0095539	A1	5/2003	Feuer
2003/0114145	A1	6/2003	Boda et al.
2003/0121967	A1	7/2003	Goldberg et al.
2003/0179747	A1	9/2003	Pyke et al.
2003/0200311	A1	10/2003	Baum
2003/0211840	A1	11/2003	Castrogiovanni et al.
2003/0219103	A1	11/2003	Rao et al.
2004/0009761	A1	1/2004	Money et al.
2004/0019539	A1	1/2004	Raman et al.
2004/0022237	A1	2/2004	Elliot et al.
2004/0034793	A1	2/2004	Yuan
2004/0157629	A1	8/2004	Kallio et al.
2004/0165709	A1	8/2004	Pence et al.
2004/0181599	A1	9/2004	Kreusch et al.
2004/0202160	A1*	10/2004	Westphal H04L 12/4633 370/389
2004/0202295	A1	10/2004	Shen et al.
2004/0203565	A1	10/2004	Chin et al.
2004/0203582	A1	10/2004	Dorenbosch et al.
2004/0218748	A1	11/2004	Fisher
2004/0240439	A1	12/2004	Castleberry et al.
2004/0255126	A1	12/2004	Reith
2005/0007999	A1	1/2005	Becker et al.
2005/0021939	A1	1/2005	Le et al.
2005/0025043	A1	2/2005	Mussman et al.
2005/0063519	A1	3/2005	James
2005/0069097	A1	3/2005	Hanson et al.
2005/0083911	A1	4/2005	Grabelsky et al.
2005/0094651	A1	5/2005	Lutz et al.
2005/0131813	A1	6/2005	Gallagher et al.
2005/0169248	A1	8/2005	Truesdale et al.
2005/0171898	A1	8/2005	Bishop et al.
2005/0174937	A1	8/2005	Scoggins et al.
2005/0177843	A1	8/2005	Williams
2005/0188081	A1	8/2005	Gibson et al.
2005/0190892	A1	9/2005	Dawson et al.
2005/0192897	A1	9/2005	Rogers et al.
2005/0192901	A1	9/2005	McCoy et al.
2005/0198499	A1	9/2005	Salapaka et al.
2005/0202799	A1	9/2005	Rollender
2005/0222952	A1	10/2005	Garrett et al.
2005/0267842	A1	12/2005	Weichert et al.
2005/0287979	A1	12/2005	Rollender
2006/0006224	A1	1/2006	Modi
2006/0007940	A1	1/2006	Sollee et al.
2006/0013266	A1	1/2006	Vega-Garcia et al.
2006/0025122	A1	2/2006	Harris et al.
2006/0030290	A1	2/2006	Rudolf et al.
2006/0036522	A1	2/2006	Perham
2006/0072547	A1	4/2006	Florkey et al.
2006/0072550	A1	4/2006	Davis et al.
2006/0078094	A1	4/2006	Breen et al.
2006/0093135	A1	5/2006	Fiatal et al.
2006/0095320	A1	5/2006	Jones
2006/0109960	A1	5/2006	D'Evelyn et al.
2006/0111116	A1	5/2006	Palmer et al.
2006/0116892	A1	6/2006	Grimes et al.
2006/0142011	A1	6/2006	Kallio
2006/0146797	A1	7/2006	Lebizay
2006/0153342	A1	7/2006	Sasaki
2006/0160565	A1	7/2006	Singh et al.
2006/0177035	A1	8/2006	Cope et al.
2006/0189303	A1	8/2006	Rollender
2006/0195398	A1	8/2006	Dheer et al.
2006/0195584	A1*	8/2006	Baumann H04M 3/54 709/227
2006/0205383	A1	9/2006	Rollender et al.
2006/0209768	A1	9/2006	Yan et al.
2006/0233317	A1	10/2006	Coster et al.
2006/0248186	A1	11/2006	Smith
2006/0251056	A1	11/2006	Feuer

(56) **References Cited**

U.S. PATENT DOCUMENTS

2006/0258328 A1 11/2006 Godoy
2006/0264200 A1 11/2006 Laiho et al.
2006/0268921 A1 11/2006 Ekstrom et al.
2006/0281437 A1 12/2006 Cook
2007/0016524 A1 1/2007 Diveley et al.
2007/0036139 A1 2/2007 Patel et al.
2007/0036143 A1 2/2007 Alt et al.
2007/0047548 A1 3/2007 Yazaki et al.
2007/0053382 A1 3/2007 Bevan et al.
2007/0064919 A1 3/2007 Chen et al.
2007/0092070 A1 4/2007 Croy et al.
2007/0112964 A1 5/2007 Guedalia et al.
2007/0115935 A1 5/2007 Qiu et al.
2007/0121590 A1* 5/2007 Turner H04L 12/66 370/352
2007/0121593 A1 5/2007 Vance et al.
2007/0121602 A1* 5/2007 Sin H04L 12/6418 370/356
2007/0127676 A1 6/2007 Khadri
2007/0174469 A1 7/2007 Andress et al.
2007/0217354 A1 9/2007 Buckley
2007/0220038 A1 9/2007 Crago
2007/0253418 A1 11/2007 Shill et al.
2007/0253429 A1 11/2007 James
2007/0263609 A1 11/2007 Mitchell
2007/0297376 A1 12/2007 Gass
2008/0013523 A1 1/2008 Nambakkam
2008/0037715 A1 2/2008 Prozeniuk et al.
2008/0043718 A1 2/2008 Chu
2008/0056235 A1 3/2008 Albina et al.
2008/0056243 A1 3/2008 Roy et al.
2008/0056302 A1 3/2008 Erdal et al.
2008/0063153 A1 3/2008 Krivorot et al.
2008/0160953 A1 7/2008 Mia et al.
2008/0166999 A1 7/2008 Guedalia et al.
2008/0167019 A1 7/2008 Guedalia et al.
2008/0167020 A1 7/2008 Guedalia et al.
2008/0167039 A1 7/2008 Guedalia et al.
2008/0187122 A1 8/2008 Baker
2008/0188198 A1 8/2008 Patel et al.
2008/0188227 A1 8/2008 Guedalia et al.
2008/0205378 A1 8/2008 Wyss et al.
2008/0310599 A1 12/2008 Purnadi et al.
2009/0003535 A1 1/2009 Grabelsky et al.
2009/0012851 A1 1/2009 Marc
2009/0017842 A1 1/2009 Fukasaku
2009/0028146 A1 1/2009 Kleyman et al.
2009/0129566 A1 5/2009 Feuer
2009/0135724 A1 5/2009 Zhang et al.
2009/0135735 A1 5/2009 Zhang et al.
2009/0141883 A1 6/2009 Bastien
2009/0213839 A1 8/2009 Davis et al.
2009/0214000 A1 8/2009 Patel et al.
2009/0238168 A1 9/2009 Lavoie et al.
2009/0268615 A1 10/2009 Pelletier
2009/0292539 A1 11/2009 Jaroker
2009/0296900 A1 12/2009 Breen et al.
2009/0325558 A1 12/2009 Pridmore et al.
2010/0002701 A1 1/2010 Hsieh et al.
2010/0008345 A1 1/2010 Lebizay
2010/0039946 A1 2/2010 Imbimbo et al.
2010/0083364 A1 4/2010 Gutierrez
2010/0086119 A1 4/2010 De Luca et al.
2010/0105379 A1 4/2010 Bonner et al.
2010/0114896 A1 5/2010 Clark et al.
2010/0115018 A1 5/2010 Yoon et al.
2010/0128729 A1 5/2010 Yazaki et al.
2010/0142382 A1 6/2010 Jungck et al.
2010/0150138 A1 6/2010 Björsell et al.
2010/0150328 A1 6/2010 Perrault et al.
2010/0172345 A1 7/2010 Björsell et al.
2010/0177671 A1 7/2010 Qiu et al.
2010/0220852 A1 9/2010 Willman et al.
2010/0233991 A1 9/2010 Crawford et al.
2010/0246589 A1 9/2010 Pelletier
2010/0272242 A1 10/2010 Croy et al.
2010/0278534 A1 11/2010 Leiden et al.
2010/0316195 A1 12/2010 Di Serio et al.
2011/0013541 A1 1/2011 Croy et al.
2011/0072095 A1 3/2011 Havriluk
2011/0122827 A1 5/2011 Björsell et al.
2011/0153809 A1 6/2011 Ghanem et al.
2011/0167164 A1 7/2011 Gutierrez
2011/0176541 A1 7/2011 James
2011/0201321 A1 8/2011 Bonner
2011/0208859 A1 8/2011 Gutierrez
2011/0235543 A1 9/2011 Seetharaman et al.
2011/0255553 A1 10/2011 Bobba et al.
2011/0261717 A1 10/2011 Akuzuwa et al.
2011/0267986 A1 11/2011 Grabelsky et al.
2011/0273526 A1 11/2011 Mehin et al.
2011/0276903 A1 11/2011 Mehin et al.
2011/0276904 A1 11/2011 Mehin et al.
2011/0292929 A1 12/2011 Haster
2012/0014383 A1 1/2012 Geromel et al.
2012/0089717 A1 4/2012 Chen
2012/0096145 A1 4/2012 Le et al.
2012/0099599 A1 4/2012 Keränen et al.
2012/0113981 A1 5/2012 Feuer
2012/0155333 A1 6/2012 Yoon et al.
2012/0170574 A1 7/2012 Huttunen et al.
2012/0195236 A1 8/2012 Knight
2012/0195415 A1 8/2012 Wyss et al.
2012/0227101 A1 9/2012 Yuan
2012/0250624 A1 10/2012 Lebizay
2012/0259975 A1 10/2012 Le et al.
2012/0270554 A1 10/2012 Hellwig et al.
2012/0282881 A1 11/2012 Mitchell
2012/0314699 A1 12/2012 Qiu et al.
2013/0039226 A1 2/2013 Sridhar
2013/0097308 A1 4/2013 Le et al.
2013/0114589 A1 5/2013 Fangman et al.
2013/0128879 A1 5/2013 Kyle
2013/0148549 A1 6/2013 Crawford et al.
2013/0173534 A1 7/2013 Nelakonda et al.
2013/0223276 A1 8/2013 Padgett
2013/0229950 A1 9/2013 Björsell et al.
2013/0237198 A1 9/2013 Vashi et al.
2013/0254301 A1 9/2013 Lin et al.
2013/0272297 A1 10/2013 Breen et al.
2013/0281147 A1 10/2013 Denman et al.
2013/0287006 A1 10/2013 Nix
2013/0310002 A1 11/2013 Celi, Jr. et al.
2013/0318166 A1 11/2013 Jungck et al.
2013/0329722 A1 12/2013 Perrault et al.
2013/0329864 A1 12/2013 Björsell et al.
2014/0010119 A1 1/2014 Björsell et al.
2014/0016764 A1 1/2014 Björsell et al.
2014/0024367 A1 1/2014 Björsell et al.
2014/0101749 A1 4/2014 Yuan
2014/0141884 A1 5/2014 Kropivny
2014/0153477 A1 6/2014 Huttunen et al.
2014/0211789 A1 7/2014 Feuer
2014/0215642 A1 7/2014 Huxham
2014/0220944 A1 8/2014 Balasubramanian
2014/0244393 A1 8/2014 Rimmer et al.
2014/0247730 A1 9/2014 Thota et al.
2014/0269624 A1 9/2014 Khay-Lbbat et al.
2014/0307858 A1 10/2014 Li et al.
2014/0321333 A1 10/2014 Björsell et al.
2014/0324969 A1 10/2014 Riddle
2014/0337961 A1 11/2014 Chien et al.
2014/0337962 A1 11/2014 Brandstatter
2014/0349602 A1 11/2014 Majumdar et al.
2015/0327320 A1 11/2015 Huttunen et al.
2015/0358470 A1 12/2015 Björsell et al.
2016/0006882 A1 1/2016 Björsell et al.
2016/0028619 A1 1/2016 Perreault et al.
2017/0104868 A1 4/2017 Björsell et al.
2017/0111265 A1 4/2017 Perreault et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2017/0126752	A1	5/2017	Perreault et al.
2017/0142256	A1	5/2017	Björsell et al.

FOREIGN PATENT DOCUMENTS

CA	2 218 218	A1	10/1997
CA	2249668	A1	4/1999
CA	2 299 037	A1	8/2000
CA	2 437 275	A1	10/2002
CA	2598200	A1	2/2008
CA	2668025	A1	5/2008
CA	2670510	A1	6/2008
CA	2 681 984	A1	10/2008
CA	2 690 236	A1	12/2008
CA	2 659 007	A1	9/2009
CA	2732148	A1	2/2010
CA	2 778 905	A1	8/2010
CA	2812174	A1	3/2011
CA	2812174	C	5/2018
CA	2732148	C	6/2018
CN	1498029	A	5/2004
CN	1498482	A	5/2004
CN	1668137	A	9/2005
CN	1274114	C	9/2006
CN	101005503	A	7/2007
CN	101069390	A	11/2007
CN	101095329	A	12/2007
CN	101584150	A	11/2009
CN	101584166	A	11/2009
CN	101605342	A	12/2009
CN	1498029	B	5/2010
CN	101772929	A	7/2010
CN	101069390	B	12/2010
CN	102137024	A	7/2011
CN	102457494	A	5/2012
CN	102484656	A	5/2012
CN	102572123	A	7/2012
CN	101095329	B	10/2012
CN	101605342	B	12/2012
CN	102833232	A	12/2012
CN	101005503	B	1/2013
CN	101772929	B	7/2014
CN	102457494	B	10/2014
DE	602 01 827	T2	11/2005
DE	11 2005 003 306	T5	1/2008
DE	601 33 316	T2	7/2008
DE	603 17 751	T2	11/2008
EP	0 841 832	A2	5/1998
EP	0 841 832	A3	5/1999
EP	1 032 224	A2	8/2000
EP	1 032 224	A3	2/2001
EP	1 244 250	A1	9/2002
EP	1 266 516	A2	12/2002
EP	1 362 456	A2	11/2003
EP	1 371 173	A1	12/2003
EP	1 389 862	A1	2/2004
EP	1 411 743	A1	4/2004
EP	1 389 862	B1	11/2004
EP	1 526 697	A2	4/2005
EP	1 362 456	A4	5/2005
EP	1 575 327	A1	9/2005
EP	1 610 583	A1	12/2005
EP	1 526 697	A3	3/2006
EP	1 721 446	A1	11/2006
EP	1 829 300	A1	9/2007
EP	1 371 173	B1	11/2007
EP	1 411 743	B1	11/2007
EP	1 362 456	B1	3/2008
EP	1 974 304	A2	10/2008
EP	1 974 304	A4	10/2008
EP	1 610 583	B1	8/2009
EP	2 084 868	AO	8/2009
EP	2 090 024	AO	8/2009
EP	2 127 232	A1	12/2009
EP	2 165 489	A1	3/2010
EP	2 215 755	A1	8/2010
EP	2 227 048	A1	9/2010
EP	2 127 232	A4	3/2011
EP	2 165 489	A4	3/2011
EP	2 311 292		4/2011
EP	1 829 300	A4	5/2012
EP	2 449 749	A1	5/2012
EP	2 478 678		7/2012
EP	2 215 755	A4	10/2012
EP	1 829 300	B1	11/2012
EP	2 449 749	B1	3/2014
EP	1 266 516	B1	5/2014
GB	2 332 337	A	6/1999
ID	W00200902627		9/2009
IN	24/2009		6/2009
IN	29/2009		7/2009
IN	287412		9/2017
JP	2011-199384	A	10/2011
KR	10-2009-0086428	A	8/2009
KR	10-2009-0095621	A	9/2009
MX	2009004811	A	8/2009
MX	2009005751	A	8/2009
SG	151991	A1	6/2009
SG	152752	A1	6/2009
SG	155474		10/2009
WO	WO 01/50693	A1	7/2001
WO	WO 01/69899	A2	9/2001
WO	WO 01/69899	A3	9/2001
WO	WO 01/80587	A1	10/2001
WO	WO 01/89145	A2	11/2001
WO	WO 02/082728	A1	10/2002
WO	WO 02/082782	A2	10/2002
WO	WO 02/082782	A3	10/2002
WO	WO 03/027801	A2	4/2003
WO	WO 2004/008786	A1	1/2004
WO	WO 2005/084002	A1	9/2005
WO	WO 2006/067269	A1	6/2006
WO	WO 2006/072099	A1	7/2006
WO	WO 2006/078175	A2	7/2006
WO	WO 2006/078175	A3	7/2006
WO	WO 2007/044454	A2	4/2007
WO	WO 2007/056158	A2	5/2007
WO	WO 2007/087077	A2	8/2007
WO	WO 2007/087077	A3	8/2007
WO	WO 2008/027065	A1	3/2008
WO	WO 2008/052340	A1	5/2008
WO	WO 2008/064481	A1	6/2008
WO	WO 2008/085614	A2	7/2008
WO	WO 2008/085614	A3	7/2008
WO	WO 2008/086350	A2	7/2008
WO	WO 2008/086350	A3	7/2008
WO	WO 2008/103652	A1	8/2008
WO	WO 2008/116296	A1	10/2008
WO	WO 2008/085614	A8	12/2008
WO	WO 2008/151406	A1	12/2008
WO	WO 2008/151406	A8	12/2008
WO	WO 2009/070202	A1	6/2009
WO	WO 2009/070278	A1	6/2009
WO	WO 2010/012090	A2	2/2010
WO	WO 2011/000405	A1	1/2011
WO	WO 2011/032256	A1	3/2011
WO	WO 2013/013189	A2	1/2013
WO	WO 2013/120069	A1	8/2013
WO	WO 2014/066155	A2	5/2014
WO	WO 2014/117599	A1	8/2014
WO	WO 2014/166258	A1	10/2014

OTHER PUBLICATIONS

Baker et al., "Cisco Support for Lawful Intercept in IP Networks," Internet Draft—working document of the Internet Engineering Task Force (IETF), accessible at http://www.ietf.org/ietf/lid-abstracts.txt, Apr. 2003, expires Sep. 30, 2003, pp. 1-15.

F. Baker et al. "RFC 3924—Cisco Architecture for Lawful Intercept in IP Networks." Oct. 2004.

Bhushan et al., "Federated Accounting: Service Charging and Billing in a Business-to-Business Environment," 0-7803-6719-7/01, © 2001 IEEE, pp. 107-121.

(56) **References Cited**

OTHER PUBLICATIONS

Cisco. "*Lawful Intercept Requirements Summary*." http://www.faqs.org/rfcs/rfc3924.html. Nov. 8, 2006.
DOTS IP Address Validation, "Overview", http://www.serviceobjects.com/products/dots_ipgeo.asp; printed Jun. 21, 2012.
DOTS Phone Exchange, "Overview", http://www.serviceobjects.com/demos/PhoneExchangeDemo.asp (URL no longer valid, current URL is http://www.serviceobjects.com/products/phone/phone-exchange); printed Jun. 21, 2012.
ETSI Technical Specification. "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery; Part 5: Service-specific details for IP Multimedia Services." Apr. 2008, 25 pgs, v.2.3.1, France.
Handley, M. et al. "RFC 2543—SIP: Session Initiation Protocol." Mar. 1999.
IETF ENUM WG R Stastny OEFEG Informational Numbering for Voip and Other IP Communications: "Numbering for ViOP and other IP Communications, draft-stastny-enum-numbering-voip-00.txt", Oct. 1, 2003, Oct. 1, 2003, pp. 1-43, XP015035676, ISSN: 0000-0004.
IP2Location, http://www.ip2location.com/; printed Jun. 20, 2012.
ETSI TS 122 173 V12.7.0 (Oct. 2014) Digital cellular telecommunications system (Phase 2+); Technical Specification 8.2.2.3—Interoperability with PSTN/ISDN and mobile CS Networks, Contents and Forward, pp. 1-9; Sec. 8, pp. 14-17.
Huitema et al., "Architecture for Internet Telephony Service for Residential Customers," Academic Paper for *Bellcore*, Mar. 2, 1999, pp. 1-14.
Jajszczyk et al., "Emergency Calls in Flow-Aware Networks," *IEEE Communications Letters*, vol. 11, No. 9, Sep. 2007, pp. 753-755.
Ketchpel et al. "U-PAI: A universal payment application interface" *Second USENIX Workshop on Electronic Commerce Proceedings*, 1996-8, pp. 1-17.
Kim et al., "An Enhanced VoIP Emergency Services Prototype," *Proceedings of the 3rd International ISCRAM Conference* (*B. Van de Walle and M. Turoff, eds.*), Newark, NJ (USA), May 2006, pp. 1-8.
Kornfeld et al., "DVB-H and IP Datacast—Broadcast to Handheld Devices," *IEEE Transactions on Broadcasting*, vol. 53, No. 1, Mar. 2007, pp. 161-170.
Kortebi et al., "SINR-Based Routing in Multi-Hop Wireless Networks to Improve VoIP Applications Support," 1-4244-0667-6/07, ©2007 IEEE, pp. 491-496.
Lee et al., "VoIP Interoperation with KT-NGN," in *the 6th International Conference on Advanced Communication Technology*, Technical Proceedings, 2004, pp. 126-128, accompanied by Title and Contents—4 pages.
Lin et al., "Effective VoIP Call Routing in Wlan and Cellular Integration," *IEEE Communications Letters*, vol. 9, No. 10, Oct. 2005, pp. 874-876.
Lind AT&T S: "ENUM Call Flows for VoIP Interworking; draft-lind-enum-callflows-03.txt", Feb. 2, 2002, No. 3, Feb. 1, 2002, pp. 1-17, XP015004214, ISSN: 0000-0004.
List of North American Numbering Plan area codes, http://en.wikipedia.org/wiki/List_of_NANP_area_codes; printed Jun. 20, 2012.
Ma et al., "Realizing MPEG4 Video Transmission Based on Mobile Station over GPRS," 0-7803-9335X/05, ©2005 IEEE, pp. 1241-1244.
Mintz-Habib et al., "A VoIP Emergency Services Architecture and Prototype," {mm2571,asr,hgs,xiaotaow}@cs.columbia.edu, 0-7803-9428-3/05, © 2005 IEEE, pp. 523-528.
Moberg & Drummond, "MIME-Based Secure Peer-to-Peer Business Data Interchange Using HTTP, Applicability Statement 2 (AS2)," *Network Working Group, Request for Comments*: 4130, Category: Standards Track, Copyright © The Internet Society Jul. 2005, pp. 1-47.
Munir, Muhammad Farukh, "Study of an Adaptive Scheme for Voice Transmission on IP in a Wireless Networking Environment 802.11e," *Dept. of Networks and Distributed Computing, Ecole Superieure En Sciences Informatiques* (*ESSI*), Université De Nice, Jun. 2005, (pp. 1-35), pp. 1-11.
Rosenberg, et al.; "RFC 3261—SIP: Session Initiation Protocol", Jun. 2002.
Sippy SIP B2BUA. "About Sippy RTPproxy." http://www.rtpproxy.org. Jul. 15, 2009.
Sripanidkulchai et al., "Call Routing Management in Enterprise VoIP Networks," Copyright 2007 ACM 978-1-59593-788-9/07/0008, 6 pages.
Stallings, William, "The Session Initiation Protocol," *The Internet Protocol Journal*, vol. 6, No. 1, Mar. 2003, pp. 20-30.
Technical Report, "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Study into routeing of MT-SMs via the HPLMN (Release 7)," 3GPP TR 23.840 V0.1.0 (Feb. 2006), 13 pages.
Thernelius, Fredrik, "SIP, NAT, and Firewalls," Master's Thesis, Ericsson, Department of Teleinformatics, May 2000, pp. 1-69.
Townsley, et al.; "RFC 2661—Layer Two Tunneling Protocol 'L2TP' ", Aug. 1999.
Trad et al., "Adaptive VoIP Transmission over Heterogeneous Wired/Wireless Networks," *V. Roca and F. Rousseau* (*Eds.*): *MIPS 2004, LNCS 3311*, pp. 25-36, 2004, © Springer-Verlag Berlin Heidelberg 2004.
Wikipedia, "International mobile subscriber identity (IMSI)," http://en.wikipedia.org/wiki/IMSI, Jul. 16, 2013.
Wikipedia, "Roaming," http://en.wikipedia.org/wiki/Roaming, Jul. 16, 2013.
Yu et al., "Service-Oriented Issues: Mobility, Security, Charging and Billing Management in Mobile Next Generation Networks," *IEEE BcN2006*, 1-4244-0146-1/06, © 2006 IEEE, pp. 1-10.
International Search Report and Written Opinion of the International Searching Authority completed Jun. 6, 2008 for PCT/CA2008/000545.
International Search Report and Written Opinion of the International Searching Authority completed Feb. 6, 2008 for PCT/CA2007/001956.
International Preliminary Report on Patentability dated May 14, 2009 for PCT/CA2007/001956.
International Search Report and Written Opinion of the International Searching Authority completed Mar. 3, 2008 for PCT/CA2007/002150.
International Preliminary Report on Patentability dated Feb. 13, 2009 for PCT/CA2007/002150.
International Preliminary Report on Patentability and Written Opinion of the International Searching Authority dated Feb. 10, 2011 for PCT/CA2009/001062.
International Search Report and Written Opinion completed on Jun. 18, 2010 for PCT/CA2009/001317.
International Search Report and Written Opinion dated Mar. 12, 2010 for PCT/CA2009/001062.
International Preliminary Report on Patentability dated Sep. 29, 2009 for PCT/CA2008/000545.
International Preliminary Report on Patentability dated Mar. 20, 2012 for PCT/CA2009/001317.
Canadian Office Action dated Jan. 27, 2015 for Canadian Patent Application No. CA 2,681,984.
Canadian Office Action dated Nov. 18, 2015 for Canadian Patent Application No. CA 2,681,984.
Canadian Office Action dated Dec. 1, 2015 for Canadian Patent Application No. CA 2,812,174.
Canadian Office Action dated Jan. 22, 2016 for Canadian Patent Application No. CA 2,916,220.
Canadian Office Action dated Mar. 3, 2016 for Canadian Patent Application No. CA 2,670,510.
Canadian Office Action dated Jun. 8, 2016 for Canadian Patent Application No. CA 2,916,217.
Canadian Office Action dated Aug. 16, 2016 for Canadian Patent Application No. CA 2,681,984.
Canadian Office Action dated Mar. 31, 2017 for Canadian Patent Application No. CA 2,916,220.
Canadian Office Action dated Apr. 27, 2018 for Canadian Patent Application No. CA 2,916,220.
Canadian Office Action dated Nov. 7, 2014 for Canadian Patent Application No. CA 2,668,025.

(56) **References Cited**

OTHER PUBLICATIONS

Canadian Office Action dated May 14, 2018 for Canadian Patent Application No. CA 2,668,025.
Canadian Office Action dated May 29, 2017 for Canadian Patent Application No. CA 2,668,025.
Canadian Office Action dated Jun. 9, 2017 for Canadian Patent Application No. CA 2,916,217.
Canadian Office Action dated Aug. 2, 2017 for Canadian Patent Application No. CA 2,681,984.
Canadian Office Action dated Sep. 18, 2014 for Canadian Patent Application No. CA 2,670,510.
Canadian Office Action dated Aug. 18, 2015 for Canadian Patent Application No. CA 2,732,148.
Chinese Office Action dated Mar. 24, 2011 for Chinese Patent Application No. CN 200780049791.5.
Chinese Office Action dated Jun. 23, 2011 for Chinese Patent Application No. CN 200780049136.X.
Extended European Search Report dated Nov. 2, 2012 for European Application No. EP 07 855 436.7.
Extended European Search Report dated Dec. 20, 2013 for European Application No. EP 09 849 358.8.
Extended European Search Report dated Apr. 16, 2014 for European Patent Application No. EP 09 802 316.1.
Supplementary European Search Report for European Application No. 07 816 106, dated Jun. 18, 2012.
European Examination Report dated Nov. 26, 2015 for European Patent Application No. EP 07 816 106.4.
Communication for European Patent Application No. EP 07 816 106.4—Invitation pursuant to Article 94(3) and Rule 71(1) EPC dated Apr. 15, 2016. All pages.
European Examination Report dated Aug. 29, 2016 for European Patent Application No. EP 07 855 436.7.
Communication under Rule 71(3) EPC—Intention to Grant—dated Oct. 14, 2016 for European Patent Application No. EP 07 816 106.4.
European Examination Report dated May 12, 2017 for European Patent Application No. EP 09-802-316.1.
Extended European Search Report dated Jul. 5, 2018 for European Application No. 18 174 930.0.
European Examination Report and Summons to Oral Proceedings dated Jun. 4, 2018 for European Patent Application No. 07 855 436.7.
First Examination Report dated Dec. 9, 2015, India Patent Application No. 1047/MUMNP/2009, which corresponds to subject U.S. Appl. No. 14/802,929.
Indian Office Action dated Jun. 21, 2017 for Indian Patent Application No. IN 1227/MUMNP/2009.
Intimation of the grant and recordal of India Patent No. 28/7412 entitled "Producing Routing Messages for Voice Over IP Communications", dated Sep. 15, 2017, for India Patent Application No. IN 1047/MUMNP/2009 filed Nov. 1, 2007.
Indonesian Examination Report dated Jul. 5, 2012 for Indonesian Patent Application No. W-00200901414.
Indonesian Examination Report dated Feb. 8, 2013 for Indonesian Patent Application No. W-00200901165.
Mexican Exam Report dated Jul. 11, 2011 for Mexican Patent Application No. MX/a/2009/004811.
Mexican Notice of Allowance dated Sep. 2, 2011 for Mexican Patent Application No. MX/a/2009/005751.
Document Title: Complaint for Patent Infringement [Jury Demand] ; Case Title: *Voip-Pal.Com, Inc.*, a Nevada corporation, Plaintiff, v. *Verizon Wireless Services, LLC*, a Delaware limited liability corporation; Verizon Communications, Inc., a Delaware corporation; AT&T, Inc., a Delaware corporation; AT&T Corp., a Delaware corporation; and Does I through X, inclusive, Defendants; Case No: 2:16-CV-00271; Court: United States District Court District of Nevada. Attachments: Table of Exhibits; Exhibit A; Exhibit B; Exhibit C; Exhibit D; Exhibit E; Chart 1 to Exhibit E; Chart 2 to Exhibit E; Chart 3 to Exhibit E; Chart 4 to Exhibit E; Chart 5 to Exhibit E; Chart 6 to Exhibit E; Exhibit F; Chart 1 to Exhibit F; Chart 2 to Exhibit F; Chart 3 to Exhibit F; Chart 4 to Exhibit F; Chart 5 to Exhibit F; Chart 6 to Exhibit F; Exhibit G; Exhibit H; and Addendum 1 to Exhibit H.
Document Title: Complaint for Patent Infringement [Jury Demand] ; Case Title: *Voip-Pal.Com, Inc.*, a Nevada corporation, Plaintiff, v. *Apple, Inc.*, a California corporation; Defendants; Case No: 2:16-CV-00260; Court: United States District Court District of Nevada. Attachments: Table of Exhibits; Exhibit A; Exhibit B; Exhibit C; Exhibit D; Chart 1 to Exhibit D; Chart 2 to Exhibit D; Chart 3 to Exhibit D; Chart 4 to Exhibit D; Exhibit E; Exhibit F; and Addendum 1 to Exhibit F.
Letter dated Nov. 30, 2015, from VoIP-Pal.com Inc. giving notice and inviting the company listed herein below to contact VoIP-Pal.com about U.S. Pat. Nos. 9,179,005 and 8,542,815 and related patents listed in the accompanying Attachment A. Sent to the following company: Apple Inc. In the U.S.
Letter dated Dec. 1, 2015, from VoIP-Pal.com Inc. giving notice and inviting the company listed herein below to contact VoIP-Pal.com about U.S. Pat. Nos. 9,179,005 and 8,542,815 and related patents listed in the accompanying Attachment A. Sent to the following company: Verizon Communications in the U.S.
Letters dated Dec. 18, 2015, from VoIP-Pal.com Inc. giving notice and inviting the companies listed herein below to contact VoIP-Pal.com about U.S. Pat. Nos. 9,179,005 and 8,542,815 and related patents listed in the accompanying Attachment A. (Please Note: Attachment A is attached here only to the first letter.) Sent to the following companies: Airtel in India; Alcatel-Lucent in France; Avaya Inc. In the U.S.; AT&T in the U.S.; Blackberry in Canada; Cable One in the U.S.; CenturyLink in the U.S.; Charter Communications in the U.S.; Cisco Systems in the U.S.; Comcast in the U.S.; Cox Communications in the U.S.; Cricket Wireless in the U.S.; Facebook in the U.S.; Freedom Pop in the U.S.; Frontier Communications in the U.S.; Google Inc. In the U.S.; HP in the U.S.; Juniper Networks in the U.S.; LoopPay, Inc. In the U.S.; Magic Jack in the U.S.; MetroPCS in the U.S.; Ooma in the U.S.; PayPal in the U.S.; Republic Wireless in the U.S.; Rok Mobile in the U.S.; Samsung Electronics—America in the U.S.; ShoreTel, Inc. In the U.S.; Siemens in Germany; Skype USA in the U.S.; Sprint in the U.S.; Square Cash in the U.S.; Suddenlink Communications in the U.S.; Talktone in the U.S.; Tango in the U.S.; Time Warner Cable in the U.S.; T-mobile in the U.S.; Twitter in the U.S.; US Cellular in the U.S.; Venmo in the U.S.; Virgin Mobile USA in the U.S.; Vodafone in the UK; and Vonage in the U.S.
Letters dated Jan. 4, 2016, from VoIP-Pal.com Inc. giving notice and inviting the companies listed herein below to contact VoIP-Pal.com about U.S. Pat. Nos. 9,179,005 and 8,542,815 and related patents listed in the accompanying Attachment A. (Please Note: Attachment A is attached here only to the first letter.) Sent to the following companies: Rogers Communications Inc. In Canada; Shaw Cable in Canada; Walmart in Alaska; and WIND Mobile in Canada.
Letters dated Jan. 21, 2016, from VoIP-Pal.com Inc. giving notice and inviting the companies listed herein below to contact VoIP-Pal.com about U.S. Pat. Nos. 9,179,005 and 8,542,815 and related patents listed in the accompanying Attachment A. (Please Note: Attachment A is attached here only to the first letter.) Sent to the following companies: Alibaba (China) Co., Ltd in China; Comwave Telecommunications in Canada; and Intel in the U.S.
Letters dated Feb. 2, 2016, from VoIP-Pal.com Inc. giving notice and inviting the companies listed herein below to contact VoIP-Pal.com about U.S. Pat. Nos. 9,179,005 and 8,542,815 and related patents listed in the accompanying Attachment A. (Please Note: Attachment A is attached here only to the first letter.) Sent to the following companies: Netflix Inc. in the U.S.; Skype Technologies in the U.S.; and WhatsApp Inc. In the U.S.
Document Title: Petition for *Inter Partes* Review of U.S. Pat. No. 8,542,815; United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Unified Patents Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner; IPR2016-01082; Patent 8,542,815; Producing Routing Messages for Voice Over IP Communications; Dated May 24, 2016. 64 sheets.
Document Title: Declaration of Michael Caloyannides; United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Unified Patents Inc.*, Petitioner v. *Voip-Pal.Com Inc.*,

(56) **References Cited**

OTHER PUBLICATIONS

Patent Owner; IPR2016-01082; U.S. Pat. No. 8,542,815; Producing Routing Messages for Voice Over IP Communications; Signed May 23, 2016; Filed May 24, 2016. 84 sheets.

Document Title: Public Switched Telephone Networks: A Network Analysis of Emerging Networks; Daniel Livengood, Jijun Lin and Chintan Vaishnav; Engineering Systems Division; Massachusetts Institute of Technology; Submitted May 16, 2006; to Dan Whitney, Joel Moses and Chris Magee. 27 sheets.

Document Title: A Brief History of VoIP; Document One—The Past; Joe Hallock; joe@sitedifference.com; date on cover page Nov. 26, 2004; Evolution and Trends in Digital Media Technologies—COM 538; Masters of Communication in Digital Media; University of Washington. 17 sheets.

Document Title: Petitioner's Voluntary Interrogatory Responses; United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Unified Patents Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner; IPR20161082; U.S. Pat. No. 8,542,815; Producing Routing Messages for Voice Over IP Communications; Signed and Filed not later than May 24, 2016. 8 sheets.

Document Title: VoIP-Pal, The World is Calling!, "Over $7 Billion in Lawsuits File by *Voip-Pal.com Inc.* vs *Apple*, Verizon and AT&T for Various Patent Infringements," *Business Wire®, A Berkshire Hathaway Company*, Feb. 11, 2016. 2 sheets.

Document Title: United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner; Case No. TBD, U.S. Pat. No. 9,179,005; Petition for *Inter Partes* Review of U.S. Pat. No. 9,179,005; Dated Jun. 15, 2016. 70 sheets.

Document Title: in the United States Patent and Trademark Office; Petition for *Inter Partes* Review Pursuant to 37 C.F.R. §42.100 ET SEQ.; In re U.S. Pat. No. 9,179,005; Currently in Litigation Styled: *VoIP-Pal.com, Inc.* v. *Apple Inc.*, Case No: 2:16-cv-00260-RFB-VCF; Issued: Nov. 3, 2015; Application Filed: Aug. 13, 2013; Applicant: Clay Perreault, et al.; Title: Producing Routing Messages for Voice Over IP Communications; Declaration of Henry H. Houh, PhD; Signed Jun. 14, 2016. 143 sheets.

Document Title: United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner; Case No. TBD, U.S. Pat. No. 8,542,815; Petition for *Inter Partes* Review of U.S. Pat. No. 8,542,815; Dated Jun. 15, 2016. 67 sheets.

Document Title: in the United States Patent and Trademark Office; Petition for *Inter Partes* Review Pursuant to 37 C.F.R. §42.100 ET SEQ.; in re U.S. Pat. No. 8,542,815; Currently in Litigation Styled: *VoIP-Pal.com, Inc.* v. *Apple Inc.*, Case No: 2:16-cv-00260-RFB-VCF; Issued: Sep. 24, 2013; Application Filed: Nov. 1, 2007; Applicant: Clay Perreault, et al.; Title: Producing Routing Messages for Voice Over IP Communications; Declaration of Henry H. Houh, PhD; Signed Jun. 14, 2016. 143 sheets.

Complaint for Patent Infringement, United States District Court, District of Nevada, Case No. 2:16-cv-2338, *Voip-Pal.Com, Inc.*, a Nevada corporation, Plaintiff v. *Twitter, Inc.*, a California corporation, Defendant, Filed Oct. 6, 2016, 8 pages.

Civil Docket for Case #: 2:16-cv-02338-RFB-CWH, United States District Court, District of Nevada (Las Vegas), *Voip-Pal.com, Inc.* v. *Twitter, Inc.*, Date Filed: Oct. 6, 2016, 2 pages.

Table of Exhibits, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, 1 page.

Exhibit A, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, U.S. Pat. No. 8,542,815 B2, Issued Sep. 24, 2013, to Clay Perrault et al., 60 pages.

Exhibit B, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, U.S. Pat. No. 9,179,005 B2, Issued Nov. 3, 2015, to Clay Perrault et al., 63 pages.

Exhibit C, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, Letter dated Dec. 18, 2015 giving notice of U.S. Pat. Nos. 8,542,815 B2; 9,179,005 B2; and related Patents listed in Attachment A, 4 pages.

Exhibit D, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, Asserted Claims and Infringement Conditions, United States District Court, District of Nevada, *Voip-Pal.Com, Inc.*, a Nevada corporation, Plaintiff v. *Twitter, Inc.*, a California corporation, Defendants, 6 pages.

Chart 1 to Exhibit D, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, Chart 1, Asserted Claims and Infringement Conditions Concerning U.S. Pat. No. 8,542,815, United States District Court, District of Nevada, *Voip-Pal.Com, Inc.*, a Nevada corporation, Plaintiff v. *Twitter, Inc.*, a California corporation, Defendants, 20 pages.

Chart 2 to Exhibit D, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, Chart 2, Asserted Claims and Infringement Conditions Concerning U.S. Pat. No. 9,179,005, United States District Court, District of Nevada, *Voip-Pal.Com, Inc.*, a Nevada corporation, Plaintiff v. *Twitter, Inc.*, a California corporation, Defendants, 28 pages.

Exhibit E, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, VPLM Active U.S. Patent Matters as of Oct. 1, 2016, 2 pages.

Exhibit F, Case 2:16-cv-02338-RFB-CWH, Filed Oct. 6, 2016, Twitter Royalty Monetization Analysis Overview, 4 pages.

Patent Owner's Preliminary Response, Case No. IPR2016-01082, U.S. Pat. No. 8,542,815, *Unified Patents Inc.*, Petitioner, v. *Voip-Pal.Com Inc.*, Patent Owner, Filing Date: Aug. 26, 2016, 80 pages.

Voip-Pal.com, Inc. Exhibit 2001, Comparison of portions of Petition with portions of Declaration, IPR2016-01082, *Unified Patents* v. *Voip-Pal*, Filing Date: Aug. 26, 2016, 9 pages.

Patent Owner's Preliminary Response to Petition for *Inter Partes* Review, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com Inc.*, Patent Owner, Filing Date: Sep. 19, 2016, 74 pages.

Voip-Pal.com, Inc. Exhibit 2001, Comparison of Petition (Ground 1) with Petition (Ground 2), IPR2016-01201, *Apple* v. *Voip-Pal*, Filing Date: Sep. 19, 2016, 19 pages.

Patent Owner's Preliminary Response to Petition for *Inter Partes* Review, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com Inc.*, Patent Owner, Filing Date: Sep. 21, 2016, 74 pages.

Voip-Pal.com, Inc. Exhibit 2001, Comparison of Petition (Ground 1) with Petition (Ground 2), IPR2016-01198, *Apple* v. *Voip-Pal*, Filing Date: Sep. 21, 2016, 21 pages.

Decision: Denying Institution of *Inter Partes* Review, 37 C.F.R. § 42.108, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Unified Patents Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner, Case IPR2016-01082, U.S. Pat. 8,542,815 B2, Paper 8, Entered: Nov. 18, 2016.

Decision: Institution of *Inter Partes* Review, 37 C.F.R. § 42.108, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner, Case IPR2016-01201, U.S. Pat. No. 8,542,815 B2, Paper 6, Entered: Nov. 21, 2016.

Decision: Institution of *Inter Partes* Review, 37 C.F.R. § 42.108, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner, Case IPR2016-01198, U.S. Pat. No. 9,179,005 B2, Paper 6, Entered: Nov. 21, 2016.

Scheduling Order: United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner, Cases IPR2016-01201, IPR2016-01198, U.S. Pat. No. 8,542,815 B2, U.S. Pat. No. 9,179,005 B2, Paper 7, Entered: Nov. 21, 2016.

Patent Owner Response to Petition, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Filed: Feb. 10, 2017, 76 pages.

Patent Owner Updated Exhibit List, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Filed: Feb. 10, 2017, 6 pages.

Voip-Pal Ex. 2002, IPR2016-01201, "Declaration of Ryan Thomas in Support of Pro HAC Vice Motion," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S.

(56) **References Cited**

OTHER PUBLICATIONS

Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 20, 2017, 4 pages.

Voip-Pal Ex. 2003, IPR2016-01201, "Technical Review of Digifonica VoIP System," Digifonica, Global Telephone Solutions, Author: John Rutter, Stuart Gare, Version V0.7 (Draft), Date: May 7, 2005, 35 pages.

Voip-Pal Ex. 2004, IPR2016-01201, Memo—"Subject: Smart 421 Contract signed and Faxed," From: Clay S. Perreault, Date: Jun. 6, 2005, 8:53 AM, to: Steve Nicholson, et al., 2 pages.

Voip-Pal Ex. 2005, IPR2016-01201, Memo—"Subject: Digifonica TEchnology review," From: Clay Perreault, Date: Jun. 6, 2005, 5:37 PM; to: John Rutter, et al., 5 pages.

Voip-Pal Ex. 2006, IPR2016-01201, Memo—"Subject: Re: Sample code for review Next document upload complete," From: Clay Perreault, Date: Jun. 15, 2005, 3:28 PM, to: John Rutter, et al., 3 pages.

Voip-Pal Ex. 2007, IPR2016-01201, DigiFonica International Inc Memo—"[Fwd: Digifonica Technical Review—draft report]," From Clay Perreault, to: Rod Thomson, et al., Tue, Jul. 5, 2005 at 4:45 PM, 2 pages.

Voip-Pal Ex. 2008, IPR2016-01201, John Rutter—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 31, 2017, 4 pages.

Voip-Pal Ex. 2009, IPR2016-01201, Stuart Gare—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 2, 2017, 4 pages.

Voip-Pal Ex. 2010, IPR2016-01201, Pentti Kalevi Huttunen—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 3, 2017, 4 pages.

Voip-Pal Ex. 2011, IPR2016-01201, Ryan Purita—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 31, 2017, 3 pages.

Voip-Pal Ex. 2012, IPR2016-01201, Johan Emil Viktor Bjorsell—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 9, 2017, 9 pages.

Voip-Pal Ex. 2013, IPR2016-01201, Clay Perreault—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 8, 2017, 6 pages.

Voip-Pal Ex. 2014, IPR2016-01201, RBR Source Code, Version 361, "call_e164.class.php RBR Version 361, Jun. 6, 2005 09:22:59," 45 pages.

Voip-Pal Ex. 2015, IPR2016-01201, RBR Source Code Log for Trunk Directory, "r1879 | cdelalande | Oct. 31, 2006 17:07:46 -0800 (Tue, Oct. 31, 2006) | 3 lines," 56 pages.

Voip-Pal Ex. 2016, IPR2016-01201, William Henry Mangione-Smith—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 10, 2017, 82 pages.

Voip-Pal Ex. 2017, IPR2016-01201, DF DigiFonica International Inc Memo—"notes from your presentation, 1 message" From Konstantin Kropivny, To: Emil Björsell, Tue, Jun. 14, 2005 at 7:33PM, 4 pages.

Voip-Pal Ex. 2018, IPR2016-01201, David Terry—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 8, 2017, 5 pages.

Voip-Pal Ex. 2019, IPR2016-01201, DF DigiFonica International Inc Memo—"Software release 10:30 am PST—11:00am PST for Aug. 25, 2005. 1 message" From Samantha Edwards, to: everyone@digifonica.com, Wed., Aug. 24, 2005 at 4:02 PM, 8 pages.

Voip-Pal Ex. 2020, IPR2016-01201, "Next Generation Networks—A Migration Path Digifonica Voice Over IP Technologies. Technology Overview, Draft Jun. 3, 2005, Not for Distribution," by Clay S Perreault, CEO / CTO, Digifonica International Ltd, Gibraltar, 45 pages.

Voip-Pal Ex. 2021, IPR2016-01201, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::Salm Rev 341, RBR Rev 341 added, 1 message" Fuad A. To: E. Björsell, Tue, May 31, 2005 at 1:13 PM, 1 page.

Voip-Pal Ex. 2022, IPR2016-01201, DF DigiFonica International Inc Memo—"Salm Rev 341, RBR Rev 341, 2 messages" Emil Björsell to: Fuad, et al., Tue, May 31, 2005 at 2:38 and 2:44 PM, 1 page.

Voip-Pal Ex. 2023, IPR2016-01201, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Roll out Rev 353 added, 1 message" Fuad A. To: E. Björsell, Thu, Jun. 2, 2005 at 1:12 PM, 1 page.

Voip-Pal Ex. 2024, IPR2016-01201, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Roll out Rev 358 added, 1 message" Fuad A. To: E. Björsell, Sun, Jun. 5, 2005 at 1:18 PM, 1 page.

Voip-Pal Ex. 2025, IPR2016-01201, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Roll out Rev 361 updated, 1 message" Fuad A. To: E. Björsell, Mon., Jun. 6, 2005 at 9:26 AM, 1 page.

Voip-Pal Ex. 2026, IPR2016-01201, DF DigiFonica International Inc Memo—"RBR Roll out Rev 361, 1 message" David Terry to: Fuad, et al., Mon., Jun. 6, 2005 at 9:33 AM, 1 page.

Voip-Pal Ex. 2027, IPR2016-01201, Df DigiFonica International Inc Memo—"RBR Roll out Rev 361, 1 message" Emil Björsell to: Fuad, et al., Mon., Jun. 6, 2005 at 11:33 AM, 1 page.

Voip-Pal Ex. 2030, IPR2016-01201, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Rev 541 updated, 1 message" Fuad A. To: E. Björsell, Thu, Aug. 4, 2005 at 11:57 AM, 1 page.

Voip-Pal Ex. 2031, IPR2016-01201, DF DigiFonica International Inc Memo—"RBR Rev 541, 1 message" David Terry to: Fuad, et al., Thu, Aug. 4, 2005 at 1:58 PM, 1 page.

Voip-Pal Ex. 2032, IPR2016-01201, DF DigiFonica International Inc Memo—"RBR Rev 541, 1 message" Emil Björsell to: Fuad, et al., Thu, Aug. 4, 2005 at 3:59 PM, 1 page.

Voip-Pal Ex. 2033, IPR2016-01201, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Roll out Rev 554 added, 1 message" Fuad A. To: Emil Björsell, Mon, Aug. 8, 2005 at 10:55 AM, 1 page.

Voip-Pal Ex. 2034, IPR2016-01201, DF DigiFonica International Inc Memo—"RBR Roll out Rev 554, 2 messages" David Terry to: Fuad, et al., Mon, Aug. 8, 2005 at 11:48 AM and 12:00 PM, 1 page.

Voip-Pal Ex. 2035, IPR2016-01201, DF DigiFonica International Inc Memo—"RBR Roll out Rev 554, 1 message" Emil Björsell to: Fuad, et al., Mon, Aug. 8, 2005 at 12:09 PM, 1 page.

Voip-Pal Ex. 2036, IPR2016-01201, DF DigiFonica International Inc Memo—"Digifonica : RBR and Salma Deployment," Samantha Edwards to: everyone@digifonica.com, Mon, Aug. 8, 2005 at 4:12 PM, 4 pages.

Voip-Pal Ex. 2042, IPR2016-01201, DF DigiFonica International Inc Memo—"RBR Roll out Rev 693⇒ 694, 1 message" Chris Huff to: Fuad, et al., Tue, Aug. 23, 2005 at 1:33 PM, 1 page.

(56) **References Cited**

OTHER PUBLICATIONS

Voip-Pal Ex. 2043, IPR2016-01201, "Deposition of Henry H. Houh, Ph.D., vol. I, Taken on Behalf of the Patent Owner," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 25, 2017, 128 pages.

Voip-Pal Ex. 2044, IPR2016-01201, "Deposition of Henry H. Houh, Ph.D., Volume II, Taken on Behalf of the Patent Owner," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 26, 2017, 158 pages.

Voip-Pal Ex. 2045, IPR2016-01201, Curriculum Vitae of William Henry Mangione-Smith, Ph.D., 23 pages.

Voip-Pal Ex. 2046, IPR2016-01201, U.S. Pat. No. 3,725,596, Issued Apr. 3, 1973, Rodney Robert Maxon et al., 18 pages.

Voip-Pal Ex. 2047, IPR2016-01201, "Merlin® Communications System, Centrex/PBS Connection," Lucent Technologies, Bell Labs Innovations, © 1984 AT&T, 999-500-138 IS, Issue 1, Mar. 1985, 26 pages.

Voip-Pal Ex. 2048, IPR2016-01201, "Telephone Features," Quick Reference Guide, Definity, Rockefeller Group, Telecommunications Services, Inc., 2000, 2 pages.

Voip-Pal Ex. 2049, IPR2016-01201, Valdar, Andy, *Understanding Telecommunications Networks*, © 2006 the Institution of Engineering and Technology, London, UK, Title page, copyright page, pp. 38-39.

Voip-Pal Ex. 2050, IPR2016-01201, Horak, Ray, "Webster's New World® Telecom Dictionary," © 2008 by Wiley Publishing, Inc., Indianapolis, Indiana, Title page, copyright page, p. 133.

Patent Owner Response to Petition, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Filed: Feb. 10, 2017, 78 pages.

Patent Owner Updated Exhibit List, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Filed: Feb. 10, 2017, 6 pages.

Voip-Pal Ex. 2002, IPR2016-01198, "Declaration of Ryan Thomas in Support of Pro HAC Vice Motion," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 20, 2017, 4 pages.

Voip-Pal Ex. 2003, IPR2016-01198, "Technical Review of Digifonica VoIP System," Digifonica, Global Telephone Solutions, Author: John Rutter, Stuart Gare, Version V0.7 (Draft), Date: May 7, 2005, 35 pages.

Voip-Pal Ex. 2004, IPR2016-01198, Memo—"Subject: Smart 421 Contract signed and Faxed," From: Clay S. Perreault, Date: Jun. 6, 2005, 8:53 AM, to: Steve Nicholson, et al., 2 pages.

Voip-Pal Ex. 2005, IPR2016-01198, Memo—"Subject: Digifonica TEchnology review," From: Clay Perreault, Date: Jun. 6, 2005, 5:37 PM; To: John Rutter, et al., 5 pages.

Voip-Pal Ex. 2006, IPR2016-01198, Memo—"Subject: Re: Sample code for review Next document upload complete," From: Clay Perreault, Date: Jun. 15, 2005, 3:28 PM, to: John Rutter, et al., 3 pages.

Voip-Pal Ex. 2007, IPR2016-01198, DigiFonica International Inc Memo—"[Fwd: Digifonica Technical Review—draft report]," From Clay Perreault, to: Rod Thomson, et al., Tue, Jul. 5, 2005 at 4:45 PM, 2 pages.

Voip-Pal Ex. 2008, IPR2016-01198, John Rutter—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 31, 2017, 4 pages.

Voip-Pal Ex. 2009, IPR2016-01198, Stuart Gare—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 2, 2017, 4 pages.

Voip-Pal Ex. 2010, IPR2016-01198, Pentti Kalevi Huttunen—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 3, 2017, 4 pages.

Voip-Pal Ex. 2011, IPR2016-01198, Ryan Purita—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 31, 2017, 3 pages.

Voip-Pal Ex. 2012, IPR2016-01198, Johan Emil Viktor Bjorsell—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 9, 2017, 9 pages.

Voip-Pal Ex. 2013, IPR2016-01198, Clay Perreault—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 8, 2017, 6 pages.

Voip-Pal Ex. 2014, IPR2016-01198, RBR Source Code, Version 361, "call_e164.class.php RBR Version 361, Jun. 6, 2005 09:22:59," 45 pages.

Voip-Pal Ex. 2015, IPR2016-01198, RBR Source Code Log for Trunk Directory, "r1879 | cdelalande | Oct. 31, 2006 17:07:46 -0800 (Tue, Oct. 31, 2006) | 3 lines," 56 pages.

Voip-Pal Ex. 2016, IPR2016-01198, William Henry Mangione-Smith—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 10, 2017, 96 pages.

Voip-Pal Ex. 2017, IPR2016-01198, DF DigiFonica International Inc Memo—"notes from your presentation, 1 message" From Konstantin Kropivny, to: Emil Björsell, Tue, Jun. 14, 2005 at 7:33PM, 4 pages.

Voip-Pal Ex. 2018, IPR2016-01198, David Terry—"Declaration in Support Patent Owner Response to Inter Partes Petition," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Feb. 8, 2017, 5 pages.

Voip-Pal Ex. 2019, IPR2016-01198, DF DigiFonica International Inc Memo—"Software release 10:30 am PST—11:00am PST for Aug. 25, 2005. 1 message" From Samantha Edwards, to: everyone@digifonica.com, Wed., Aug. 24, 2005 at 4:02 PM, 8 pages.

Voip-Pal Ex. 2020, IPR2016-01198, "Next Generation Networks—A Migration Path Digifonica Voice Over IP Technologies. Technology Overview, Draft Jun. 3, 2005, Not for Distribution," by Clay S Perreault, CEO / CTO, Digifonica International Ltd, Gibraltar, 45 pages.

Voip-Pal Ex. 2021, IPR2016-01198, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::Salm Rev 341, RBR Rev 341 added, 1 message" Fuad A. To: E. Björsell, Tue, May 31, 2005 at 1:13 PM, 1 page.

Voip-Pal Ex. 2022, IPR2016-01198, DF DigiFonica International Inc Memo—"Salm Rev 341, RBR Rev 341, 2 messages" Emil Björsell to: Fuad, et al., Tue, May 31, 2005 at 2:38 and 2:44 PM, 1 page.

(56) **References Cited**

OTHER PUBLICATIONS

Voip-Pal Ex. 2023, IPR2016-01198, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Roll out Rev 353 added, 1 message" Fuad A. To: E. Björsell, Thu, Jun. 2, 2005 at 1:12 PM, 1 page.
Voip-Pal Ex. 2024, IPR2016-01198, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Roll out Rev 358 added, 1 message" Fuad A. To: E. Björsell, Sun, Jun. 5, 2005 at 1:18 PM, 1 page.
Voip-Pal Ex. 2025, IPR2016-01198, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Roll out Rev 361 updated, 1 message" Fuad A. To: E. Björsell, Mon., Jun. 6, 2005 at 9:26 AM, 1 page.
Voip-Pal Ex. 2026, IPR2016-01198, DF DigiFonica International Inc Memo—"RBR Roll out Rev 361, 1 message" David Terry to: Fuad, et al., Mon., Jun. 6, 2005 at 9:33 AM, 1 page.
Voip-Pal Ex. 2027, IPR2016-01198, DF DigiFonica International Inc Memo—"RBR Roll out Rev 361, 1 message" Emil Björsell to: Fuad, et al., Mon., Jun. 6, 2005 at 11:33 AM, 1 page.
Voip-Pal Ex. 2030, IPR2016-01198, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Rev 541 updated, 1 message" Fuad A. To: E. Björsell, Thu, Aug. 4, 2005 at 11:57 AM, 1 page.
Voip-Pal Ex. 2031, IPR2016-01198, DF DigiFonica International Inc Memo—"RBR Rev 541, 1 message" David Terry to: Fuad, et al., Thu, Aug. 4, 2005 at 1:58 PM, 1 page.
Voip-Pal Ex. 2032, IPR2016-01198, DF DigiFonica International Inc Memo—"RBR Rev 541, 1 message" Emil Björsell to: Fuad, et al., Thu, Aug. 4, 2005 at 3:59 PM, 1 page.
Voip-Pal Ex. 2033, IPR2016-01198, DF DigiFonica International Inc Memo—"Software roll out for supernodes.::RBR Roll out Rev 554 added, 1 message" Fuad A. To: Emil Björsell, Mon, Aug. 8, 2005 at 10:55 AM, 1 page.
Voip-Pal Ex. 2034, IPR2016-01198, DF DigiFonica International Inc Memo—"RBR Roll out Rev 554, 2 messages" David Terry to: Fuad, et al., Mon, Aug. 8, 2005 at 11:48 AM and 12:00 PM, 1 page.
Voip-Pal Ex. 2035, IPR2016-01198, DF DigiFonica International Inc Memo—"RBR Roll out Rev 554, 1 message" Emil Björsell to: Fuad, et al., Mon, Aug. 8, 2005 at 12:09 PM, 1 page.
Voip-Pal Ex. 2036, IPR2016-01198, DF DigiFonica International Inc Memo—"Digifonica : RBR and Salma Deployment," Samantha Edwards to: everyone@digifonica.com, Mon, Aug. 8, 2005 at 4:12 PM, 4 pages.
Voip-Pal Ex. 2042, IPR2016-01198, DF DigiFonica International Inc Memo—"RBR Roll out Rev 693⇒ 694, 1 message" Chris Huff to: Fuad, et al., Tue, Aug. 23, 2005 at 1:33 PM, 1 page.
Voip-Pal Ex. 2043, IPR2016-01198, "Deposition of Henry H. Houh, Ph.D., vol. I, Taken on Behalf of the Patent Owner," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 25, 2017, 128 pages.
Voip-Pal Ex. 2044, IPR2016-01198, "Deposition of Henry H. Houh, Ph.D., vol. II, Taken on Behalf of the Patent Owner," *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, Dated: Jan. 26, 2017, 158 pages.
Voip-Pal Ex. 2045, IPR2016-01198, Curriculum Vitae of William Henry Mangione-Smith, Ph.D., 23 pages.
Voip-Pal Ex. 2046, IPR2016-01198, U.S. Pat. No. 3,725,596, Issued Apr. 3, 1973, Rodney Robert Maxon et al., 18 pages.
Voip-Pal Ex. 2047, IPR2016-01198, "Merlin® Communications System, Centrex/PBS Connection," Lucent Technologies, Bell Labs Innovations, © 1984 AT&T, 999-500-138 IS, Issue 1, Mar. 1985, 26 pages.
Voip-Pal Ex. 2048, IPR2016-01198, "Telephone Features," Quick Reference Guide, Definity, Rockefeller Group, Telecommunications Services, Inc., 2000, 2 pages.
Voip-Pal Ex. 2049, IPR2016-01198, Valdar, Andy, *Understanding Telecommunications Networks*, © 2006 The Institution of Engineering and Technology, London, UK, Title page, copyright page, pp. 38-39.
Voip-Pal Ex. 2050, IPR2016-01198, Horak, Ray, "Webster's New World® Telecom Dictionary," © 2008 by Wiley Publishing, Inc., Indianapolis, Indiana, Title page, copyright page, p. 133.
Document Title: United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner; Case No. IPR2017-01399-815; U.S. Pat. No. 8,542,815; Petition for Inter Partes Review of U.S. Pat. No. 8,542,815; Dated May 9, 2017, 63 pages.
Petitioner Apple Inc. Exhibit 1003, Case No. IPR2017-01399-815; U.S. Pat. No. 8,542,815: U.S. Pat. No. 7,486,684 to Chu, et al., 59 pages.
Petitioner Apple Inc. Exhibit 1004, Case No. IPR2017-01399-815; U.S. Pat. No. 8,542,815: U.S. Pat. No. 6,760,324 to Scott, et al., 65 pages.
Petitioner Apple Inc. Exhibit 1005, Case No. IPR2017-01399-815; U.S. Pat. No. 8,542,815: Declaration of Henry H. Hough, PhD, 45 pages.
Petitioner Apple Inc. Exhibit 1006, Case No. IPR2017-01399-815; U.S. Pat. No. 8,542,815: U.S. Publication No. 2002/0122547 to Hinchey et al., 21 pages.
Document Title: United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. Patent of *Voip-Pal.Com Inc.*, Patent Owner; Case No. IPR2017-01398-005; U.S. Pat. No. 9,179,005; Petition for Inter Partes Review of U.S. Pat. No. 9,179,005; Dated May 9, 2017. 54 pages.
Petitioner Apple Inc. Exhibit 1006, Case No. IPR2017-01398-005; U.S. Pat. No. 9,179,005: U.S. Pat. No. 7,486,684 to Chu, et al., 59 pages.
Petitioner Apple Inc. Exhibit 1007, Case No. IPR2017-01398-005; U.S. Pat. No. 9,179,005: U.S. Pat. No. 6,760,324 to Scott, et al., 65 pages.
Petitioner Apple Inc. Exhibit 1008, Case No. IPR2017-01398-005; U.S. Pat. No. 9,179,005: Declaration of Henry H. Hough, PhD, 41 pages.
Petitioner Apple Inc. Exhibit 1009, Case No. IPR2017-01398-005; U.S. Pat. No. 9,179,005: U.S. Publication No. 2002/0122547 to Hinchey et al., 21 pages.
Document Title: in the United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner v. *Digifonica (International) Limited* Patent Owner, Case No. IPR2017-01382; U.S. Pat. No. 8,542,815; Petition for *Inter Partes* Review of U.S. Pat. No. 8,542,815; Dated May 8, 2017, 84 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner v. *Digifonica (International) Limited* Patent Owner, U.S. Pat. No. 8,542,815, *Inter Partes* Review No. IPR2017-01382; Declaration of James Bress in Support of Petition for *Inter Partes* Review of U.S. Pat. No. 8,542,815; with Appendices A through II, 2113 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix A, James R. Bress, Curriculum Vitae, 26 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix B, Chapter 5, Telecommunications Essentials, Lillian Goleniewski, © 2002, 40 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix C, Chapter 11, Telecommunications Essentials, Lillian Goleniewski, © 2002, 41 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix D, ITU-T Recommendation E.164 (May 1997), 27 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix E, Telcordia Notes on the Networks, SR-2275, Issue 4, Oct. 2000, pp. 3-8-3-14, 9 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix F, Chapter 4, Telecommunications Essentials, Lillian Goleniewski, © 2002, pp. 99-100, 4 pages.

(56) **References Cited**

OTHER PUBLICATIONS

Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix G, Telcordia Notes on the Networks, SR-2275, Issue 4, Oct. 2000, pp. 18-1-18-20, 22 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix H, Softswitch, Architecture for VoIP, Franklin D. Ohrtman, Jr., © 2003, Chapter 2, 32 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix I, Telecommunications Act of 1996, 104th Congress of the U.S.A., Jan. 1996, 128 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix J, Perspectives on the AIN Architecture, Berman et al., IEEE Communications Magazine, Feb. 1992, 6 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix K, U.S. Pat. No. 7,907,714 B2, to Baniak et al., 21 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix L, The IMS, Poikselkä & Mayer, © 2009, John Wiley & Sons Ltd, Chapter 1 Introduction, 14 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix M, the IMS, Poikselkä & Mayer, © 2009, John Wiley & Sons Ltd, pp. 24-25 and 86-94, 13 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix N, Chapter 9, Telecommunications Essentials, Lillian Goleniewski, © 2002, 42 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix O, Softswitch, Architecture for VoIP, Franklin D. Ohrtman, Jr., © 2003, pp. 238-239, 4 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix P, Softswitch, Architecture for VoIP, Franklin D. Ohrtman, Jr., © 2003, Chapter 4, pp. 67-86, 22 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix Q, Softswitch, Architecture for VoIP, Franklin D. Ohrtman, Jr., © 2003, Chapter 5, pp. 87-112, 28 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix R, Telecommunications Essentials, Lillian Goleniewski, © 2002, p. 221, 3 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix S, Network Working Group, RFC (Request for Comments): 1122, Internat Engineering Task Force, R. Braden, Ed., Oct. 1989, pp. 18-25, 9 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix T, RFC (Request for Comments): 791, Internet Protocol, Darpa Internet Program, Protocol Specification, Sep. 1981, by Information Sciences Institute, USC, 50 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix U, Network Working Group, RFC (Request for Comments): 1034, P. Mockapetris, ISI, Nov. 1987, pp. 155, 55 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix V, Network Working Group, RFC (Request for Comments): 1035, P. Mockapetris, ISI, Nov. 1987, pp. 155, 55 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix W, Network Working Group, RFC (Request for Comments): 3761, P. Faltstrom et al., Apr. 2004, pp. 1-18, 18 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix X, U.S. Pat. No. 6,594,254 B1, to Kelly, 18 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix Y, ITU-T Recommendation H.323 (Jul. 2003), 298 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix Z, Telcordia Notes on the Networks, SR-2275, Issue 4, Oct. 2000, pp. 6-306-6-309, 4 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix AA, Telcordia Notes on the Networks, SR-2275, Issue 4, Oct. 2000, pp. 14-10-14-13, 6 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix BB, The Internet Engineering Task Force (IETF®), May 5, 2017, 2 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix CC, Network Working Group, RFC (Request for Comments): 3261, J. Rosenberg et al., Jun. 2002, 269 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix DD, Network Working Group, RFC (Request for Comments): 3666, A. Johnston et al., Dec. 2003, 118 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix EE, Network Working Group, RFC (Request for Comments): 3665, A. Johnston et al., Dec. 2003, 94 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix FF, Network Working Group, RFC (Request for Comments): 2327, M. Handley et al., Apr. 1998, 42 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix GG, ITU-T Recommendation Q.931 (May 1998), 345 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix HH, Telcordia Notes on the Networks, SR-2275, Issue 4, Oct. 2000, pp. 14-76-14-77, 4 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, Case No. IPR2017-01382; Appendix II, Telcordia Notes on the Networks, SR-2275, Issue 4, Oct. 2000, p. 10-7, 3 pages.
Petitioner AT&T Services, Inc. Exhibit 1004, Case No. IPR2017-01382; James R. Bress, Curriculum Vitae, 26 pages.
Petitioner AT&T Services, Inc. Exhibit 1005, Case No. IPR2017-01382; U.S. Pat. No. 6,240,449, Issued May 29, 2001 to Raymond Nadeau, 13 pages.
Petitioner AT&T Services, Inc. Exhibit 1006, Case No. IPR2017-01382; U.S. Pat. No. 6,594,254 B1, Issued Jul. 15, 2003 to Keith C. Kelly, 18 pages.
Petitioner AT&T Services, Inc. Exhibit 1007, Case No. IPR2017-01382; U.S. Pat. No. 7,715,413 B2, Issued May 11, 2010, to Vaziri et al., 53 pages.
Petitioner AT&T Services, Inc. Exhibit 1008, Case No. IPR2017-01382; Decision, Institution of *Inter Partes* Review, 37 C.F.R. § 42.108, Paper 6, Entered Nov. 21, 2016, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com Inc.*, Patent Owner, Case IPR2016-01201, U.S. Pat. No. 8,542,815 B2, Before Barbara A. Benoit, Lynne E. Pettigrew, and Stacy B. Margolies, Administrative Patent Judges, 33 pages.
Petitioner AT&T Services, Inc. Exhibit 1009, Case No. IPR2017-01382; p. 221 and Chapter 11, Telecommunications Essentials, Lillian Goleniewski, © 2002, 44 pages.
Petitioner AT&T Services, Inc. Exhibit 1010, Case No. IPR2017-01382; RFC (Request for Comments): 791, Internet Protocol, Darpa Internet Program, Protocol Specification, Sep. 1981, by Information Sciences Institute, USC, 50 pages.
Petitioner AT&T Services, Inc. Exhibit 1011, Case No. IPR2017-01382; ITU-T Recommendation H.323 (Jul. 2003), 298 pages.
Petitioner AT&T Services, Inc. Exhibit 1012, Case No. IPR2017-01382; Telcordia Notes on the Networks, SR-2275, Issue 4, Oct. 2000, p. 10-7, 3 pages.
Document Title: In the United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner v. *Digifonica (International) Limited* Patent Owner, Case No. IPR2017-01383; U.S. Pat. No. 9,179,005; Petition for Inter Partes Review of U.S. Pat. No. 9,179,005; Dated May 8, 2017, 92 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, United States Patent and Trademark Office; Before The Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner v. *Digifonioa (International) Limited* Patent Owner, U.S. Pat. No. 9,179,005, *Inter Partes* Review No. IPR2017-01383; Declaration of James Bress in Support of Petition for *Inter Partes* Review of U.S. Pat. No. 9,179,005; with Appendices A through II, 2094 pages.
Petitioner AT&T Services, Inc. Exhibit 1004, Case No. IPR2017-01383; James R. Bress, Curriculum Vitae, 26 pages.
Petitioner AT&T Services, Inc. Exhibit 1005, Case No. IPR2017-01383; U.S. Pat. No. 6,240,449, Issued May 29, 2001 to Raymond Nadeau, 13 pages.
Petitioner AT&T Services, Inc. Exhibit 1006, Case No. IPR2017-01383; U.S. Publication No. 2004/0218748 A1, Published Nov. 4, 2004, by Stephen Fisher, 18 pages.

(56) **References Cited**

OTHER PUBLICATIONS

Petitioner AT&T Services, Inc. Exhibit 1007, Case No. IPR2017-01383; U.S. Pat. No. 6,594,254 B1, Issued Jul. 15, 2003, to Keith C. Kelly, 18 pages.
Petitioner AT&T Services, Inc. Exhibit 1008, Case No. IPR2017-01383; U.S. Pat. No. 6,674,850 B2, Issued Jan. 6, 2004, to Vu et al., 10 pages.
Petitioner AT&T Services, Inc. Exhibit 1009, Case No. IPR2017-01383; Decision, Institution of *Inter Partes* Review, 37 C.F.R. § 42.108, Paper 6, Entered Nov. 21, 2016, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com Inc.*, Patent Owner, Case IPR2016-01198, U.S. Pat. No. 9,179,005 B2, Before Barbara A. Benoit, Lynne E. Pettigrew, and Stacy B. Margolies, Administrative Patent Judges, 32 pags.
Petitioner AT&T Services, Inc. Exhibit 1010, Case No. IPR2017-01383; Patent Owner Response to Petition, Filed Feb. 10, 2017, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case IPR2016-01198, U.S. Pat. No. 9,179,005 B2, 78 pages.
Document Title: In the United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner v. *Digifonica (International) Limited* Patent Owner, Case No. IPR2017-01384; U.S. Pat. No. 9,179,005; Petition for *Inter Partes* Review of U.S. Pat. No. 9,179,005; Dated May 7, 2017, 70 pages.
Petitioner AT&T Services, Inc. Exhibit 1003, United States Patent and Trademark Office; Before The Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner v. *Digifonioa (International) Limited* Patent Owner, U.S. Pat. No. 9,179,005, *Inter Partes* Review No. IPR2017-01384; Declaration of James Bress in Support of Petition for *Inter Partes* Review of U.S. Pat. No. 9,179,005; with Appendices A through II, 2085 pages.
Petitioner AT&T Services, Inc. Exhibit 1004, Case No. IPR2017-01384; James R. Bress, Curriculum Vitae, 26 pages.
Petitioner AT&T Services, Inc. Exhibit 1005, Case No. IPR2017-01384; U.S. Pat. No. 6,240,449, Issued May 29, 2001 to Raymond Nadeau, 13 pages.
Petitioner AT&T Services, Inc. Exhibit 1006, Case No. IPR2017-01384; U.S. Pat. No. 6,594,254 B1, Issued Jul. 15, 2003, to Keith C. Kelly, 18 pages.
Petitioner AT&T Services, Inc. Exhibit 1007, Case No. IPR2017-01384; U.S. Pat. No. 7,715,413 B2, Issued May 11, 2010, to Vaziri et al., 53 pages.
Petitioner AT&T Services, Inc. Exhibit 1008, Case No. IPR2017-01384; Decision, Institution of *Inter Partes* Review, 37 C.F.R. § 42.108, Paper 6, Entered Nov. 21, 2016, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com INC.*, Patent Owner, Case IPR2016-01198, Patent 9,179,005 B2, Before Barbara A. Benoit, Lynne E. Pettigrew, and Stacy B. Margolies, Administrative Patent Judges, 32 pages.
Petitioner AT&T Services, Inc. Exhibit 1009, Case No. IPR2017-01384; p. 221 and Chapter 11, Telecommunications Essentials, Lillian Goleniewski, © 2002, 44 pages.
Petitioner AT&T Services, Inc. Exhibit 1010, Case No. IPR2017-01384; RFC (Request for Comments): 791, Internet Protocol, Darpa Internet Program, Protocol Specification, Sep. 1981, by Information Sciences Institute, USC, 50 pages.
Petitioner AT&T Services, Inc. Exhibit 1011, Case No. IPR2017-01384; ITU-T Recommendation H.323 (Jul. 2003), 298 pages.
Petitioner AT&T Services, Inc. Exhibit 1012, Case No. IPR2017-01384; Telcordia Notes on the Networks, SR-2275, Issue 4, Oct. 2000, p. 10-7, 3 pages.
Document Title: United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Petitioner's Reply to Patent Owner's Response, Dated May 17, 2017, 34 pages.
Petitioner Apple Inc. Exhibit 1007, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Discovery Deposition of William Henry Mangione-Smith, taken on Apr. 19, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 213 pages.
Petitioner Apple Inc. Exhibit 1008, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Discovery Deposition of John Rutter, taken (by phone) on Apr. 5, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 43 pages.
Petitioner Apple Inc. Exhibit 1009, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Discovery Deposition of David Terry, taken on Mar. 24, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 95 pages.
Petitioner Apple Inc. Exhibit 1010, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Discovery Deposition of Clay Perreault, taken on Apr. 12, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 118 pages.
Petitioner Apple Inc. Exhibit 1011, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Complaint for Patent Infringement [Jury Demand], United States District Court, District of Nevada, Case No. 2:16-CV-00260, *Voip-Pal.Com, Inc.*, a Nevada corporation, Plaintiff, v. *Apple, Inc.*, a California corporation, Defendants, filed Feb. 9, 2016, 8 pages.
Petitioner Apple Inc. Exhibit 1012, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Discovery Deposition of Johan Emil Viktor Bjorsell, taken on Mar. 24, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 204 pages.
Petitioner Apple Inc. Exhibit 1013, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Letter dated Apr. 21, 2017 to Adam P. Seitz et al., Erise IP, P.A., re: IPR2016-01198 & IPR1026-01201, "Pursuant to the Board Order of Apr. 19, 2017 (Paper 28) . . . " from Kerry Taylor, Knobbe, Martens, Olson & Bear, LLP, 1 page.
Petitioner Apple Inc. Exhibit 1014, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201; U.S. Pat. No. 8,542,815; Email dated May 1, 2017 to Adam P. Seitz et al., Erise IP, P.A., re: IPR2016-01198 & IPR1026-01201—Fuad Arafa, from Kerry Taylor, Knobbe, Martens, Olson & Bear, LLP, 2 pages.
Document Title: United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com Inc.*, Patent Owner; Case No. IPR2016-01198; U.S. Pat. No. 9,179,005; Petitioner's Reply to Patent Owner's Response, Paper 34, Dated May 17, 2017, 33 pages.
Petitioner Apple Inc. Exhibit 1010, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198; U.S. Pat. No. 9,179,005; Discovery Deposition of William Henry Mangione-Smith, taken on Apr. 19, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 213 pages.
Petitioner Apple Inc. Exhibit 1011, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc., Petitioner* v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198; U.S. Pat. No. 9,179,005; Discovery Deposition of John Rutter, taken (by phone) on Apr. 5, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 43 pages.
Petitioner Apple Inc. Exhibit 1012, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-

(56) **References Cited**

OTHER PUBLICATIONS

01198; U.S. Pat. No. 9,179,005; Discovery Deposition of David Terry, taken on Mar. 24, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 95 pages.

Petitioner Apple Inc. Exhibit 1013, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198; U.S. Pat. No. 9,179,005; Discovery Deposition of Clay Perreault, taken on Apr. 12, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 118 pages.

Petitioner Apple Inc. Exhibit 1014, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198; U.S. Pat. No. 9,179,005; Complaint for Patent Infringement [Jury Demand], United States District Court, District of Nevada, Case No. 2:16-CV-00260, *Voip-Pal.Com, Inc.*, a Nevada corporation, Plaintiff, v. *Apple, Inc.*, a California corporation, Defendants, filed Feb. 9, 2016, 8 pages.

Petitioner Apple Inc. Exhibit 1015, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198; U.S. Pat. No. 9,179,005; Discovery Deposition of Johan Emil Viktor Bjorsell, taken on Mar. 24, 2017 in Case No. IPR2016-01198; U.S. Pat. No. 9,179,005, 204 pages.

Petitioner Apple Inc. Exhibit 1016, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198; U.S. Pat. No. 9,179,005; Letter dated Apr. 21, 2017 to Adam P. Seitz et al., Erise IP, P.A., re: IPR2016-01198 & IPR1026-01201, "Pursuant to the Board Order of Apr. 19, 2017 (Paper 28) . . . " from Kerry Taylor, Knobbe, Martens, Olson & Bear, LLP, 1 page.

Petitioner Apple Inc. Exhibit 1017, United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198; U.S. Pat. No. 9,179,005; Email dated May 1, 2017 to Adam P. Seitz et al., Erise IP, P.A., re: IPR2016-01198 & IPR1026-01201—Fuad Arafa, from Kerry Taylor, Knobbe, Martens, Olson & Bear, LLP, 2 pages.

Document Title: United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com.Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Patent Owner Objections to Apple Evidence Served With Petitioner's Reply, Filed on behalf of Patent Owner Voip-Pal.com Inc., Filed: May 24, 2017, 6 pages.

Document Title: United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner v. *Voip-Pal.Com.Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005; Patent Owner Objections to Apple Evidence Served With Petitioner'S Reply, Filed on behalf of Patent Owner Voip-Pal.com Inc., Filed: May 24, 2017, 6 pages.

Petitioner's Request for Oral Argument, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, dated Jun. 14, 2017, 4 pages.

Patent Owner Sur-Reply in Response to Petitioner's Reply, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, Patent 8,542,815, dated Jun. 14, 2017, 8 pages.

Patent Owner Request for Oral Argument, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, dated Jun. 14, 2017, 4 pages.

Patent Owner Motion to Exclude, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, dated Jun. 14, 2017, 18 pages.

Voip-Pal Ex. 2052, IPR2016-01201, *Apple Inc.* vs. *Voip-Pal.com, Inc.*, Reporter's Transcript of Telephonic Hearing, Jun. 7, 2017, 16 sheets.

Petitioner's Request for Oral Argument, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, Patent 9,179,005, dated Jun. 14, 2017, 4 pages.

Patent Owner Sur-Reply in Response to Petitioner's Reply, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, Patent 9,179,005, dated Jun. 14, 2017, 8 pages.

Patent Owner Request for Oral Argument, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, Patent 9,179,005, dated Jun. 14, 2017, 4 pages.

Patent Owner Motion to Exclude, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, Patent 9,179,005, dated Jun. 14, 2017, 18 pages.

Voip-Pal Ex. 2052, IPR2016-01198, *Apple Inc.* vs. *Voip-Pal.com, Inc.*, Reporter's Transcript of Telephonic Hearing, Jun. 7, 2017, 16 sheets.

Order, Conduct of Proceeding, 37 C.F.R. § 42.5, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com Inc.*, Patent Owner, Cases IPR2016-01198 and IPR2016-01201, U.S. Pat. Nos. 9,179,005 B2 and 8,542,815 B2, Paper No. 37, Filed: Jun. 13, 2017, 3 pages.

Voip-Pal Ex. 2053, IPR2016-01198, *Apple Inc.* vs. *Voip-Pal.com, Inc.*, Reporters Transcript of Telephonic Hearing, Jun. 20, 2017, 25 pages.

Voip-Pal Ex. 2053, IPR2016-01201, *Apple Inc.* vs. *Voip-Pal.com, Inc.*, Reporters Transcript of Telephonic Hearing, Jun. 20, 2017, 25 pages.

Order, *Conduct of Proceeding*, 37 C.F.R. § 42.5, United States Patent and Trademark Office, Before the Patent Trail and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner. Cases IPR2016-01198 and IPR2016-01201, U.S. Pat. Nos. 9,179,005 B2 and 8,542,815 B2, Paper No. 43, Filed: Jun. 22, 2017, 4 pages.

Order, *Trial Hearing*, 37 C.F.R. § 42.70, United States Patent and Trademark Office, Before the Patent Trail and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner. Cases IPR2016-01198 and IPR2016-01201, U.S. Pat. Nos. 9,179,005 B2 and 8,542,815 B2, Paper No. 45, Filed: Jun. 26, 2017, 4 pages.

Petitioner's Opposition to Patent Owner's Motion to Exclude, Unted States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01201, U.S. Pat. No. 8,542,815, Date: Jun. 26, 2017, 15 pages.

Petitioner's Opposition to Patent Owner's Motion to Exclude, Unted States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2016-01198, U.S. Pat. No. 9,179,005, Date: Jun. 26, 2017, 15 pages.

Patent Owner Reply to Opposition to Motion to Exclude, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR 2016-01198, U.S. Pat. No. 9,179,005, Filed: Jul. 3, 2017, 8 pages.

Patent Owner Reply to Opposition to Motion to Exclude, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR 2016-01201, U.S. Pat. No. 8,542,815, Filed: Jul. 3, 2017, 8 pages.

Voip-Pal Ex. 2054, IPR2016-01198, Voip-Pal's Demonstratives for Oral Hearing, *Apple Inc.* v. *Voip-Pal.Com, Inc.*, Case IPR2016-01201 (U.S. Pat. No. 8,542,815), Case IPR2016-01198 (U.S. Pat. No. 9,179,005), Jul. 20, 2017, 34 pages.

Voip-Pal Ex. 2054, IPR2016-01201, Voip-Pal's Demonstratives for Oral Hearing, *Apple Inc.* v. *Voip-Pal.Com, Inc.*, Case IPR2016-01201 (U.S. Pat. No. 8,542,815), Case IPR2016-01198 (U.S. Pat. No. 9,179,005), Jul. 20, 2017, 34 pages.

(56) **References Cited**

OTHER PUBLICATIONS

Petitioner Apple Inc. Ex. 1018, Petitioner's Demonstrative Exhibits, *Inter Partes* Reviews, U.S. Pat. No. 9,179,005 & 8,542,815, Oral Argument, Jul. 20, 2017, *Apple Inc.* v. *Voip-Pal.com, Inc.*, Case IPR2016-01198; U.S. Pat. No. 9,179,005, Case IPR2016-01201; U.S. Pat. No. 8,542,815, 46 pages.

Patent Owner's Preliminary Response to Petition for *Inter Partes* Review, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *AT&T Services, Inc.*, Petitioner, v. *VoIP-Palcom, Inc.*, Patent Owner, Case No. IPR2017-01382, U.S. Pat. No. 8,542,815, dated Aug. 24, 2017, 71 pages.

Patent Owner's Preliminary Response to Petition for *Inter Partes* Review, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *AT&T Services, Inc.*, Petitioner, v. *VoIP-Pal.Com, Inc.*, Patent Owner, Case No. IPR2017-01383, U.S. Pat. No. 9,179,005, dated Aug. 24, 2017, 74 pages.

Patent Owner's Preliminary Response to Petition for *Inter Partes* Review, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *AT&T Services, Inc.*, Petitioner, v. *VoIP-Pal.Com, Inc.*, Patent Owner, Case No. IPR2017-01384, U.S. Pat. No. 9,179,005, dated Aug. 24, 2017, 61 pages.

Patent Owner's Preliminary Response to Petition for *Inter Partes* Review, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner, Case No. IPR2017-01398, U.S. Pat. No. 9,179,005, dated Aug. 25, 2017, 76 pages.

Patent Owner's Preliminary Response to Petition for *Inter Partes* Review, United States Patent and Trademark Office, Before the Patent Trial and Appeal Board, *Apple Inc.*, Petitioner, v. *VoIP-Pal.Com, Inc.*, Patent Owner, Case No. IPR2017-01399, U.S. Pat. No. 8,542,815, dated Aug. 25, 2017, 77 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com., Inc.* Patent Owner; Cases IPR2016-01198 and IPR2016-01201; U.S. Pat. No. 9,179,005 B2 and 8,542,815 B2; Record of Oral Hearing, Held: Jul. 20, 2017; Before Josiah C. Cocks, Jennifer Meyer Chagnon, and John A. Hudalla, Administrative Patent Judges, 83 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2016-01198, U.S. Pat. No. 9,179,005 B2; Final Written Decision; Paper 53, Entered: Nov. 20, 2017; 29 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2016-01201, U.S. Pat. No. 8,542,815 B2; Final Written Decision; Paper 54, Entered: Nov. 20, 2017; 29 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2017-01399, U.S. Pat. No. 8,542,815 B2; Decision: Denying Institution of *Inter Partes* Review; Paper No. 6, Entered: Nov. 20, 2017; 23 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2017-01398, U.S. Pat. No. 9,179,005 B2; Decision: Denying Institution of *Inter Partes* Review; Paper No. 6, Entered: Nov. 20, 2017; 23 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2017-01382, U.S. Pat. No. 8,542,815 B2; Decision: Denying Institution of *Inter Partes* Review; Paper No. 8, Entered: Nov. 20, 2017; 28 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2017-01383, U.S. Pat. No. 9,179,005 B2; Decision: Denying Institution of *Inter Partes* Review; Paper No. 8, Entered: Nov. 20, 2017; 43 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *AT&T Services, Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2017-01384, U.S. Pat. No. 9,179,005 B2; Decision: Denying Institution of *Inter Partes* Review; Paper No. 8, Entered: Nov. 20, 2017; 31 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Cases IPR2016-01198 and IPR2016-01201, U.S. Pat. 9,179,005 B2 and 8,542,815 B2; Order, Conduct of Proceeding, 37 C.F.R. § 42.5; Paper No. 54, Entered: Dec. 20, 2017; 4 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Petitioner's Motion for Entry of Judgment in Favor of Petitioner etc; Paper 55, Date: Dec. 20, 2017; 18 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Petitioner's Updated Exhibit List; Date: Dec. 22, 2017; 4 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Exhibit 1019—Sep. 18, 2017 Voip-Pal Website advertising Dr. Sawyer's Letters; Date: Dec. 20, 2017; 1 page.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Exhibit 1020—Sep. 2017 Voip-Pal Website posting and linking all of Dr. Sawyer's Letters; Date: Dec. 20, 2017; 2 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, vs. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005 B2 and Case No. IPR2016-01201, U.S. Pat. No. 8,542,815 B2; IPR2016-01201 Exhibit 1021—Telephonic Hearing Before the Administrative Patent Judges: Dec. 19, 2017; 25 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005; Petitioner's Motion for Entry of Judgment in Favor of Petitioner etc; Date: Dec. 20, 2017; 18 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005; Petitioner's Updated Exhibit List; Date: Dec. 22, 2017; 4 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2016-01198, U.S. Pat. No. 9,179,005 B2; Exhibit 1019—Sep. 18, 2017 Voip-Pal Website advertising Dr. Sawyer's Letters; Date: Dec. 20, 2017; 1 page.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case IPR2016-01198, U.S. Pat. No. 9,179,005 B2; Exhibit 1020—Sep. 2017 Voip-Pal Website posting and linking all of Dr. Sawyer's Letters; Date: Dec. 20, 2017; 2 pages.

United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, vs. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005 B2 and Case No. IPR2016-01201, U.S. Pat. No. 8,542,815 B2; IPR2016-01198 Exhibit 1021—Telephonic Hearing Before the Administrative Patent Judges: Dec. 19, 2017; 25 pages.

Exhibit 3001 filed Dec. 20, 2017—Letter from Ryan L. Thomas dated Dec. 19, 2017 re Representation of VoIP-Pal.com, Inc. in Conference Call to the Administrative Patent Judges in re IPR2016-01198 and IPR-2016-01201; 1 page.

Exhibit 3002 filed Dec. 20, 2017—Email from Attorney Adam Seitz dated Dec. 15, 2017 to the Administrative Patent Judges in re IPR2016-01198 and IPR-2016-01201 re Authorization to File Motion for Sanctions; 1 page.

Exhibit 3003 filed Dec. 20, 2017—Letter from Dr. Thomas E. Sawyer (Shareholder) dated May 1, 2017 to Ptab Chief Judge David P. Ruschke in re IPR2016-01198 and IPR-2016-01201 re Review of Proceedings, 6 pages.

Exhibit 3004 filed Dec. 20, 2017—Letter from Dr. Thomas E. Sawyer (Shareholder) dated Jun. 21, 2017 to Ptab Chief Judge David P. Ruschke in re IPR2016-01198 and IPR-2016-01201 re Review of Proceedings, 3 pages.

(56) **References Cited**

OTHER PUBLICATIONS

Exhibit 3005 filed Dec. 20, 2017—Letter from Dr. Thomas E. Sawyer (Shareholder) dated Jul. 11, 2017 to PTAB Chief Judge David P. Ruschke in re IPR2016-01198 and IPR-2016-01201 re Review of Proceedings, 5 pages.
Exhibit 3006 filed Dec. 20, 2017—Letter from Dr. Thomas E. Sawyer (Shareholder) dated Jul. 27, 2017 to the Secretary of the Department of Commerce Hon. Wilbur Ross et al. In re IPR2016-01198 and IPR-2016-01201 re Review of Proceedings, 6 pages.
Exhibit 3007 filed Dec. 20, 2017—Letter from Dr. Thomas E. Sawyer (Shareholder) dated Aug. 31, 2017 to the Secretary of the Department of Commerce Hon. Wilbur Ross in re IPR2016-01198 and IPR-2016-01201 re Review of Proceedings, 8 pages.
Exhibit 3008 filed Dec. 20, 2017—Letter from Dr. Thomas E. Sawyer (Shareholder) dated Oct. 23, 2017 to the PTAB Chief Judge David P. Ruschke et al. in re IPR2016-01198 and IPR-2016-01201 re Review of Proceedings, 10 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005; Patent Owner's Opposition to Apple's Motion for Sanctions Pursuant to Board Order of Dec. 20, 2017; Filed: Jan. 12, 2018; 17 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005; Patent Owner's Updated Exhibit List; Filed: Jan. 12, 2018; 9 pages.
Voip-Pal Exhibit 2056, IPR2016-01198; United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005; Declaration in Support of Patent Owner's Opposition to Motion for Sanctions; Dated: Jan. 12, 2018; 12 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Patent Owner's Opposition to Apple's Motion for Sanctions Pursuant to Board Order of Dec. 20, 2017; Filed: Jan. 12, 2018; 17 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Patent Owner's Updated Exhibit List; Filed: Jan. 12, 2018; 9 pages.
Voip-Pal Exhibit 2056, IPR2016-01198; United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Declaration in Support of Patent Owner's Opposition to Motion for Sanctions; Dated: Jan. 12, 2018; 12 pages.
Voip-Pal Exhibit 2057; IPR2016-01198 and IPR2016-01201; Declaration of Adam R. Knecht, Esq. Regarding Notice of Various Letters From Dr. Thomas Sawyer to the Honorable Judge Richard F. Boulware II (ECF Nos. 28 and 32); including Exhibit A (7 pages), Exhibit B (19 pages) and Exhibit C (12 pages); Executed on Dec. 18, 2017; 40 pages.
Voip-Pal Exhibit 2058; IPR2016-01198 and IPR2016-01201; O'Brien et al., "Revealed: Federal Judges Guilty of Owning Stock in Corporations They Ruled on," Occupy.com(May 1, 2014) 11 pages.
Voip-Pal Exhibit 2059; IPR2016-01198 and IPR2016-01201; Letter dated Aug. 7, 2013 from Kathryn Siehndel, USPTO FOIA Officer Re: Freedom of Information Act (FOIA) Request No. F-13-00218 concerning U.S. Pat. No. 7,139,761; 77 pages.
Voip-Pal Exhibit 2060; IPR2016-01198 and IPR2016-01201; Questionnaire for Non-Judicial Nominees; Affidavit executed by Michelle K. Lee Oct. 28, 2014; 40 pages.
Voip-Pal Exhibit 2061; IPR2016-01198 and IPR2016-01201; Davis, R., "PTAB's 'Death Squad' Label Not Totally Off-Base, Chief Says," *Law360*, New York (Aug. 14, 2014) 4 pages.
Voip-Pal Exhibit 2062; IPR2016-01198 and IPR2016-01201; Graham et al., "The Brainy Bunch," *Intellectual Property: An ALM Supplement*, Fall 2015, 7 pages.
Voip-Pal Exhibit 2063; IPR2016-01198 and IPR2016-01201; Patent Trial and Appeal Board Statistics, USPTO, Jan. 31, 2017, 15 pages.
Voip-Pal Exhibit 2064; IPR2016-01198 and IPR2016-01201; Davis, R., "Fed. Circ. Reverses PTAB Nix of Synopsys Circuit Patent," *Law360*, New York, Apr. 24, 2017, 5 pages.
Voip-Pal Exhibit 2065; IPR2016-01198 and IPR2016-01201; Scheller et al. "Federal Circuit to PTAB: No Short Cuts Allowed," *The National Law Review*; Apr. 25, 2017, 5 pages.
Voip-Pal Exhibit 2066; IPR2016-01198 and IPR2016-01201; Couturier, K. "How Europe Is Going After Apple, Google and Other U.S. Tech Giants," *New York Times*, Apr. 13, 2015, 1 page.
Voip-Pal Exhibit 2067; IPR2016-01198 and IPR2016-01201; Manjoo, F., "Tech Giants Seem Invincible. That Worries Lawmakers." *New York Times*, Jan. 4, 2017, 5 pages.
Voip-Pal Exhibit 2068; IPR2016-01198 and IPR2016-01201; Quinn et al., "Michelle Lee's views on patent quality out of touch with reality facing patent applicants," *IPWatchdog®*, Feb. 2, 2017, 5 pages.
Voip-Pal Exhibit 2069; IPR2016-01198 and IPR2016-01201; Quinn, G., "Michelle Lee launches PTAB initiative to 'shape and improve' IPR proceedings," *IPWatchdog®*, Apr. 10, 2017, 3 pages.
Voip-Pal Exhibit 2070; IPR2016-01198 and IPR2016-01201; Kampis, J., "Google employees have enjoyed revolving door during Obama administration," watchdog.org, Aug. 8, 2016, 6 pages.
Voip-Pal Exhibit 2071; IPR2016-01198 and IPR2016-01201; Dayen, D., "The Android Administration," *The Intercept_*, Apr. 22, 2016, 16 pages.
Voip-Pal Exhibit 2072; IPR2016-01198 and IPR2016-01201; Editor Charlie, "©scleland: How Google Is Anti-employment Anti-property & Pro-regulation," *Artist Rights Watch, News for the Artist Rights Advocacy Community*, Nov. 18, 2016, 3 pages.
Voip-Pal Exhibit 2073; IPR2016-01198 and IPR2016-01201; Press Release: "Voip-Pal Issues a Correction to its Press Release of Sep. 18, 2017," Voip-Pal.Com Inc., Jan. 11, 2018, 1 page.
Voip-Pal Exhibit 2074; IPR2016-01198 and IPR2016-01201; "Former head of Google patent strategy appointed to run U.S. patent agency," ai (/Profile/12836/AppleInsider), Dec. 12, 2013, 8 pages.
Voip-Pal Exhibit 2075; IPR2016-01198 and IPR2016-01201; Vermont, S. "IPR Statistics Revisited: Yep, It's A Patent Killing Field," PatentAttorney.com, Feb. 8, 2017, 9 pages.
Voip-Pal Exhibit 2076; IPR2016-01198 and IPR2016-01201; Sterne et al., "PTAB Death Squads: Are All Commercially Viable Patents Invalid?" *IPWatchdog®*, Mar. 24, 2014, 5 pages.
Voip-Pal Exhibit 2077; IPR2016-01198 and IPR2016-01201; Sheafe, B., "Dear Congress: A Small Request on Behalf of the Innovators You (Theoretically) Represent: Part 2," *IPWire*, Jan. 12, 2018, 5 pages.
Voip-Pal Exhibit 2078; IPR2016-01198 and IPR2016-01201; Brachmann, S., "Are conflicts of interest at the PTAB leading to preferential decisions for Apple?" *IPWatchdog®*, Apr. 28, 2017, 5 pages.
Voip-Pal Exhibit 2079; IPR2016-01198 and IPR2016-01201; Quinn et al., "Patent owners do not like IPRs despite what Bloomberg Law, AIPLA study says," *IPWatchdog®*, Feb. 6, 2017, 5 pages.
Voip-Pal Exhibit 2080; IPR2016-01198 and IPR2016-01201; "Does Google's Michelle Lee Work for Both Google and the U.S. Patent Office at the Same Time?" *The Corruption Times, Your Public New Wiki for Social Updates*, Apr. 6, 2016, 8 pages.
Voip-Pal Exhibit 2081; IPR2016-01198 and IPR2016-01201; Morinville, P., "The Senate Must Vet Vishal Amin," *IPWatchdog®*, Apr. 23, 2017, 4 pages.
Voip-Pal Exhibit 2082; IPR2016-01198 and IPR2016-01201; The New York Times "May 15, 1911, Supreme Court Orders Standard Oil to Be Broken Up," *By the Learning Network*, May 15, 2012, 3 pages.
Voip-Pal Exhibit 2083; IPR2016-01198 and IPR2016-01201; Simpson et al., "PTAB Kill Rates: How IPRs Are Affecting Patents," *Law360*, New York, Sep. 15, 2015, 6 pages.

(56) **References Cited**

OTHER PUBLICATIONS

Voip-Pal Exhibit 2084; IPR2016-01198 and IPR2016-01201; Vermont, S., "IPR Statistics Revisited: Yep, It's a Patent Killing Field," PatentAttorney.com, Feb. 8, 2017, 9 pages.
Voip-Pal Exhibit 2085; IPR2016-01198 and IPR2016-01201; Robinson, E., "Why the Unified Patents Model Would Not Work in China," *IPWatchdog®*, Apr. 26, 2017, 4 pages.
Voip-Pal Exhibit 2086; IPR2016-01198 and IPR2016-01201; Brachmann et al., "US Inventor sets patents on fire as part of PTAB protest at USPTO," *IPWatchdog®*, Aug. 11, 2017, 4 pages.
Voip-Pal Exhibit 2087; IPR2016-01198 and IPR2016-01201; "Selection process for assigning judges to expanded PTAB panels," *717 Madison Place*, Aug. 28, 2017, 3 pages.
Voip-Pal Exhibit 2088; IPR2016-01198 and IPR2016-01201; Eden, S., "How the U.S. Patent Office Got So Screwed Up," *Popular Mechanics*, Jun. 21, 2016, 21 pages.
Voip-Pal Exhibit 2089; IPR2016-01198 and IPR2016-01201; Quinn, G., "Supreme Court to decide if Inter Partes Review is Unconstitutional," *IPWatchdog®*, Jun. 12, 2017, 4 pages.
Voip-Pal Exhibit 2090; IPR2016-01198 and IPR2016-01201; Quinn, G., "Industry reaction to Scotus patent venue decision in TC Heartland v. Kraft Food Group," *IPWatchdog®*, May 22, 2017, 7 pages.
Voip-Pal Exhibit 2091; IPR2016-01198 and IPR2016-01201; Flibbert et al., "5 Distinctions Between IPRs and District Court Patent Litigation," *Finnegan*, Dec. 16, 2015, 6 pages.
Voip-Pal Exhibit 2092; IPR2016-01198 and IPR2016-01201; "2404. Hobbs Act—Under Color of Official Right," USAM, Department of Justice, downloaded on Jan. 12, 2018, 5 pages.
Voip-Pal Exhibit 2093; IPR2016-01198 and IPR2016-01201; "Selection process for assigning judges to expanded Ptab panels," *717 Madison Place*, Aug. 28, 2017, 3 pages.
Voip-Pal Exhibit 2094; IPR2016-01198 and IPR2016-01201; "2015 Summary of Ethics Rules," *Economic Development Administration*, U.S. Department of Commerce, 16 pages.
Voip-Pal Exhibit 2095; IPR2016-01198 and IPR2016-01201; "Patent Trial and Appeal Board Statistics," United States Patent and Trademark Office, USPTO, Mar. 31, 2017, 15 pages.
Voip-Pal Exhibit 2096; IPR2016-01198 and IPR2016-01201; Madigan et al., "Turning Gold to Lead: How Patent Eligibility Doctrine is Undermining U.S. Leadership in Innovation," *George Mason Law & Economics Research Paper* No. 17-16, Mar. 30, 2017, 21 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Cases IPR2016-01198 and IPR2016-01201, U.S. Pat. Nos. 9,179,005 B2 and 8,542,815 B2; Order, Conduct of Proceeding, 37 C.F.R. § 42.5, for both proceedings; Paper No. 62, Entered: Jan. 19, 2018, 4 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; IPR2016-01198, U.S. Pat. No. 9,179,005; Notice of Appeal, Dated: Jan. 22, 2018, 5 pages.
Apple Exhibit 1022, IPR2016-01198, Telephonic Hearing Before the Administrative Patent Judges; Jan. 19, 2018; 14 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; IPR2016-01201, U.S. Pat. No. 8,542,815; Notice of Appeal, Dated: Jan. 22, 2018, 5 pages.
Apple Exhibit 1022, IPR2016-01201, Telephonic Hearing Before the Administrative Patent Judges; Jan. 19, 2018; 14 pages.
Case: 18-1456; Document: 1-1; Filed: Jan. 23, 2018, 1 page: UNited States Court of Appeals for the Federal Circuit; *Notice of Docketing*; 18-1456—*Apple Inc.* v. *Voip-Pal.com, Inc.*; Date of Docketing: Jan. 23, 2018, IPR2016-01198; 1 page.
Case: 18-1456; Document: 1-2; Filed: Jan. 23, 2018, 34 pages: United States Court of Appeals for the Federal Circuit; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; IPR2016-01198, U.S. Pat. No. 9,179,005; Notice of Appeal, (Dated: Jan. 22, 2018, 5 pages); with Paper 53; Entered: Nov. 20, 2017; Final Written Decision; 35 U.S.C. § 318(a) and 37 C.F.R. § 42.73; (29 pages).
Case: 18-1456; Document 6; Filed: Jan. 25, 2018; 14 pages: In the United States Court of Appeals for the Federal Circuit, *Apple Inc.*, Petitioner-Appellant, v. *Voip-Pal.Com, Inc.*, Patent Owner-Appellee. On Appeal from the United States Patent and Trademark Office, Patent Trial and Appeal Board, in Case No. IPR2016-01198; Motion of Appellant Apple Inc. To Stay Appeal or for a Limited Remand to Allow Conclusion of Administrative Proceedings.
Case: 18-1457; Document: 1-1; Filed: Jan. 23, 2018, 1 page: United States Court of Appeals for the Federal Circuit; *Notice of Docketing*; 18-1457—*Apple Inc.* v. *Voip-Pal.com, Inc.*; Date of Docketing: Jan. 23, 2018, IPR2016-01201; 1 page.
Case: 18-1457; Document: 1-2; Filed: Jan. 23, 2018, 34 pages: United States Court of Appeals for the Federal Circuit; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; IPR2016-01201, U.S. Pat. No. 8,542,815; Notice of Appeal, (Dated: Jan. 22, 2018, 5 pages); with Paper 54; Entered: Nov. 20, 2017; Final Written Decision; 35 U.S.C. § 318(a) and 37 C.F.R. § 42.73; (29 pages).
Case: 18-1457; Document 6; Filed: Jan. 25, 2018; 14 pages: In the United States Court of Appeals for the Federal Circuit, *Apple Inc.*, Petitioner-Appellant, v. *Voip-Pal.Com, Inc.*, Patent Owner-Appellee. On Appeal from the United States Patent and Trademark Office, Patent Trial and Appeal Board, in Case No. IPR2016-01201; Motion of Appellant Apple Inc. to Stay Appeal or for a Limited Remand to Allow Conclusion of Administrative Proceedings.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005; Petitioner's Reply in Support of Its Motion for Entry of Judgment in Favor of Petitioner as a Sanction for Improper *Ex Parte* Communications by Patent Owner, or, Alternatively, for New and Constitutionally Correct Proceedings, Date: Jan. 26, 2018, 11 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01198, U.S. Pat. No. 9,179,005; Petitioner's Updated Exhibit List, Date: Jan. 26, 2018, 4 pages.
Apple Exhibit 1023, IPR2016-01198, Voip-Pal Issues a Correction to its Press Release of Sep. 18, 2017; Jan. 12, 2018, 1 page.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Petitioner's Reply in Support of Its Motion for Entry of Judgment in Favor of Petitioner as a Sanction for Improper *Ex Parte* Communications by Patent Owner, or, Alternatively, for New and Constitutionally Correct Proceedings, Date: Jan. 26, 2018, 11 pages.
United States Patent and Trademark Office; Before the Patent Trial and Appeal Board; *Apple Inc.*, Petitioner, v. *Voip-Pal.Com, Inc.*, Patent Owner; Case No. IPR2016-01201, U.S. Pat. No. 8,542,815; Petitioner's Updated Exhibit List, Date: Jan. 26, 2018, 4 pages.
Apple Exhibit 1023, IPR2016-01201, Voip-Pal Issues a Correction to its Press Release of Sep. 18, 2017; Jan. 12, 2018, 1 page.
Case: 18-1456; Document 7; Filed: Jan. 29, 2018; 2 pages: United States Court of Appeals for the Federal Circuit, Order; consolidating the appeals.
Case: 18-1457; Document 7; Filed: Jan. 29, 2018; 2 pages: United States Court of Appeals for the Federal Circuit, Order; consolidating the appeals.
Case 2:18-cv-00953-RFB-GWF, Document 1, Filed May 24, 2018; Voip-Pal.com, Inc. Complaint for Patent Infringement [Jury Demand] against Defendant Apple, Inc., United States District Court, District of Nevada, 30 pages.
Case 2:18-cv-01076, Document 1, Filed Jun. 15, 2018, Voip-Pal.com, Inc. Complaint for Patent Infringement [Jury Demand], United States District Court, District of Nevada against Defendants Amazon.com, Inc. ("Amazon Inc."), Amazon Technologies, Inc. ("Amazon Technologies") and Amazon Lab126 ("Amazon Lab126" and together with Amazon Inc. and Amazon Technologies collectively referred to as the "Defendants"), 39 pages.
Case 2:18-cv-01129-RCJ-VCF; Document 6; Filed Aug. 9, 2018; 30 pages; United States District Court District of Nevada, AT&T Corp's Motion to Dismiss Plaintiff's Second Amended Complaint.
Case 2:18-cv-01129-RCJ-VCF; Document 6-1; Filed Aug. 9, 2018; 3 pages: : United States District Court District of Nevada; Decla-

(56) **References Cited**

OTHER PUBLICATIONS

ration of Lauren J. Dreyer in Support of AT&T Corp's Motion to Dismiss Plaintiff's Second Amended Complaint.
Case 2:18-cv-01129-RCJ-VCF Document 6-2 Filed Aug. 9, 2018; 8 pages United States District Court District of Nevada; Appendix A—Asserted Claims of '005 Patent.
Case 2:18-cv-01129-RCJ-VCF Document 6-3 Filed Aug. 9, 2018; 6 pages, United States District Court District of Nevada; Appendix B—Asserted Claims of '815 Patent.
Case 2:18-cv-01129-RCJ-VCF Document 6-4 Filed Aug. 9, 2018; 70 pages: United States District Court District of Nevada; Exhibit 1—War Department Field Manual for the Telephone Switchboard Operating Procedure.
Case 2:18-cv-01129-RCJ-VCF Document 6-5 Filed Aug. 9, 2018; 6 pages United States District Court District of Nevada; Exhibit 2—Transcript of "Telephone Technology—1940s—USA".
Case 2:18-cv-01129-RCJ-VCF Document 6-6 Filed Aug. 9, 2018; 79 pages: United States District Court District of Nevada; Exhibit 3—Patent Owner's Response (Paper 17), IPR 2016-01198.
Case 2:18-cv-01129-RCJ-VCF Document 6-7 Filed Aug. 9, 2018; 33 pages: United States District Court District of Nevada; Exhibit 4—Institution Decision (Paper 6), IPR2016-01198.
Case 2:18-cv-01129-RCJ-VCF Document 6-8 Filed Aug. 9, 2018; 6 pages: United States District Court District of Nevada; Exhibit 5, 34 pages: Institution Decision (Paper 6), IPR2016-01201.
Case 2:18-cv-01129-RCJ-VCF, Document 14, Filed Sep. 6, 2018; 39 pages: United States District Court District of Nevada, Plaintiff Voip-Pal's Opposition to AT&T Corp's Motion to Dismiss Plaintiff's Second Amended Complaint.
Case 2:16-cv-00271-RCJ-VCF, Document 68, Filed Aug. 9, 2018; 30 pages: United States District Court District of Nevada; Verizon Wireless's Motion to Dismiss Plaintiff's Second Amended Complaint.
Case 2:16-cv-00271-RCJ-VCF, Document 68-1, Filed Aug. 9, 2018, 225 pages: United States District Court District of Nevada; Exhibit A—Declaration of Megan S. Woodworth in Support of Verizon Wireless's Motion to Dismiss Plaintiff's Second Amended Complaint.
Case 2:16-cv-00271-RCJ-VCF, Document 68-2, Filed Aug. 9, 2018, 8 pages: United States District Court District of Nevada; Appendix A: Asserted Claims of '005 Patent.
Case 2:16-cv-00271-RCJ-VCF, Document 68-3, Filed Aug. 9, 2018, 6 pages: United States District Court District of Nevada; Appendix B: Asserted Claims of '815 Patent.
Case 2:16-cv-00271-RCJ-VCF, Document 82, Filed Sep. 7, 2018; 39 pages: United States District Court District of Nevada; Plaintiff Voip-Pal's Opposition to Verizon's Motion to Dismiss Plaintiff's Second Amended Complaint (Corrected Brief).
Case No. 2:16-cv-00271-RCJ-VCF, Document 79, filed on Sep. 6, 2018, Motion for Leave to Amend/Correct [10] Amended Complaint, by Plaintiff Voip-Pal.com, Inc., in *Voip-Pal.com, Inc.* v. *Verizon Wireless Services, LLC et al.* (11 pages).
Case No. 2:16-cv-00271-RCJ-VCF, Document 79-1, filed on Sep. 6, 2018, Exhibit to Motion for Leave to Amend/Correct [10] Amended Complaint, by Plaintiff Voip-Pal.com, Inc., in *Voip-Pal.com, Inc.* v. *Verizon Wireless Services, LLC et al.*, namely, Third Amended Complaint for Patent Infringement (148 pages).
Case No: 2:18-cv-01129-RCJ-VCF, Document 12, filed on Sep. 6, 2018, Motion for Leave to Amend/Correct Amended Complaint by Plaintiff Voip-Pal.com, Inc., in *Voip-Pal.com, Inc.* v. *AT&T Corp.* (11 pages).
Case No: 2:18-cv-01129-RCJ-VCF, Document 12-1, filed on Sep. 6, 2018, Exhibit to Motion to Amend/Correct [3] Amended Complaint by Plaintiff Voip-Pal.com, Inc., in *Voip-Pal.com, Inc.* v. *AT&T Corp.*, namely, Third Amended Complaint for Patent Infringement (147 pages).
Case No. 2:16-cv-00271-RCJ-VCF, Document 13, filed Sep. 6, 18, Motion to Strike [6] Motion to Dismiss, by Plaintiff Voip-Pal.com, Inc., in *Voip-Pal.com, Inc.* v. *AT&T Corp.* (15 pages).
Case No. 2:16-cv-00271-RCJ-VCF, Document 80, filed Sep. 6, 2018, Motion to Strike [68] Motion to Dismiss, by Plaintiff Voip-Pal.com, Inc., in *Voip-Pal.com, Inc.* v. *Verizon Wireless Services, LLC et al.* (15 pages).
Canadian Office Action dated Oct. 24, 2018 for Canadian Patent Application No. CA 2,670,510.

* cited by examiner


10
11
Database 18
DB Request
DB Response
vm.ywr.digifonica.com
Vm 19
Routing Controller (RC) 16
RC Request 110
Routing Message 112
Call Controller (CC) YVR Back to Back User Agent SIP Proxy 14
118,119
114,116
MR 9
13
108,118
20
Telus Gateway
Shaw Gateway
Sprint Gateway
15
2001 1050 2222 Calgary
SIP Invite
12
192.168.0.20 2001 1050 8667 Vancouver
17
To Other System Node
21
Call Controller LHR
London

FIG. 1


Phone
Temporary Memory 40
Program Memory 34
12
30
Username 50
63
61
70 74
(2001 1050 8667)
Password 52
SIP Proxy Add 54
53
IP Address (192.168.0.20)
Firewall 56
Call ID 57
Dialed # 45
Audio Path IP Address (2001 1050 2222) 47
μp 32
Parameter Memory 38
I/O 36
48
Internet Connection
46
Handset
42
Dialing Functions 44

FIG. 2

SIP Invite Message

60	Caller	2001 1050 8667
62	Callee	2001 1050 2222
64	Digest Parameters	XXXXXXX
65	Call ID	FF10@ 192.168.0.20
67	IP Address	192.168.0.20
69	Caller UDP Port	1

FIG. 3



FIG. 4


Call Controller Process
120
Receive SIP Invite Message
Authenticate 122
Error Handling 124
Caller ID Field Contents= IP Address? 121
N
Y
Set Type = 3rd Party Invite 123
Set Type = Regular Invite 125
Establish Call ID 126
Prepare RC Request Message 128
Send RC Request Message 129

FIG. 5


150
RC Request Message
152 Caller 2001 1050 8667
154 Callee 2001 1050 2222
156 Digest XXXXXXX
158 Call ID FF10@ 192.168.0.20
160 Type Subscriber

FIG. 6


Routing Controller (16)
207
209
211
Caller ID
Callee ID
Retrieved Dialing Profile
Call Type Flag
Subscriber Bundle Record
Bundle Override Record
Program Memory 204
RC Request Message Handler 250
200
206
Username To Domain Table
µp 202
DB Response
RC Request
212
214
I/O 208
210
216
DB Request
Routing Message

FIG. 7


250
RC Request Message Handler
Store contents of RC request message in buffer
252
Use caller field to get dialing profile for caller from database
254
Concurrent calls from maximum concurrent calls?
256
N
Send error message to call controller
259
End
Y
Increment current concurrent call field of dialling profile
271
A
B
Subscriber username has same prefix as caller node?
280
Y
N
Set call type =cross domain
302
Load routing message with contents of caller, callee from RC request and set route = IP address or domain of callee's; super node TTL=99999
350
Send routing message to call controller
381
End
600
Use callee field to get dialing profile for callee
602
Get call forward, call block and voicemail tables from database
Caller matches block pattern?
608
Y
Send drop call message to call controller
610
End
N
Store username and domain of callee in routing message buffer
609
Entries in CF table?
612
Y
N
Load caller buffer with 1st CF entries
622
D

FIG. 8A


A
257
Callee identifier begins with caller IDD?
Y
N
259
Set call type to international
261
Format callee identifier and remove IDD
380
Callee identifier begins with caller NDD?
Y
N
382
Callee identifier starts with caller local area code starting from NDD length offset?
Y
N
384
Set call type as national
386
Set call type as local call national style
388
Format callee identifier, remove NDD, prepend with caller country code
390
Callee identifier starts with caller area code?
Y
N
392
Set call type to local
394
Format callee identifier and prepend with caller country code
396
Callee identifier length matches caller local dialing lengths and no multi local area codes?
Y
N
398
Set call type to local
400
Format callee identifier and prepend with caller country code and area code
402
Callee identifier is a valid user name?
Y
N
404
Error
End
406
Set call type to network
B
(Private System Call)
263
Length OK?
Y
N
265
Incorrect length message
End
269
Formatted callee identifier has DID bank table record?
Y
N
279
Set callee ID to username number from DID record
B
(Private System Call)
408
Set callee identifier = newly formatted E164 number
410
Get ML ID from E164 number
C
(Public System Call)

FIG. 8B


D
620
Voicemail enabled?
N
Y
640
Store voicemail server address and seconds in routing message buffer
642
Get TTL (in sec) based on cost of routing and user's balance store in routing message buffer
644
Store address of current node in routing message buffer
646
Send routing message to call controller
End

FIG. 8C


C
412
Get supplier ID codes from supplier tables based on master list ID
560
Load prefix field with supplier prefix
562
Load callee field with modified callee number for corresponding supplier
563
Load route field with route identifier
564
Get TTL based on routing cost
566
Store TTL and timeout value in routing message buffer
571
Repeat until all suppliers considered?
Y
N
568
Send routing message
End

FIG. 8D


253
Dialing Profile for a User
258 Username
Assigned on Subscription
260 Domain
Domain Associated with User
262 NDD
1
264 IDD
011
266 Country Code
1
267 Local Area Codes
604;778
268 Caller Minimum Local Length
10
270 Caller Maximum Local Length
10
273 Reseller
Retailer
275 Maximum # of concurrent calls
Assigned on Subscription
277 Current # of concurrent calls
Assigned on Subscription

FIG. 9


Dialing Profile for Caller (Vancouver Subscriber)
276
61
284
63
70
74
258 Username
2001 1050 8667
260 Domain
sp.vvr.digifonica.com
282
262 NDD
1
264 IDD
011
286
288
290
266 Country Code
1
267 Local Area Codes
604;778 (Vancouver)
268 Caller Minimum Local Length
10
270 Caller Maximum Local Length
10
273 Reseller
Klondike
275 Maximum # of concurrent calls
5
277 Current # of concurrent calls
0

FIG. 10

Callee Profile for Calgary Subscriber	
Username	2001 1050 2222
Domain	sp.yvr.digifonica.com
NDD	1
IDD	011
Country Code	1
Local Area Codes	403 (Calgary)
Caller Minimum Local Length	7
Caller Maximum Local Length	10
Reseller	Deerfoot
Maximum # of concurrent calls	5
Current # of concurrent calls	0

FIG. 11

Callee Profile for London Subscriber	
Username	4401 1062 4444
Domain	sp.lhr.digifonica.com
NDD	0
IDD	00
Country Code	44
Local Area Codes	20 (London)
Caller Minimum Local Length	10
Caller Maximum Local Length	11
Reseller	Marble Arch
Maximum # of concurrent calls	5
Current # of concurrent calls	0

FIG. 12


278
DID Bank Table Record Format
281 Username System subscriber
272 User Domain Host name of supernode
274 DID E164#

FIG. 13


300
61
DID Bank Table Record for Calgary Subscriber
281 Username 2001 1050 2222
272 User Domain Sp.yvr.digifonica.com
274 DID 1 604 867 5309
283
285
287
289

FIG. 14



FIG. 15

FIG. 16



FIG. 17



FIG. 18

Master List Record Format

500	ml_id	Alphanumeric
502	Dialing code	Number Sequence
504	Country code	The country code is the national prefix to be used when dialing TO a particular country FROM another country.
506	Nat Sign #(Area Code)	Number Sequence
508	Min Length	Numeric
510	Max Length	Numeric
512	NDD	The NDD prefix is the access code used to make a call **WITHIN** that country from one city to another (when calling another city in the same vicinity, this may not be necessary).
514	IDD	The **IDD prefix** is the international prefix needed to dial a call **FROM** the country listed **TO** another country.
516	Buffer rate	Safe change rate above the highest rate charged by suppliers

FIG. 19

Example: Master List Record with Populated Fields

ml_id	1019
Dialing code	1604
Country code	1
Nat Sign #(Area Code)	604
Min Length	7
Max Length	7
NDD	1
IDD	011
Buffer rate	$0.009/min

FIG. 20

Suppliers List Record Format

540	Sup_id	Name code
542	MI_id	Numeric code
544	Prefix (optional)	String identifying supplier's traffic #
546	Specific Route	IP address
548	NDD/IDD rewrite	
550	Rate	Cost per second to Digifonica to use this route
551	Timeout	Maximum time to wait for a response when requesting this gateway

FIG. 21

Telus Supplier Record

Sup_id	2010 (Telus)
MI_id	1019
Prefix (optional)	4973#
Specific Route	72.64.39.58
NDD/IDD rewrite	011
Rate	$0.02/min
Timeout	20

FIG. 22

Shaw Supplier Record

Sup_id	2011 (Shaw)
MI_id	1019
Prefix (optional)	4974#
Specific Route	73.65.40.59
NDD/IDD rewrite	011
Rate	$0.025/min
Timeout	30

FIG. 23

Sprint Supplier Record

Sup_id	2012 (Sprint)
MI_id	1019
Prefix (optional)	4975#
Specific Route	74.66.41.60
NDD/IDD rewrite	011
Rate	$0.03/min
Timeout	40

FIG. 24

Routing Message Buffer for Gateway Call

4973#01160486753O9@72.64.39.58;ttl=3600;to=20 ~ 570
4974#01160486753O9@73.65.40.59;ttl=3600;to=30 ~ 572
4975#01160486753O9@74.66.41.60;ttl=3600;to=40 ~ 574

FIG. 25

Call Block Table Record Format

604 ~	Username	Digifonica #
606 ~	Block Pattern	PSTN compatible or Digifonica #

FIG. 26

Call Block Table Record for Calgary Callee

604 ~	Username of Callee	2001 1050 2222
606 ~	Block Pattern	2001 1050 8664

FIG. 27

Call Forwarding Table Record Format for Callee

614 ~	Username of Callee	Digifonica #
616 ~	Destination Number	Digifonica #
618 ~	Sequence Number	Integer indicating order to try this

FIG. 28

Call Forwarding Table Record for Calgary Callee

614 ~	Username of Callee	2001 1050 2222
616 ~	Destination Number	2001 1055 2223
618 ~	Sequence Number	1

FIG. 29

Voicemail Table Record Format

624	Username of Callee	Digifonica #
626	Vm Server	domain name
628	Seconds to Voicemail	time to wait before engaging voicemail
630	Enabled	yes/no

FIG. 30

Voicemail Table Record for Calgary Callee

Username of Callee	2001 1050 2222
Vm Server	vm.yvr.digifonica.com
Seconds to Voicemail	20
Enabled	1

FIG. 31

Routing Message Buffer - Same Node

650 ~ 200110502222@sp.yvr.digifonica.com;ttl=3600
652 ~ 200110552223@sp.yvr.digifonica.com;ttl=3600
654 ~ vm.yvr.digifonica.com;20;ttl=60
656 ~ sp.yvr.digifonica.com

FIG. 32


Start
700
Call type=
Network or Cross
Domain?
Y
Set TTL=99999
702
End
N
704
Get subscriber bundle record
for caller & store locally
712
Bundle
override record for
ML_ID?
Y
Store record in
local memory
728
N
730
Services
field of subscriber bundle
record for callee has service field
free local calling code and call type
is local or local/national
style?
Y
Set TTL=99999
732
End
N
A

FIG. 33A


A
734
Copy & store subscriber account record for caller
746
Subscriber account record funds bal. field or free seconds field>0?
N
Set TTL=0
748
End
Y
750
Calculate call cost per second
752
Cost/sec=0?
Y
Set TTL=99999
754
End
N
Set first TTL=
(Funds bal / Cost/sec + Free time balance)
756
758
Set second TTL according to billing pattern
772
Set TTL=Second TTL
End

FIG. 33B

706

Subscriber Bundle Table Record		
708	Username	Subscriber username
710	Services	Codes identifying service features (e.g. Free local calling; call blocking, voicemail)

FIG. 34

Subscriber Bundle Record for Vancouver Caller		
708	Username	2001 1050 8667
710	Services	10; 14; 16

FIG. 35

714

Bundle Override Table Record		
716	ML_Id	Master list ID code
718	Override type	Fixed; percent; cents
720	Override value	real number representing value of override type
722	Inc1	first level of charging (minimum # of seconds) charge
724	Inc2	second level of charging

FIG. 36

726

Bundle Override Record for Located ML_iD		
716	ML_Id	1019
718	Override type	percent
720	Override value	10.0
722	Inc1	30 seconds
724	Inc2	6 seconds

FIG. 37


736
Subscriber Account Table Record
738
Username
Subscriber username
740
Funds balance
real number representing $ value of credit
742
Free time balance
integer representing # of free seconds

FIG. 38


744
Subscriber Account Record for Vancouver Caller
738
Username
2001 1050 8667
740
Funds balance
$10.00
742
Free time balance
100

FIG. 39


760
Start
762
Set remainder=[TTL-INC1] MOD INC2
764
Remainder>0?
Y
766
TTL=TTL-remainder
N
768
TTL<INC1?
Y
770
TTL=0
N
End

FIG. 40


780
Start
782
Look for special rate record based on ML_ID+reseller
Found
Not Found
802
Look for markup record in markup table based on reseller
Found
Not Found
820
Get markup record with reseller=ALL
800
Set ResellerCost/sec= markup value field of located record+contents of buffer rate field from master list record
822
Set SystemOperatorCost/sec= contents buffer rate field from store list record
824
Calltype= local or nat/local style and caller has free local calling?
Y
N
826
Set user cost/sec =0¢
Set Inc1 buffer=1
Set Inc2 buffer=1
828
Bundle override record has ML_ID= stored ML_ID?
N
Y
830
Check reseller special designation table for record with ML_ID?
N
Y
832
Get reseller global markup record based on reseller
862
Set override=contents of markup value field of located record
Inc1=contents of Inc1 field of located record
Inc1=contents of Inc2 field of located record
864
Cost/sec=reseller cost+override
End

FIG. 41


784
System Operator Special Rates Table Record
786 Reseller retailer id
788 ML_Id master list id
790 Markup Table fixed; percent; cents
792 Markup Value real number representing value of markup type
794 Inc1 first level of charging (minimum # of seconds) charge
796 Inc2 second level of charging

FIG. 42


798
System Operator Special Rates Table Record for Klondike
786 Reseller Klondike
788 ML_Id 1019
790 Markup Table cents
792 Markup Value $0.001
794 Inc1 30
796 Inc2 6

FIG. 43

804

System Operator Markup Table Record

806	Reseller	reseller id code
808	Markup Table	fixed; percent; cents
810	Markup Value	real number representing value of markup type
812	Inc1	first level of charging (minimum # of seconds) charge
814	Inc2	second level of charging

FIG. 44

System Operator Markup Table Record for the Reseller Klondike

806	Reseller	Klondike
808	Markup Table	cents
810	Markup Value	$0.01
812	Inc1	30
814	Inc2	6

FIG. 45

System Operator Markup Table Record

806	Reseller	all
808	Markup Table	percent
810	Markup Value	1.0
812	Inc1	30
814	Inc2	6

FIG. 46

832

Reseller Special Destinations Table Record

834	Reseller	reseller id code
836	ML_id	Master List ID code
838	Markup Table	fixed; percent; cents
840	Markup Value	real number representing value of markup type
842	Inc1	first level of charging (minimum # of seconds) charge
844	Inc2	second level of charging

FIG. 47

846

Reseller Special Destinations Table Record for the Reseller Klondike

834	Reseller	Klondike
836	ML_id	1019
838	Markup Table	percent
840	Markup Value	5%
842	Inc1	30
844	Inc2	6

FIG. 48

848

Reseller Global Markup Table Record

850	Reseller	reseller id code
852	Markup Table	fixed; percent; cents
854	Markup Value	real number representing value of markup type
856	Inc1	first level of charging (minimum # of seconds) charge
858	Inc2	second level of charging

FIG. 49

860

Reseller Global Markup Table Record for the Reseller Klondike

850	Reseller	Klondike
852	Markup Table	percent
854	Markup Value	10%
856	Inc1	30
858	Inc2	6

FIG. 50


900
SIP Bye Message
902 Caller Username
904 Callee PSTN compatible # or Username
906 Call ID unique call identifier (hexadecimal string@IP))

FIG. 51


908
SIP Bye Message
902 Caller 2001 1050 8667
904 Callee 2001 1050 2222
906 Call ID FA10@192.168.0.20

FIG. 52


910
SIP Bye Message
Copy Caller, Callee & CallID field contents from Bye message rec'd from phone to same fields of RC Call Stop msg buffer
912
Copy Acct Start Time from Call Timer; Copy Acct Stop Time from Call Timer
914
Calculate Communication Session Time (Call Stop-Call Start) & store in RC Call Stop msg buffer
916
Decrement contents of current concurrent call field (277)
917
Copy route from call log
918
Send RC Stop msg to RC
920
Send Bye msg to Callee
922
End

FIG. 53

1000

RC Call Stop Message

1002	Caller	Username
1004	Callee	PSTN compatible # or Username
1006	Call ID	unique call identifier (hexadecimal string@IP)
1008	Acct Start Time	start time of call
1010	Acct Stop Time	time the call ended
1012	Acct Session Time	start time-stop time (in seconds)
1014	Route	IP address for the communications link that was established

FIG. 54

1020

RC Call Stop Message for Calgary Callee

1002	Caller	2001 1050 8667
1004	Callee	2001 1050 2222
1006	Call ID	FA10@192.168.0.20
1008	Acct Start Time	2006-12-30 12:12:12
1010	Acct Stop Time	2006-12-30 12:12:14
1012	Acct Session Time	2
1014	Route	72.64.39.58

FIG. 55


950
RC STOP CALL MSG.
952
Comm Session time ≤ Inc1?
Y
954
Set chargeable time=Inc1
N
956
Set Remainder=(CommSessionTime-Inc1) mod Inc2
958
Remainder>0?
Y
960
Chargeable time= CommSessionTime-Remainder
N
962
Chargeable time=Contents of CommSessionTime from RC Call Stop msg
964
Chargeable time ≥ Free seconds balance?
N
User cost=0
968
Y
966
Set free seconds bal=0
Decrement subscriber account record free seconds balance by chargeable time
970
A
B

FIG. 56A


A
B
972
Remaining chargeable time=chargeable time-free seconds bal
974
User cost=remaining chargeable time x cost/sec
976
Decrement subscriber account record funds balance by user cost
978
Reseller Cost=Reseller Cost/sec x Acct Session Time
980
Add Reseller Cost to Reseller Balance field of Reseller Account Record
990
System Operator Cost=Sys Op Cost/sec x Acct Session Time
992
Add System Operator Cost to Sys Op Accounts Record
End

FIG. 56B



FIG. 57



FIG. 58



FIG. 59



FIG. 60

PRODUCING ROUTING MESSAGES FOR VOICE OVER IP COMMUNICATIONS

This application is a continuation of U.S. application Ser. No. 15/730,600, filed Oct. 11, 2017, which is a continuation of U.S. application Ser. No. 15/396,344, filed Dec. 30, 2016, now U.S. Pat. No. 9,813,330, which is a continuation of U.S. application Ser. No. 14/877,570, filed Oct. 7, 2015, now U.S. Pat. No. 9,537,762, which is a continuation of U.S. application Ser. No. 13/966,096, filed Aug. 13, 2013, now U.S. Pat. No. 9,179,005, which is a continuation of U.S. application Ser. No. 12/513,147, filed Mar. 1, 2010, now U.S. Pat. No. 8,542,815, which is a national phase entry of PCT/CA2007/001956, filed Nov. 1, 2007, which claims priority to U.S. Provisional Application No. 60/856,212, filed Nov. 2, 2006, all of which are incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

Field of Invention

This invention relates to voice over IP communications and methods and apparatus for routing and billing.

Description of Related Art

Internet protocol (IP) telephones are typically personal computer (PC) based telephones connected within an IP network, such as the public Internet or a private network of a large organization. These IP telephones have installed "voice-over-IP" (VoIP) software enabling them to make and receive voice calls and send and receive information in data and video formats.

IP telephony switches installed within the IP network enable voice calls to be made within or between IP networks, and between an IP network and a switched circuit network (SCN), such as the public switched telephone network (PSTN). If the IP switch supports the Signaling System 7 (SS7) protocol, the IP telephone can also access PSTN databases.

The PSTN network typically includes complex network nodes that contain all information about a local calling service area including user authentication and call routing. The PSTN network typically aggregates all information and traffic into a single location or node, processes it locally and then passes it on to other network nodes, as necessary, by maintaining route tables at the node. PSTN nodes are redundant by design and thus provide reliable service, but if a node should fail due to an earthquake or other natural disaster, significant, if not complete service outages can occur, with no other nodes being able to take up the load.

Existing VoIP systems do not allow for high availability and resiliency in delivering Voice Over IP based Session Initiation Protocol (SIP) Protocol service over a geographically dispersed area such as a city, region or continent. Most resiliency originates from the provision of IP based telephone services to one location or a small number of locations such as a single office or network of branch offices.

SUMMARY OF THE INVENTION

In accordance with one aspect of the invention, there is provided a process for operating a call routing controller to facilitate communication between callers and callees in a system comprising a plurality of nodes with which callers and callees are associated. The process involves, in response

to initiation of a call by a calling subscriber, receiving a caller identifier and a callee identifier. The process also involves using call classification criteria associated with the caller identifier to classify the call as a public network call or a private network call. The process further involves producing a routing message identifying an address, on the private network, associated with the callee when the call is classified as a private network call. The process also involves producing a routing message identifying a gateway to the public network when the call is classified as a public network call.

The process may involve receiving a request to establish a call, from a call controller in communication with a caller identified by the callee identifier.

Using the call classification criteria may involve searching a database to locate a record identifying calling attributes associated with a caller identified by the caller identifier.

Locating a record may involve locating a caller dialing profile comprising a username associated with the caller, a domain associated with the caller, and at least one calling attribute.

Using the call classification criteria may involve comparing calling attributes associated with the caller dialing profile with aspects of the callee identifier.

Comparing may involve determining whether the callee identifier includes a portion that matches an IDD associated with the caller dialing profile.

Comparing may involve determining whether the callee identifier includes a portion that matches an NDD associated with the caller dialing profile.

Comparing may involve determining whether the callee identifier includes a portion that matches an area code associated with the caller dialing profile.

Comparing may involve determining whether the callee identifier has a length within a range specified in the caller dialing profile.

The process may involve formatting the callee identifier into a pre-defined digit format to produce a re-formatted callee identifier.

Formatting may involve removing an international dialing digit from the callee identifier, when the callee identifier begins with a digit matching an international dialing digit specified by the caller dialing profile associated with the caller.

Formatting may involve removing a national dialing digit from the callee identifier and prepending a caller country code to the callee identifier when the callee identifier begins with a national dialing digit.

Formatting may involve prepending a caller country code to the callee identifier when the callee identifier begins with digits identifying an area code specified by the caller dialing profile.

Formatting may involve prepending a caller country code and an area code to the callee identifier when the callee identifier has a length that matches a caller dialing number format specified by the caller dialing profile and only one area code is specified as being associated with the caller in the caller dialing profile.

The process may involve classifying the call as a private network call when the re-formatted callee identifier identifies a subscriber to the private network. The process may involve determining whether the callee identifier complies with a pre-defined username format and if so, classifying the call as a private network call.

The process may involve causing a database of records to be searched to locate a direct in dial (DID) bank table record associating a public telephone number with the reformatted

callee identifier and if the DID bank table record is found, classifying the call as a private network call and if a DID bank table record is not found, classifying the call as a public network call.

Producing the routing message identifying a node on the private network may involve setting a callee identifier in response to a username associated with the DID bank table record.

Producing the routing message may involve determining whether a node associated with the reformatted callee identifier is the same as a node associated the caller identifier.

Determining whether a node associated with the reformatted callee identifier is the same as a node associated the caller identifier may involve determining whether a prefix of the re-formatted callee identifier matches a corresponding prefix of a username associated with the caller dialing profile.

When the node associated with the caller is not the same as the node associated with the callee, the process involves producing a routing message including the caller identifier, the reformatted callee identifier and an identification of a private network node associated with the callee and communicating the routing message to a call controller.

When the node associated with the caller is the same as the node associated with the callee, the process involves determining whether to perform at least one of the following: forward the call to another party, block the call and direct the caller to a voicemail server associated with the callee.

Producing the routing message may involve producing a routing message having an identification of at least one of the callee identifier, an identification of a party to whom the call should be forwarded and an identification of a voicemail server associated with the callee.

The process may involve communicating the routing message to a call controller.

Producing a routing message identifying a gateway to the public network may involve searching a database of route records associating route identifiers with dialing codes to find a route record having a dialing code having a number pattern matching at least a portion of the reformatted callee identifier.

The process may involve searching a database of supplier records associating supplier identifiers with the route identifiers to locate at least one supplier record associated with the route identifier associated with the route record having a dialing code having a number pattern matching at least a portion of the reformatted callee identifier.

The process may involve loading a routing message buffer with the reformatted callee identifier and an identification of specific routes associated respective ones of the supplier records associated with the route record and loading the routing message buffer with a time value and a timeout value.

The process may involve communicating a routing message involving the contents of the routing message buffer to a call controller.

The process may involve causing the dialing profile to include a maximum concurrent call value and a concurrent call count value and causing the concurrent call count value to be incremented when the user associated with the dialing profile initiates a call and causing the concurrent call count value to be decremented when a call with the user associated with the dialing profile is ended.

In accordance with another aspect of the invention, there is provided a call routing apparatus for facilitating communications between callers and callees in a system comprising a plurality of nodes with which callers and callees are associated. The apparatus includes receiving provisions for receiving a caller identifier and a callee identifier, in response to initiation of a call by a calling subscriber. The apparatus also includes classifying provisions for classifying the call as a private network cal or a public network call according to call classification criteria associated with the caller identifier. The apparatus further includes provisions for producing a routing message identifying an address, on the private network, associated with the callee when the call is classified as a private network call. The apparatus also includes provisions for producing a routing message identifying a gateway to the public network when the call is classified as a public network call.

The receiving provisions may be operably configured to receive a request to establish a call, from a call controller in communication with a caller identified by the callee identifier.

The apparatus may further include searching provisions for searching a database including records associating calling attributes with subscribers to the private network to locate a record identifying calling attributes associated with a caller identified by the caller identifier.

The records may include dialing profiles each including a username associated with the subscriber, an identification of a domain associated with the subscriber, and an identification of at least one calling attribute associated with the subscriber.

The call classification provisions may be operably configured to compare calling attributes associated with the caller dialing profile with aspects of the callee identifier.

The calling attributes may include an international dialing digit and call classification provisions may be operably configured to determine whether the callee identifier includes a portion that matches an IDD associated with the caller dialing profile.

The calling attributes may include an national dialing digit and the call classification provisions may be operably configured to determine whether the callee identifier includes a portion that matches an NDD associated with the caller dialing profile.

The calling attributes may include an area code and the call classification provisions may be operably configured to determine whether the callee identifier includes a portion that matches an area code associated with the caller dialing profile.

The calling attribute may include a number length range and the call classification provisions may be operably configured to determine whether the callee identifier has a length within a number length range specified in the caller dialing profile.

The apparatus may further include formatting provisions for formatting the callee identifier into a pre-defined digit format to produce a re-formatted callee identifier.

The formatting provisions may be operably configured to remove an international dialing digit from the callee identifier, when the callee identifier begins with a digit matching an international dialing digit specified by the caller dialing profile associated with the caller.

The formatting provisions may be operably configured to remove a national dialing digit from the callee identifier and prepend a caller country code to the callee identifier when the callee identifier begins with a national dialing digit.

The formatting provisions may be operably configured to prepend a caller country code to the callee identifier when the callee identifier begins with digits identifying an area code specified by the caller dialing profile.

The formatting provisions may be operably configured to prepend a caller country code and area code to the callee identifier when the callee identifier has a length that matches a caller dialing number format specified by the caller dialing profile and only one area code is specified as being associated with the caller in the caller dialing profile.

The classifying provisions may be operably configured to classify the call as a private network call when the re-formatted callee identifier identifies a subscriber to the private network.

The classifying provisions may be operably configured to classify the call as a private network call when the callee identifier complies with a pre-defined username format.

The apparatus may further include searching provisions for searching a database of records to locate a direct in dial (DID) bank table record associating a public telephone number with the reformatted callee identifier and the classifying provisions may be operably configured to classify the call as a private network call when the DID bank table record is found and to classify the call as a public network call when a DID bank table record is not found

The private network routing message producing provisions may be operably configured to produce a routing message having a callee identifier set according to a username associated with the DID bank table record.

The private network routing message producing provisions may be operably configured to determine whether a node associated with the reformatted callee identifier is the same as a node associated the caller identifier.

The private network routing provisions may include provisions for determining whether a prefix of the re-formatted callee identifier matches a corresponding prefix of a username associated with the caller dialing profile.

The private network routing message producing provisions may be operably configured to produce a routing message including the caller identifier, the reformatted callee identifier and an identification of a private network node associated with the callee and to communicate the routing message to a call controller.

The private network routing message producing provisions may be operably configured to perform at least one of the following forward the call to another party, block the call and direct the caller to a voicemail server associated with the callee, when the node associated with the caller is the same as the node associated with the callee.

The provisions for producing the private network routing message may be operably configured to produce a routing message having an identification of at least one of the callee identifier, an identification of a party to whom the call should be forwarded and an identification of a voicemail server associated with the callee.

The apparatus further includes provisions for communicating the routing message to a call controller.

The provisions for producing a public network routing message identifying a gateway to the public network may include provisions for searching a database of route records associating route identifiers with dialing codes to find a route record having a dialing code having a number pattern matching at least a portion of the reformatted callee identifier.

The apparatus further includes provisions for searching a database of supplier records associating supplier identifiers with the route identifiers to locate at least one supplier record associated with the route identifier associated with the route record having a dialing code having a number pattern matching at least a portion of the reformatted callee identifier.

The apparatus further includes a routing message buffer and provisions for loading the routing message buffer with the reformatted callee identifier and an identification of specific routes associated respective ones of the supplier records associated with the route record and loading the routing message buffer with a time value and a timeout value.

The apparatus further includes provisions for communicating a routing message including the contents of the routing message buffer to a call controller.

The apparatus further includes means for causing said dialing profile to include a maximum concurrent call value and a concurrent call count value and for causing said concurrent call count value to be incremented when the user associated with said dialing profile initiates a call and for causing said concurrent call count value to be decremented when a call with said user associated with said dialing profile is ended.

In accordance with another aspect of the invention, there is provided a data structure for access by an apparatus for producing a routing message for use by a call routing controller in a communications system. The data structure includes dialing profile records comprising fields for associating with respective subscribers to the system, a subscriber user name, direct-in-dial records comprising fields for associating with respective subscriber usernames, a user domain and a direct-in-dial number, prefix to node records comprising fields for associating with at least a portion of the respective subscriber usernames, a node address of a node in the system, whereby a subscriber name can be used to find a user domain, at least a portion of the a subscriber name can be used to find a node with which the subscriber identified by the subscriber name is associated, and a user domain and subscriber name can be located in response to a direct-in-dial number.

In accordance with another aspect of the invention, there is provided a data structure for access by an apparatus for producing a routing message for use by a call routing controller in a communications system. The data structure includes master list records comprising fields for associating a dialing code with respective master list identifiers and supplier list records linked to master list records by the master list identifiers, said supplier list records comprising fields for associating with a communications services supplier, a supplier id, a master list id, a route identifier and a billing rate code, whereby communications services suppliers are associated with dialing codes, such that dialing codes can be used to locate suppliers capable of providing a communications link associated with a given dialing code.

In accordance with another aspect of the invention, there is provided a method for determining a time to permit a communication session to be conducted. The method involves calculating a cost per unit time, calculating a first time value as a sum of a free time attributed to a participant in the communication session and the quotient of a funds balance held by the participant to the cost per unit time value and producing a second time value in response to the first time value and a billing pattern associated with the participant, the billing pattern including first and second billing intervals and the second time value being the time to permit a communication session to be conducted.

Calculating the first time value may involve retrieving a record associated with the participant and obtaining from the record at least one of the free time and the funds balance.

Producing the second time value may involve producing a remainder value representing a portion of the second

billing interval remaining after dividing the second billing interval into a difference between the first time value and the first billing interval.

Producing the second time value may involve setting a difference between the first time value and the remainder as the second time value.

The method may further involve setting the second time value to zero when the remainder is greater than zero and the first time value is less than the free time associated with the participant.

Calculating the cost per unit time may involve locating a record in a database, the record comprising a markup type indicator, a markup value and a billing pattern and setting a reseller rate equal to the sum of the markup value and the buffer rate.

Locating the record in a database may involve locating at least one of a record associated with a reseller and a route associated with the reseller, a record associated with the reseller and a default reseller markup record.

Calculating the cost per unit time value further may involve locating at least one of an override record specifying a route cost per unit time amount associated with a route associated with the communication session, a reseller record associated with a reseller of the communications session, the reseller record specifying a reseller cost per unit time associated with the reseller for the communication session, a default operator markup record specifying a default cost per unit time.

The method may further involve setting as the cost per unit time the sum of the reseller rate and at least one of the route cost per unit time, the reseller cost per unit time and the default cost per unit time.

The method may further involve receiving a communication session time representing a duration of the communication session and incrementing a reseller balance by the product of the reseller rate and the communication session time.

The method may further involve receiving a communication session time representing a duration of the communication session and incrementing a system operator balance by a product of the buffer rate and the communication session time.

In accordance with another aspect of the invention, there is provided an apparatus for determining a time to permit a communication session to be conducted. The apparatus includes a processor circuit, a computer readable medium coupled to the processor circuit and encoded with instructions for directing the processor circuit to calculate a cost per unit time for the communication session, calculate a first time value as a sum of a free time attributed to a participant in the communication session and the quotient of a funds balance held by the participant to the cost per unit time value and produce a second time value in response to the first time value and a billing pattern associated with the participant, the billing pattern including first and second billing intervals and the second time value being the time to permit a communication session to be conducted.

The instructions may include instructions for directing the processor circuit to retrieve a record associated with the participant and obtain from the record at least one of the free time and the funds balance.

The instructions may include instructions for directing the processor circuit to produce the second time value by producing a remainder value representing a portion of the second billing interval remaining after dividing the second billing interval into a difference between the first time value and the first billing interval.

The instructions may include instructions for directing the processor circuit to produce the second time value comprises setting a difference between the first time value and the remainder as the second time value. The instructions may include instructions for directing the processor circuit to set the second time value to zero when the remainder is greater than zero and the first time value is less than the free time associated with the participant.

The instructions for directing the processor circuit to calculate the cost per unit time may include instructions for directing the processor circuit to locate a record in a database, the record comprising a markup type indicator, a markup value and a billing pattern and set a reseller rate equal to the sum of the markup value and the buffer rate.

The instructions for directing the processor circuit to locate the record in a database may include instructions for directing the processor circuit to locate at least one of a record associated with a reseller and a route associated with the reseller, a record associated with the reseller, and a default reseller markup record. The instructions for directing the processor circuit to calculate the cost per unit time value may further include instructions for directing the processor circuit to locate at least one of an override record specifying a route cost per unit time amount associated with a route associated with the communication session, a reseller record associated with a reseller of the communications session, the reseller record specifying a reseller cost per unit time associated with the reseller for the communication session, a default operator markup record specifying a default cost per unit time.

The instructions may include instructions for directing the processor circuit to set as the cost per unit time the sum of the reseller rate and at least one of the route cost per unit time, the reseller cost per unit time and the default cost per unit time.

The instructions may include instructions for directing the processor circuit to receive a communication session time representing a duration of the communication session and increment a reseller balance by the product of the reseller rate and the communication session time.

The instructions may include instructions for directing the processor circuit to receive a communication session time representing a duration of the communication session and increment a system operator balance by a product of the buffer rate and the communication session time.

In accordance with another aspect of the invention, there is provided a process for attributing charges for communications services. The process involves determining a first chargeable time in response to a communication session time and a pre-defined billing pattern, determining a user cost value in response to the first chargeable time and a free time value associated with a user of the communications services, changing an account balance associated with the user in response to a user cost per unit time. The process may further involve changing an account balance associated with a reseller of the communications services in response to a reseller cost per unit time and the communication session time and changing an account balance associated with an operator of the communications services in response to an operator cost per unit time and the communication session time.

Determining the first chargeable time may involve locating at least one of an override record specifying a route cost per unit time and billing pattern associated with a route associated with the communication session, a reseller record associated with a reseller of the communications session, the reseller record specifying a reseller cost per unit time and

billing pattern associated with the reseller for the communication session and a default record specifying a default cost per unit time and billing pattern and setting as the pre-defined billing pattern the billing pattern of the record located. The billing pattern of the record located may involve a first billing interval and a second billing interval.

Determining the first chargeable time may involve setting the first chargeable time equal to the first billing interval when the communication session time is less than or equal to the first billing interval.

Determining the first chargeable time may involve producing a remainder value representing a portion of the second billing interval remaining after dividing the second billing interval into a difference between communication session time and the first interval when the communication session time is greater than the communication session time and setting the first chargeable time to a difference between the communication session time and the remainder when the remainder is greater than zero and setting the first chargeable time to the communication session time when the remainder is not greater than zero.

The process may further involve determining a second chargeable time in response to the first chargeable time and the free time value associated with the user of the communications services when the first chargeable time is greater than or equal to the free time value associated with the user of the communications services.

Determining the second chargeable time may involve setting the second chargeable time to a difference between the first chargeable time.

The process may further involve resetting the free time value associated with the user to zero when the first chargeable time is greater than or equal to the free time value associated with the user of the communications services.

Changing an account balance associated with the user may involve calculating a user cost value in response to the second chargeable time and the user cost per unit time.

The process may further involve changing a user free cost balance in response to the user cost value.

The process may further involve setting the user cost to zero when the first chargeable time is less than the free time value associated with the user.

The process may further involve changing a user free time balance in response to the first chargeable time.

In accordance with another aspect of the invention, there is provided an apparatus for attributing charges for communications services. The apparatus includes a processor circuit, a computer readable medium in communication with the processor circuit and encoded with instructions for directing the processor circuit to determine a first chargeable time in response to a communication session time and a pre-defined billing pattern, determine a user cost value in response to the first chargeable time and a free time value associated with a user of the communications services, change an account balance associated with the user in response to a user cost per unit time.

The instructions may further include instructions for changing an account balance associated with a reseller of the communications services in response to a reseller cost per unit time and the communication session time and changing an account balance associated with an operator of the communications services in response to an operator cost per unit time and the communication session time.

The instructions for directing the processor circuit to determine the first chargeable time may further include instructions for causing the processor circuit to communicate with a database to locate at least one of an override record specifying a route cost per unit time and billing pattern associated with a route associated with the communication session, a reseller record associated with a reseller of the communications session, the reseller record specifying a reseller cost per unit time and billing pattern associated with the reseller for the communication session and a default record specifying a default cost per unit time and billing pattern and instructions for setting as the pre-defined billing pattern the billing pattern of the record located. The billing pattern of the record located may include a first billing interval and a second billing interval.

The instructions for causing the processor circuit to determine the first chargeable time may include instructions for directing the processor circuit to set the first chargeable time equal to the first billing interval when the communication session time is less than or equal to the first billing interval.

The instructions for causing the processor circuit to determine the first chargeable time may include instructions for producing a remainder value representing a portion of the second billing interval remaining after dividing the second billing interval into a difference between communication session time and the first interval when the communication session time is greater than the communication session time and instructions for causing the processor circuit to set the first chargeable time to a difference between the communication session time and the remainder when the remainder is greater than zero and instructions for causing the processor circuit to set the first chargeable time to the communication session time when the remainder is not greater than zero.

The instructions may further include instructions for causing the processor circuit to determine a second chargeable time in response to the first chargeable time and the free time value associated with the user of the communications services when the first chargeable time is greater than or equal to the free time value associated with the user of the communications services.

The instructions for causing the processor circuit to determine the second chargeable time may include instructions for causing the processor circuit to set the second chargeable time to a difference between the first chargeable time.

The instructions may further include instructions for causing the processor circuit to reset the free time value associated with the user to zero when the first chargeable time is greater than or equal to the free time value associated with the user of the communications services.

The instructions for causing the processor circuit to change an account balance associated with the user may include instructions for causing the processor circuit to calculate a user cost value in response to the second chargeable time and the user cost per unit time.

The instructions may further include instructions for causing the processor circuit to change a user free cost balance in response to the user cost value.

The instructions may further include instructions for causing the processor circuit to set the user cost to zero when the first chargeable time is less than the free time value associated with the user.

The instructions may further include instructions for causing the processor circuit to change a user free time balance in response to the first chargeable time.

In accordance with another aspect of the invention, there is provided a computer readable medium encoded with codes for directing a processor circuit to execute one or more of the methods described above and/or variants thereof.

Other aspects and features of the present invention will become apparent to those ordinarily skilled in the art upon review of the following description of specific embodiments of the invention in conjunction with the accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

In drawings which illustrate embodiments of the invention,

FIG. **1** is a block diagram of a system according to a first embodiment of the invention;

FIG. **2** is a block diagram of a caller telephone according to the first embodiment of the invention;

FIG. **3** is a schematic representation of a SIP invite message transmitted between the caller telephone and a controller shown in FIG. **1**;

FIG. **4** is a block diagram of a call controller shown in FIG. **1**;

FIG. **5** is a flowchart of a process executed by the call controller shown in FIG. **1**;

FIG. **6** is a schematic representation of a routing, billing and rating (RC) request message produced by the call controller shown in FIG. **1**;

FIG. **7** is a block diagram of a processor circuit of a routing, billing, rating element of the system shown in FIG. **1**;

FIGS. **8**A-**8**D is a flowchart of a RC request message handler executed by the RC processor circuit shown in FIG. **7**;

FIG. **9** is a tabular representation of a dialing profile stored in a database accessible by the RC shown in FIG. **1**;

FIG. **10** is a tabular representation of a dialing profile for a caller using the caller telephone shown in FIG. **1**;

FIG. **11** is a tabular representation of a callee profile for a callee located in Calgary;

FIG. **12** is a tabular representation of a callee profile for a callee located in London;

FIG. **13** is a tabular representation of a Direct-in-Dial (DID) bank table record stored in the database shown in FIG. **1**;

FIG. **14** is a tabular representation of an exemplary DID bank table record for the Calgary callee referenced in FIG. **11**;

FIG. **15** is a tabular representation of a routing message transmitted from the RC to the call controller shown in FIG. **1**;

FIG. **16** is a schematic representation of a routing message buffer holding a routing message for routing a call to the Calgary callee referenced in FIG. **11**;

FIG. **17** is a tabular representation of a prefix to supernode table record stored in the database shown in FIG. **1**;

FIG. **18** is a tabular representation of a prefix to supernode table record that would be used for the Calgary callee referenced in FIG. **11**;

FIG. **19** is a tabular representation of a master list record stored in a master list table in the database shown in FIG. **1**;

FIG. **20** is a tabular representation of a populated master list record;

FIG. **21** is a tabular representation of a suppliers list record stored in the database shown in FIG. **1**;

FIG. **22** is a tabular representation of a specific supplier list record for a first supplier;

FIG. **23** is a tabular representation of a specific supplier list record for a second supplier;

FIG. **24** is a tabular representation of a specific supplier list record for a third supplier;

FIG. **25** is a schematic representation of a routing message, held in a routing message buffer, identifying to the controller a plurality of possible suppliers that may carry the call;

FIG. **26** is a tabular representation of a call block table record;

FIG. **27** is a tabular representation of a call block table record for the Calgary callee;

FIG. **28** is a tabular representation of a call forwarding table record;

FIG. **29** is a tabular representation of a call forwarding table record specific for the Calgary callee;

FIG. **30** is a tabular representation of a voicemail table record specifying voicemail parameters to enable the caller to leave a voicemail message for the callee;

FIG. **31** is a tabular representation of a voicemail table record specific to the Calgary callee;

FIG. **32** is a schematic representation of an exemplary routing message, held in a routing message buffer, indicating call forwarding numbers and a voicemail server identifier;

FIGS. **33**A and **33**B are respective portions of a flowchart of a process executed by the RC processor for determining a time to live value;

FIG. **34** is a tabular representation of a subscriber bundle table record;

FIG. **35** is a tabular representation of a subscriber bundle record for the Vancouver caller;

FIG. **36** is a tabular representation of a bundle override table record;

FIG. **37** is a tabular representation of bundle override record for a located master list ID;

FIG. **38** is a tabular representation of a subscriber account table record;

FIG. **39** is a tabular representation of a subscriber account record for the Vancouver caller;

FIG. **40** is a flowchart of a process for producing a second time value executed by the RC processor circuit shown in FIG. **7**;

FIG. **41** is a flowchart for calculating a call cost per unit time;

FIG. **42** is a tabular representation of a system operator special rates table record;

FIG. **43** is a tabular representation of a system operator special rates table record for a reseller named Klondike;

FIG. **44** is a tabular representation of a system operator mark-up table record;

FIG. **45** is a tabular representation of a system operator mark-up table record for the reseller Klondike;

FIG. **46** is a tabular representation of a default system operator mark-up table record;

FIG. **47** is a tabular representation of a reseller special destinations table record;

FIG. **48** is a tabular representation of a reseller special destinations table record for the reseller Klondike;

FIG. **49** is a tabular representation of a reseller global mark-up table record;

FIG. **50** is a tabular representation of a reseller global mark-up table record for the reseller Klondike;

FIG. **51** is a tabular representation of a SIP bye message transmitted from either of the telephones shown in FIG. **1** to the call controller;

FIG. **52** is a tabular representation of a SIP bye message sent to the controller from the Calgary callee;

FIG. **53** is a flowchart of a process executed by the call controller for producing a RC stop message in response to receipt of a SIP bye message;

FIG. **54** is a tabular representation of an exemplary RC call stop message;

FIG. **55** is a tabular representation of an RC call stop message for the Calgary callee;

FIGS. **56**A and **56**B are respective portions of a flowchart of a RC call stop message handling routine executed by the RC shown in FIG. **1**;

FIG. **57** is a tabular representation of a reseller accounts table record;

FIG. **58** is a tabular representation of a reseller accounts table record for the reseller Klondike;

FIG. **59** is a tabular representation of a system operator accounts table record; and

FIG. **60** is a tabular representation of a system operator accounts record for the system operator described herein.

DETAILED DESCRIPTION

Referring to FIG. **1**, a system for making voice over IP telephone/videophone calls is shown generally at **10**. The system includes a first super node shown generally at **11** and a second super node shown generally at **21**. The first super node **11** is located in geographical area, such as Vancouver, B.C., Canada for example and the second super node **21** is located in London, England, for example. Different super nodes may be located in different geographical regions throughout the world to provide telephone/videophone service to subscribers in respective regions. These super nodes may be in communication with each other by high speed/high data throughput links including optical fiber, satellite and/or cable links, forming a backbone to the system. These super nodes may alternatively or, in addition, be in communication with each other through conventional internet services.

In the embodiment shown, the Vancouver supernode **11** provides telephone/videophone service to western Canadian customers from Vancouver Island to Ontario. Another node (not shown) may be located in Eastern Canada to provide services to subscribers in that area.

Other nodes of the type shown may also be employed within the geographical area serviced by a supernode, to provide for call load sharing, for example within a region of the geographical area serviced by the supernode. However, in general, all nodes are similar and have the properties described below in connection with the Vancouver supernode **11**.

In this embodiment, the Vancouver supernode includes a call controller (C) **14**, a routing controller (RC) **16**, a database **18** and a voicemail server **19** and a media relay **9**. Each of these may be implemented as separate modules on a common computer system or by separate computers, for example. The voicemail server **19** need not be included in the node and can be provided by an outside service provider.

Subscribers such as a subscriber in Vancouver and a subscriber in Calgary communicate with the Vancouver supernode using their own internet service providers which route internet traffic from these subscribers over the internet shown generally at **13** in FIG. **1**. To these subscribers the Vancouver supernode is accessible at a pre-determined internet protocol (IP) address or a fully qualified domain name that can be accessed in the usual way through a subscriber's internet service provider. The subscriber in Vancouver uses a telephone **12** that is capable of communicating with the Vancouver supernode **11** using Session Initiation Protocol (SIP) messages and the Calgary subscriber uses a similar telephone **15**, in Calgary AB.

It should be noted that throughout the description of the embodiments of this invention, the IP/UDP addresses of all elements such as the caller and callee telephones, call controller, media relay, and any others, will be assumed to be valid IP/UDP addresses directly accessible via the Internet or a private IP network, for example, depending on the specific implementation of the system. As such, it will be assumed, for example, that the caller and callee telephones will have IP/UDP addresses directly accessible by the call controllers and the media relays on their respective supernodes, and those addresses will not be obscured by Network Address Translation (NAT) or similar mechanisms. In other words, the IP/UDP information contained in SIP messages (for example the SIP Invite message or the RC Request message which will be described below) will match the IP/UDP addresses of the IP packets carrying these SIP messages.

It will be appreciated that in many situations, the IP addresses assigned to various elements of the system may be in a private IP address space, and thus not directly accessible from other elements. Furthermore, it will also be appreciated that NAT is commonly used to share a "public" IP address between multiple devices, for example between home PCs and IP telephones sharing a single Internet connection. For example, a home PC may be assigned an IP address such as 192.168.0.101 and a Voice over IP telephone may be assigned an IP address of 192.168.0.103. These addresses are located in so called "non-routable" (IP) address space and cannot be accessed directly from the Internet. In order for these devices to communicate with other computers located on the Internet, these IP addresses have to be converted into a "public" IP address, for example 24.10.10.123 assigned by the Internet Service Provider to the subscriber, by a device performing NAT, typically a home router. In addition to translating the IP addresses, NAT typically also translates UDP port numbers, for example an audio path originating at a VoIP telephone and using a UDP port 12378 at its private IP address, may have be translated to a UDP port 23465 associated with the public IP address of the NAT device. In other words, when a packet originating from the above VoIP telephone arrives at an Internet-based supernode, the source IP/UDP address contained in the IP packet header will be 24.10.10.1:23465, whereas the source IP/UDP address information contained in the SIP message inside this IP packet will be 192.168.0.103:12378. The mismatch in the IP/UDP addresses may cause a problem for SIP-based VoIP systems because, for example, a supernode will attempt to send messages to a private address of a telephone but the messages will never get there.

Referring to FIG. **1**, in an attempt to make a call by the Vancouver telephone/videophone **12** to the Calgary telephone/videophone **15**, the Vancouver telephone/videophone sends a SIP invite message to the Vancouver supernode **11** and in response, the call controller **14** sends an RC request message to the RC **16** which makes various enquiries of the database **18** to produce a routing message which is sent back to the call controller **14**. The call controller **14** then communicates with the media relay **9** to cause a communications link including an audio path and a videophone (if a videopath call) to be established through the media relay to the same node, a different node or to a communications supplier gateway as shown generally at **20** to carry audio, and where applicable, video traffic to the call recipient or callee.

Generally, the RC **16** executes a process to facilitate communication between callers and callees. The process involves, in response to initiation of a call by a calling subscriber, receiving a callee identifier from the calling

subscriber, using call classification criteria associated with the calling subscriber to classify the call as a public network call or a private network call and producing a routing message identifying an address on the private network, associated with the callee when the call is classified as a private network call and producing a routing message identifying a gateway to the public network when the call is classified as a public network call.

Subscriber Telephone

In greater detail, referring to FIG. **2**, in this embodiment, the telephone/videophone **12** includes a processor circuit shown generally at **30** comprising a microprocessor **32**, program memory **34**, an input/output (I/O) port **36**, parameter memory **38** and temporary memory **40**. The program memory **34**, I/O port **36**, parameter memory **38** and temporary memory **40** are all in communication with the microprocessor **32**. The I/O port **36** has a dial input **42** for receiving a dialed telephone/videophone number from a keypad, for example, or from a voice recognition unit or from pre-stored telephone/videophone numbers stored in the parameter memory **38**, for example. For simplicity, in FIG. **2** a box labelled dialing functions **44** represents any device capable of informing the microprocessor **32** of a callee identifier, e.g., a callee telephone/videophone number.

The processor **32** stores the callee identifier in a dialed number buffer **45**. In this case, assume the dialed number is 2001 1050 2222 and that it is a number associated with the Calgary subscriber. The I/O port **36** also has a handset interface **46** for receiving and producing signals from and to a handset that the user may place to his ear. This interface **46** may include a BLUETOOTH™ wireless interface, a wired interface or speaker phone, for example. The handset acts as a termination point for an audio path (not shown) which will be appreciated later. The I/O port **36** also has an internet connection **48** which is preferably a high speed internet connection and is operable to connect the telephone/videophone to an internet service provider. The internet connection **48** also acts as a part of the voice path, as will be appreciated later. It will be appreciated that where the subscriber device is a videophone, a separate video path is established in the same way an audio path is established. For simplicity, the following description refers to a telephone call, but it is to be understood that a videophone call is handled similarly, with the call controller causing the media relay to facilitate both an audio path and a video path instead of only an audio path.

The parameter memory **38** has a username field **50**, a password field **52** an IP address field **53** and a SIP proxy address field **54**, for example. The user name field **50** is operable to hold a user name, which in this case is 2001 1050 8667. The user name is assigned upon subscription or registration into the system and, in this embodiment, includes a twelve digit number having a continent code **61**, a country code **63**, a dealer code **70** and a unique number code **74**. The continent code **61** is comprised of the first or left-most digit of the user name in this embodiment. The country code **63** is comprised of the next three digits. The dealer code **70** is comprised of the next four digits and the unique number code **74** is comprised of the last four digits. The password field **52** holds a password of up to 512 characters, in this example. The IP address field **53** stores an IP address of the telephone, which for this explanation is 192.168.0.20. The SIP proxy address field **54** holds an IP protocol compatible proxy address which may be provided to the telephone through the internet connection **48** as part of a registration procedure.

The program memory **34** stores blocks of codes for directing the processor **32** to carry out the functions of the telephone, one of which includes a firewall block **56** which provides firewall functions to the telephone, to prevent access by unauthorized persons to the microprocessor **32** and memories **34**, **38** and **40** through the internet connection **48**. The program memory **34** also stores codes **57** for establishing a call ID. The call ID codes **57** direct the processor **32** to produce a call identifier having a format comprising a hexadecimal string at an IP address, the IP address being the IP address of the telephone. Thus, an exemplary call identifier might be FF10@192.168.0.20.

Generally, in response to picking up the handset interface **46** and activating a dialing function **44**, the microprocessor **32** produces and sends a SIP invite message as shown in FIG. **3**, to the routing controller **16** shown in FIG. **1**. This SIP invite message is essentially to initiate a call by a calling subscriber.

Referring to FIG. **3**, the SIP invite message includes a caller ID field **60**, a callee identifier field **62**, a digest parameters field **64**, a call ID field **65** an IP address field **67** and a caller UDP port field **69**. In this embodiment, the caller ID field **60** includes the user name 2001 1050 8667 that is the Vancouver user name stored in the user name field **50** of the parameter memory **38** in the telephone **12** shown in FIG. **2**. In addition, referring back to FIG. **3**, the callee identifier field **62** includes a callee identifier which in this embodiment is the user name 2001 1050 2222 that is the dialed number of the Calgary subscriber stored in the dialed number buffer **45** shown in FIG. **2**. The digest parameters field **64** includes digest parameters and the call ID field **65** includes a code comprising a generated prefix code (FF10) and a suffix which is the Internet Protocol (IP) address of the telephone **12** stored in the IP address field **53** of the telephone. The IP address field **67** holds the IP address assigned to the telephone, in this embodiment 192.168.0.20, and the caller UDP port field **69** includes a UDP port identifier identifying a UDP port at which the audio path will be terminated at the caller's telephone.

Call Controller

Referring to FIG. **4**, a call controller circuit of the call controller **14** (FIG. **1**) is shown in greater detail at **100**. The call controller circuit **100** includes a microprocessor **102**, program memory **104** and an I/O port **106**. The circuit **100** may include a plurality of microprocessors, a plurality of program memories and a plurality of I/O ports to be able to handle a large volume of calls. However, for simplicity, the call controller circuit **100** will be described as having only one microprocessor **102**, program memory **104** and I/O port **106**, it being understood that there may be more.

Generally, the I/O port **106** includes an input **108** for receiving messages such as the SIP invite message shown in FIG. **3**, from the telephone shown in FIG. **2**. The I/O port **106** also has an RC request message output **110** for transmitting an RC request message to the RC **16** of FIG. **1**, an RC message input **112** for receiving routing messages from the RC **16**, a gateway output **114** for transmitting messages to one of the gateways **20** shown in FIG. **1** to advise the gateway to establish an audio path, for example, and a gateway input **116** for receiving messages from the gateway. The I/O port **106** further includes a SIP output **118** for transmitting messages to the telephone **12** to advise the telephone of the IP addresses of the gateways which will establish the audio path. The I/O port **106** further includes a voicemail server input and output **117**, **119** respectively for communicating with the voicemail server **19** shown in FIG. **1**.

While certain inputs and outputs have been shown as separate, it will be appreciated that some may be a single IP address and IP port. For example, the messages sent to the RC **16** and received from the RC **16** may be transmitted and received on the same single IP port.

The program memory **104** includes blocks of code for directing the microprocessor **102** to carry out various functions of the call controller **14**. For example, these blocks of code include a first block **120** for causing the call controller circuit **100** to execute a SIP invite to RC request process to produce an RC request message in response to a received SIP invite message. In addition, there is a routing message to gateway message block **122** which causes the call controller circuit **100** to produce a gateway query message in response to a received routing message from the RC **16**.

Referring to FIG. **5**, the SIP invite to RC request process is shown in more detail at **120**. On receipt of a SIP invite message of the type shown in FIG. **3**, block **122** of FIG. **5** directs the call controller circuit **100** of FIG. **4** to authenticate the user. This may be done, for example, by prompting the user for a password, by sending a message back to the telephone **12** which is interpreted at the telephone as a request for a password entry or the password may automatically be sent to the call controller **14** from the telephone, in response to the message. The call controller **14** may then make enquiries of databases to which it has access, to determine whether or not the user's password matches a password stored in the database. Various functions may be used to pass encryption keys or hash codes back and forth to ensure that the transmittal of passwords is secure.

Should the authentication process fail, the call controller circuit **100** is directed to an error handling routine **124** which causes messages to be displayed at the telephone **12** to indicate there was an authentication problem. If the authentication procedure is passed, block **121** directs the call controller circuit **100** to determine whether or not the contents of the caller ID field **60** of the SIP invite message received from the telephone is an IP address. If it is an IP address, then block **123** directs the call controller circuit **100** to set the contents of a type field variable maintained by the microprocessor **102** to a code representing that the call type is a third party invite. If at block **121** the caller ID field contents do not identify an IP address, then block **125** directs the microprocessor to set the contents of the type field to a code indicating that the call is being made by a system subscriber. Then, block **126** directs the call controller circuit to read the call identifier **65** provided in the SIP invite message from the telephone **12**, and at block **128** the processor is directed to produce an RC request message that includes that call ID. Block **129** then directs the call controller circuit **100** to send the RC request to the RC **16**.

Referring to FIG. **6**, an RC request message is shown generally at **150** and includes a caller field **152**, a callee field **154**, a digest field **156**, a call ID field **158** and a type field **160**. The caller, callee, digest call ID fields **152**, **154**, **156** and **158** contain copies of the caller, callee, digest parameters and call ID fields **60**, **62**, **64** and **65** of the SIP invite message shown in FIG. **3**. The type field **160** contains the type code established at blocks **123** or **125** of FIG. **5** to indicate whether the call is from a third party or system subscriber, respectively. The caller identifier field may include a PSTN number or a system subscriber username as shown, for example.

Routing Controller (RC)

Referring to FIG. **7**, the RC **16** is shown in greater detail and includes an RC processor circuit shown generally at **200**. The RC processor circuit **200** includes a processor **202**, program memory **204**, a table memory **206**, buffer memory **207**, and an I/O port **208**, all in communication with the processor **202**. (As earlier indicated, there may be a plurality of processor circuits (**202**), memories (**204**), etc.) The buffer memory **207** includes a caller id buffer **209** and a callee id buffer **211**.

The I/O port **208** includes a database request port **210** through which a request to the database (**18** shown in FIG. **1**) can be made and includes a database response port **212** for receiving a reply from the database **18**. The I/O port **208** further includes an RC request message input **214** for receiving the RC request message from the call controller (**14** shown in FIG. **1**) and includes a routing message output **216** for sending a routing message back to the call controller **14**. The I/O port **208** thus acts to receive caller identifier and a callee identifier contained in the RC request message from the call controller, the RC request message being received in response to initiation of a call by a calling subscriber.

The program memory **204** includes blocks of codes for directing the processor **202** to carry out various functions of the RC (**16**). One of these blocks includes an RC request message handler **250** which directs the RC to produce a routing message in response to a received RC request message. The RC request message handler process is shown in greater detail at **250** in FIGS. **8**A through **8**D.

RC Request Message Handler

Referring to FIG. **8**A, the RC request message handler begins with a first block **252** that directs the RC processor circuit (**200**) to store the contents of the RC request message (**150**) in buffers in the buffer memory **207** of FIG. **7**, one of which includes the caller ID buffer **209** of FIG. **7** for separately storing the contents of the callee field **154** of the RC request message. Block **254** then directs the RC processor circuit to use the contents of the caller field **152** in the RC request message shown in FIG. **6**, to locate and retrieve from the database **18** a record associating calling attributes with the calling subscriber. The located record may be referred to as a dialing profile for the caller. The retrieved dialing profile may then be stored in the buffer memory **207**, for example.

Referring to FIG. **9**, an exemplary data structure for a dialing profile is shown generally at **253** and includes a user name field **258**, a domain field **260**, and calling attributes comprising a national dialing digits (NDD) field **262**, an international dialing digits (IDD) field **264**, a country code field **266**, a local area codes field **267**, a caller minimum local length field **268**, a caller maximum local length field **270**, a reseller field **273**, a maximum number of concurrent calls field **275** and a current number of concurrent calls field **277**. Effectively the dialing profile is a record identifying calling attributes of the caller identified by the caller identifier. More generally, dialing profiles represent calling attributes of respective subscribers.

An exemplary caller profile for the Vancouver subscriber is shown generally at **276** in FIG. **10** and indicates that the user name field **258** includes the user name (2001 1050 8667) that has been assigned to the subscriber and is stored in the user name field **50** in the telephone as shown in FIG. **2**.

Referring back to FIG. **10**, the domain field **260** includes a domain name as shown at **282**, including a node type identifier **284**, a location code identifier **286**, a system provider identifier **288** and a domain portion **290**. The domain field **260** effectively identifies a domain or node associated with the user identified by the contents of the user name field **258**. In this embodiment, the node type identifier **284** includes the code "sp" identifying a supernode and the location identifier **286** identifies the supernode as being in

Vancouver (YVR). The system provider identifier **288** identifies the company supplying the service and the domain portion **290** identifies the "corn" domain.

The national dialed digit field **262** in this embodiment includes the digit "1" and, in general, includes a number specified by the International Telecommunications Union (ITU) Telecommunications Standardization Sector (ITU-T) E.164 Recommendation which assigns national dialing digits to countries.

The international dialing digit field **264** includes a code also assigned according to the ITU-T according to the country or location of the user.

The country code field **266** also includes the digit "1" and, in general, includes a number assigned according to the ITU-T to represent the country in which the user is located.

The local area codes field **267** includes a list of area codes that have been assigned by the ITU-T to the geographical area in which the subscriber is located. The caller minimum and maximum local number length fields **268** and **270** hold numbers representing minimum and maximum local number lengths permitted in the area code(s) specified by the contents of the local area codes field **267**. The reseller field **273** is optional and holds a code identifying a retailer of the services, in this embodiment "Klondike". The maximum number of concurrent calls field **275** holds a code identifying the maximum number of concurrent calls that the user is entitled to cause to concurrently exist. This permits more than one call to occur concurrently while all calls for the user are billed to the same account. The current number of concurrent calls field **277** is initially 0 and is incremented each time a concurrent call associated with the user is initiated and is decremented when a concurrent call is terminated. The area codes associated with the user are the area codes associated with the location code identifier **286** of the contents of the domain field **260**.

A dialing profile of the type shown in FIG. **9** is produced whenever a user registers with the system or agrees to become a subscriber to the system. Thus, for example, a user wishing to subscribe to the system may contact an office maintained by a system operator and personnel in the office may ask the user certain questions about his location and service preferences, whereupon tables can be used to provide office personnel with appropriate information to be entered into the user name **258**, domain **260**, NDD **262**, IDD **264**, country code **266**, local area codes **267**, caller minimum and maximum local length fields **268** and **270** reseller field **273** and concurrent call fields **275** and **277** to establish a dialing profile for the user.

Referring to FIGS. **11** and **12**, callee dialing profiles for users in Calgary and London, respectively for example, are shown.

In addition to creating dialing profiles when a user registers with the system, a direct-in-dial (DID) record of the type shown at **278** in FIG. **13** is added to a direct-in-dial bank table in the database (**18** in FIG. **1**) to associate the username and a host name of the supernode with which the user is associated, with an E.164 number associated with the user on the PSTN network.

An exemplary DID table record entry for the Calgary callee is shown generally at **300** in FIG. **14**. The user name field **281** and user domain field **272** are analogous to the user name and user domain fields **258** and **260** of the caller dialing profile shown in FIG. **10**. The contents of the DID field **274** include a E.164 public telephone number including a country code **283**, an area code **285**, an exchange code **287** and a number **289**. If the user has multiple telephone numbers, then multiple records of the type shown at **300** would be included in the DID bank table, each having the same user name and user domain, but different DID field **274** contents reflecting the different telephone numbers associated with that user.

In addition to creating dialing profiles as shown in FIG. **9** and DID records as shown in FIG. **13** when a user registers with the system, call blocking records of the type shown in FIG. **26**, call forwarding records of the type shown in FIG. **28** and voicemail records of the type shown in FIG. **30** may be added to the database **18** when a new subscriber is added to the system.

Referring back to FIG. **8**A, after retrieving a dialing profile for the caller, such as shown at **276** in FIG. **10**, the RC processor circuit **200** is directed to block **256** which directs the processor circuit (**200**) to determine whether the contents of the concurrent call field **277** are less then the contents of the maximum concurrent call field **275** of the dialing profile for the caller and, if so, block **271** directs the processor circuit to increment the contents of the concurrent call field **277**. If the contents of concurrent call field **277** are equal to or greater than the contents of the maximum concurrent call field **275**, block **259** directs the processor circuit **200** to send an error message back to the call controller (**14**) to cause the call controller to notify the caller that the maximum number of concurrent calls has been reached and no further calls can exist concurrently, including the presently requested call.

Assuming block **256** allows the call to proceed, the RC processor circuit **200** is directed to perform certain checks on the callee identifier provided by the contents of the callee field **154** in FIG. **6**, of the RC request message **150**. These checks are shown in greater detail in FIG. **8**B.

Referring to FIG. **8**B, the processor (**202** in FIG. **7**) is directed to a first block **257** that causes it to determine whether a digit pattern of the callee identifier (**154**) provided in the RC request message (**150**) includes a pattern that matches the contents of the international dialing digits (IDD) field **264** in the caller profile shown in FIG. **10**. If so, then block **259** directs the processor (**202**) to set a call type code identifier variable maintained by the processor to indicate that the call is an international call and block **261** directs the processor to produce a reformatted callee identifier by reformatting the callee identifier into a predefined digit format. In this embodiment, this is done by removing the pattern of digits matching the IDD field contents **264** of the caller dialing profile to effectively shorten the callee identifier. Then, block **263** directs the processor **202** to determine whether or not the callee identifier has a length which meets criteria establishing it as a number compliant with the E.164 Standard set by the ITU. If the length does not meet this criteria, block **265** directs the processor **202** to send back to the call controller (**14**) a message indicating the length is not correct. The process is then ended. At the call controller **14**, routines (not shown) stored in the program memory **104** may direct the processor (**102** of FIG. **4**) to respond to the incorrect length message by transmitting a message back to the telephone (**12** shown in FIG. **1**) to indicate that an invalid number has been dialed.

Still referring to FIG. **8**B, if the length of the amended callee identifier meets the criteria set forth at block **263**, block **269** directs the processor (**202** of FIG. **7**) to make a database request to determine whether or not the amended callee identifier is found in a record in the direct-in-dial bank (DID) table. Referring back to FIG. **8**B, at block **269**, if the processor **202** receives a response from the database indicating that the reformatted callee identifier produced at block **261** is found in a record in the DID bank table, then

the callee is a subscriber to the system and the call is classified as a private network call by directing the processor to block **279** which directs the processor to copy the contents of the corresponding user name field (**281** in FIG. **14**) from the callee DID bank table record (**300** in FIG. **14**) into the callee ID buffer (**211** in FIG. **7**). Thus, the processor **202** locates a subscriber user name associated with the reformatted callee identifier. The processor **202** is then directed to point B in FIG. **8**A.

Subscriber to Subscriber Calls Between Different Nodes

Referring to FIG. **8**A, block **280** directs the processor (**202** of FIG. **7**) to execute a process to determine whether or not the node associated with the reformatted callee identifier is the same node that is associated with the caller identifier. To do this, the processor **202** determines whether or not a prefix (e.g., continent code **61**) of the callee name held in the callee ID buffer (**211** in FIG. **7**), is the same as the corresponding prefix of the caller name held in the username field **258** of the caller dialing profile shown in FIG. **10**. If the corresponding prefixes are not the same, block **302** in FIG. **8**A directs the processor (**202** in FIG. **7**) to set a call type flag in the buffer memory (**207** in FIG. **7**) to indicate the call is a cross-domain call. Then, block **350** of FIG. **8**A directs the processor (**202** of FIG. **7**) to produce a routing message identifying an address on the private network with which the callee identified by the contents of the callee ID buffer is associated and to set a time to live for the call at a maximum value of 99999, for example.

Thus the routing message includes a caller identifier, a call identifier set according to a username associated with the located DID bank table record and includes an identifier of a node on the private network with which the callee is associated.

The node in the system with which the callee is associated is determined by using the callee identifier to address a supernode table having records of the type as shown at **370** in FIG. **17**. Each record **370** has a prefix field **372** and a supernode address field **374**. The prefix field **372** includes the first n digits of the callee identifier. In this embodiment n=2. The supernode address field **374** holds a code representing the IP address or a fully qualified domain name of the node associated with the code stored in the callee identifier prefix field **372**. Referring to FIG. **18**, for example, if the prefix is 20, the supernode address associated with that prefix is sp.yvr.digifonica.com.

Referring to FIG. **15**, a generic routing message is shown generally at **352** and includes an optional supplier prefix field **354**, and optional delimiter field **356**, a callee user name field **358**, at least one route field **360**, a time to live field **362** and other fields **364**. The optional supplier prefix field **354** holds a code for identifying supplier traffic. The optional delimiter field **356** holds a symbol that delimits the supplier prefix code from the callee user name field **358**. In this embodiment, the symbol is a number sign (#). The route field **360** holds a domain name or IP address of a gateway or node that is to carry the call, and the time to live field **362** holds a value representing the number of seconds the call is permitted to be active, based on subscriber available minutes and other billing parameters.

Referring to FIG. **8**A and FIG. **16**, an example of a routing message produced by the processor at block **350** for a caller associated with a different node than the caller is shown generally at **366** and includes only a callee field **359**, a route field **361** and a time to live field **362**.

Referring to FIG. **8**A, having produced a routing message as shown in FIG. **16**, block **381** directs the processor (**202** of FIG. **7**) to send the routing message shown in FIG. **16** to the call controller **14** shown in FIG. **1**.

Referring back to FIG. **8**B, if at block **257**, the callee identifier stored in the callee id buffer (**211** in FIG. **7**) does not begin with an international dialing digit, block **380** directs the processor (**202**) to determine whether or not the callee identifier begins with the same national dial digit code as assigned to the caller. To do this, the processor (**202**) is directed to refer to the retrieved caller dialing profile as shown in FIG. **10**. In FIG. **10**, the national dialing digit code **262** is the number 1. Thus, if the callee identifier begins with the number 1, then the processor (**202**) is directed to block **382** in FIG. **8**B.

Block **382** directs the processor (**202** of FIG. **7**) to examine the callee identifier to determine whether or not the digits following the NDD digit identify an area code that is the same as any of the area codes identified in the local area codes field **267** of the caller dialing profile **276** shown in FIG. **10**. If not, block **384** of FIG. **8**B directs the processor **202** to set the call type flag to indicate that the call is a national call. If the digits following the NDD digit identify an area code that is the same as a local area code associated with the caller as indicated by the caller dialing profile, block **386** directs the processor **202** to set the call type flag to indicate a local call, national style. After executing blocks **384** or **386**, block **388** directs the processor **202** to format the callee identifier into a pre-defined digit format to produce a re-formatted callee identifier by removing the national dialed digit and prepending a caller country code identified by the country code field **266** of the caller dialing profile shown in FIG. **10**. The processor (**202**) is then directed to block **263** of FIG. **8**B to perform other processing as already described above.

If at block **380**, the callee identifier does not begin with a national dialed digit, block **390** directs the processor (**202**) to determine whether the callee identifier begins with digits that identify the same area code as the caller. Again, the reference for this is the retrieved caller dialing profile shown in FIG. **10**. The processor (**202**) determines whether or not the first few digits of the callee identifier identify an area code corresponding to the local area code field **267** of the retrieved caller dialing profile. If so, then block **392** directs the processor **202** to set the call type flag to indicate that the call is a local call and block **394** directs the processor (**202**) to format the callee identifier into a pre-defined digit format to produce a reformatted callee identifier by prepending the caller country code to the callee identifier, the caller country code being determined from the country code field **266** of the retrieved caller dialing profile shown in FIG. **10**. The processor (**202**) is then directed to block **263** for further processing as described above.

Referring back to FIG. **8**B, at block **390**, the callee identifier does not start with the same area code as the caller, block **396** directs the processor (**202** of FIG. **7**) to determine whether the number of digits in the callee identifier, i.e. the length of the callee identifier, is within the range of digits indicated by the caller minimum local number length field **268** and the caller maximum local number length field **270** of the retrieved caller dialing profile shown in FIG. **10**. If so, then block **398** directs the processor (**202**) to set the call type flag to indicate a local call and block **400** directs the processor (**202**) to format the callee identifier into a pre-defined digit format to produce a reformatted callee identifier by prepending to the callee identifier the caller country code (as indicated by the country code field **266** of the retrieved caller dialing profile shown in FIG. **10**) followed by the caller area code (as indicated by the local area code

field **267** of the caller profile shown in FIG. **10**). The processor (**202**) is then directed to block **263** of FIG. **8**B for further processing as described above.

Referring back to FIG. **8**B, if at block **396**, the callee identifier has a length that does not fall within the range specified by the caller minimum local number length field (**268** in FIG. **10**) and the caller maximum local number length field (**270** in FIG. **10**), block **402** directs the processor **202** of FIG. **7** to determine whether or not the callee identifier identifies a valid user name. To do this, the processor **202** searches through the database (**18** of FIG. **10** of dialing profiles to find a dialing profile having user name field contents (**258** in FIG. **10**) that match the callee identifier. If no match is found, block **404** directs the processor (**202**) to send an error message back to the call controller (**14**). If at block **402**, a dialing profile having a user name field **258** that matches the callee identifier is found, block **406** directs the processor **202** to set the call type flag to indicate that the call is a private network call and then the processor is directed to block **280** of FIG. **8**A. Thus, the call is classified as a private network call when the callee identifier identifies a subscriber to the private network.

From FIG. **8**B, it will be appreciated that there are certain groups of blocks of codes that direct the processor **202** in FIG. **7** to determine whether the callee identifier has certain features such as an international dialing digit, a national dialing digit, an area code and a length that meet certain criteria, and cause the processor **202** to reformat the callee identifier stored in the callee id buffer **211**, as necessary into a predetermined target format including only a country code, area code, and a normal telephone number, for example, to cause the callee identifier to be compatible with the E.164 number plan standard in this embodiment. This enables block **269** in FIG. **8**B to have a consistent format of callee identifiers for use in searching through the DID bank table records of the type shown in FIG. **13** to determine how to route calls for subscriber to subscriber calls on the same system. Effectively, therefore blocks **257**, **380**, **390**, **396** and **402** establish call classification criteria for classifying the call as a public network call or a private network call. Block **269** classifies the call, depending on whether or not the formatted callee identifier has a DID bank table record and this depends on how the call classification criteria are met and block **402** directs the processor **202** of FIG. **7** to classify the call as a private network call when the callee identifier complies with a pre-defined format, i.e. is a valid user name and identifies a subscriber to the private network, after the callee identifier has been subjected to the classification criteria of blocks **257**, **380**, **390** and **396**.

Subscriber to Non-Subscriber Calls

Not all calls will be subscriber to subscriber calls and this will be detected by the processor **202** of FIG. **7** when it executes block **269** in FIG. **8**B, and does not find a DID bank table record that is associated with the callee, in the DID bank table. When this occurs, the call is classified as a public network call by directing the processor **202** to block **408** of FIG. **8**B which causes it to set the contents of the callee id buffer **211** of FIG. **7** equal to the newly formatted callee identifier, i.e., a number compatible with the E.164 standard. Then, block **410** of FIG. **8**B directs the processor (**202**) to search a database of route or master list records associating route identifiers with dialing codes shown in FIG. **19** to locate a router having a dialing code having a number pattern matching at least a portion of the reformatted callee identifier.

Referring to FIG. **19**, a data structure for a master list or route list record is shown. Each master list record includes a master list ID field **500**, a dialing code field **502**, a country code field **504**, a national sign number field **506**, a minimum length field **508**, a maximum length field **510**, a national dialed digit field **512**, an international dialed digit field **514** and a buffer rate field **516**.

The master list ID field **500** holds a unique code such as 1019, for example, identifying the record. The dialing code field **502** holds a predetermined number pattern that the processor **202** of FIG. **7** uses at block **410** in FIG. **8**B to find the master list record having a dialing code matching the first few digits of the amended callee identifier stored in the callee id buffer **211**. The country code field **504** holds a number representing the country code associated with the record and the national sign number field **506** holds a number representing the area code associated with the record. (It will be observed that the dialing code is a combination of the contents of the country code field **504** and the national sign number field **506**.) The minimum length field **508** holds a number representing the minimum length of digits associated with the record and the maximum length field **51** holds a number representing the maximum number of digits in a number with which the record may be compared. The national dialed digit (NDD) field **512** holds a number representing an access code used to make a call within the country specified by the country code, and the international dialed digit (IDD) field **514** holds a number representing the international prefix needed to dial a call from the country indicated by the country code.

Thus, for example, a master list record may have a format as shown in FIG. **20** with exemplary field contents as shown.

Referring back to FIG. **8**B, using the country code and area code portions of the reformatted callee identifier stored in the callee id buffer **211**, block **410** directs the processor **202** of FIG. **7** to find a master list record such as the one shown in FIG. **20** having a dialing code that matches the country code (1) and area code (**604**) of the callee identifier. Thus, in this example, the processor (**202**) would find a master list record having an ID field containing the number **1019**. This number may be referred to as a route ID. Thus, a route ID number is found in the master list record associated with a predetermined number pattern in the reformatted callee identifier.

After executing block **410** in FIG. **8**B, the process continues as shown in FIG. **8**D. Referring to FIG. **8**D, block **412** directs the processor **202** of FIG. **7** to use the route ID number to search a database of supplier records associating supplier identifiers with route identifiers to locate at least one supplier record associated with the route identifier to identify at least one supplier operable to supply a communications link for the route.

Referring to FIG. **21**, a data structure for a supplier list record is shown. Supplier list records include a supplier ID field **540**, a master list ID field **542**, an optional prefix field **544**, a specific route identifier field **546**, a NDD/IDD rewrite field **548**, a rate field **550**, and a timeout field **551**. The supplier ID field **540** holds a code identifying the name of the supplier and the master list ID field **542** holds a code for associating the supplier record with a master list record. The prefix field **544** holds a string used to identify the supplier traffic and the specific route identifier field **546** holds an IP address of a gateway operated by the supplier indicated by the supplier ID field **540**. The NDD/IDD rewrite field **548** holds a code representing a rewritten value of the NDD/IDD associated with this route for this supplier, and the rate field **550** holds a code indicating the cost per second to the system operator to use the route provided by the gateway specified by the contents of the route identifier field **546**. The timeout

field **551** holds a code indicating a time that the call controller should wait for a response from the associated gateway before giving up and trying the next gateway. This time value may be in seconds, for example. Exemplary supplier records are shown in FIGS. **22**, **23** and **24** for the exemplary suppliers shown at **20** in FIG. **1**, namely Telus, Shaw and Sprint.

Referring back to FIG. **8**D, at block **412** the processor **202** finds all supplier records that identify the master list ID found at block **410** of FIG. **8**B.

Referring back to FIG. **8**D, block **560** directs the processor **202** of FIG. **7** to begin to produce a routing message of the type shown in FIG. **15**. To do this, the processor **202** loads a routing message buffer as shown in FIG. **25** with a supplier prefix of the least costly supplier where the least costly supplier is determined from the rate fields **550** of FIG. **21** of the records associated with respective suppliers.

Referring to FIGS. **22-24**, in the embodiment shown, the supplier "Telus" has the lowest number in the rate field **550** and therefore the prefix 4973 associated with that supplier is loaded into the routing message buffer shown in FIG. **25** first. Block **562** in FIG. **8**D directs the processor to delimit the prefix 4973 by the number sign (#) and to next load the reformatted callee identifier into the routing message buffer shown in FIG. **25**. At block **563** of FIG. **8**D, the contents of the route identifier field **546** of FIG. **21** of the record associated with the supplier "Telus" are added by the processor **202** of FIG. **7** to the routing message buffer shown in FIG. **25** after an @ sign delimiter, and then block **564** in FIG. **8**D directs the processor to get a time to live value, which in one embodiment may be 3600 seconds, for example. Block **566** then directs the processor **202** to load this time to live value and the timeout value (**551**) in FIG. **21** in the routing message buffer of FIG. **25**. Accordingly, a first part of the routing message for the Telus gateway is shown generally at **570** in FIG. **25**.

Referring back to FIG. **8**D, block **571** directs the processor **202** back to block **560** and causes it to repeat blocks **560**, **562**, **563**, **564** and **566** for each successive supplier until the routing message buffer is loaded with information pertaining to each supplier identified by the processor at block **412**. Thus, a second portion of the routing message as shown at **572** in FIG. **25** relates to the second supplier identified by the record shown in FIG. **23**. Referring back to FIG. **25**, a third portion of the routing message as shown at **574** and is associated with a third supplier as indicated by the supplier record shown in FIG. **24**.

Consequently, referring to FIG. **25**, the routing message buffer holds a routing message identifying a plurality of different suppliers able to provide gateways to the public telephone network (i.e. specific routes) to establish at least part of a communication link through which the caller may contact the callee. In this embodiment, each of the suppliers is identified, in succession, according to rate. Other criteria for determining the order in which suppliers are listed in the routing message may include preferred supplier priorities which may be established based on service agreements, for example. Referring back to FIG. **8**D, block **568** directs the processor **202** of FIG. **7** to send the routing message shown in FIG. **25** to the call controller **14** in FIG. **1**.

Subscriber to Subscriber Calls within the Same Node

Referring back to FIG. **8**A, if at block **280**, the callee identifier received in the RC request message has a prefix that identifies the same node as that associated with the caller, block **600** directs the processor **202** to use the callee identifier in the callee id buffer **211** to locate and retrieve a dialing profile for the callee. The dialing profile may be of the type shown in FIG. **11** or **12**, for example. Block **602** of FIG. **8**A then directs the processor **202** of FIG. **7** to get call block, call forward and voicemail records from the database **18** of FIG. **1** based on the user name identified in the callee dialing profile retrieved by the processor at block **600**. Call block, call forward and voicemail records may be as shown in FIGS. **26**, **27**, **28** and **30** for example.

Referring to FIG. **26**, the call block records include a user name field **604** and a block pattern field **606**. The user name field holds a user name corresponding to the user name in the user name field (**258** in FIG. **10**) of the callee profile and the block pattern field **606** holds one or more E.164-compatible numbers or user names identifying PSTN numbers or system subscribers from whom the subscriber identified in the user name field **604** does not wish to receive calls.

Referring to FIG. **8**A and FIG. **27**, block **608** directs the processor **202** of FIG. **7** to determine whether or not the caller identifier received in the RC request message matches a block pattern stored in the block pattern field **606** of the call block record associated with the callee identified by the contents of the user name field **604** in FIG. **26**. If the caller identifier matches a block pattern, block **610** directs the processor to send a drop call or non-completion message to the call controller (**14**) and the process is ended. If the caller identifier does not match a block pattern associated with the callee, block **609** directs the processor to store the username and domain of the callee, as determined from the callee dialing profile, and a time to live value in the routing message buffer as shown at **650** in FIG. **32**. Referring back to FIG. **8**A, block **612** then directs the processor **202** to determine whether or not call forwarding is required.

Referring to FIG. **28**, the call forwarding records include a user name field **614**, a destination number field **616**, and a sequence number field **618**. The user name field **614** stores a code representing a user with which the record is associated. The destination number field **616** holds a user name representing a number to which the current call should be forwarded, and the sequence number field **618** holds an integer number indicating the order in which the user name associated with the corresponding destination number field **616** should be attempted for call forwarding. The call forwarding table may have a plurality of records for a given user. The processor **202** of FIG. **7** uses the contents of the sequence number field **618** to place the records for a given user in order. As will be appreciated below, this enables the call forwarding numbers to be tried in an ordered sequence.

Referring to FIG. **8**A and FIG. **29**, if at block **612**, the call forwarding record for the callee identified by the callee identifier contains no contents in the destination number field **616** and accordingly no contents in the sequence number field **618**, there are no call forwarding entries for this callee, and the processor **202** is directed to block **620** in FIG. **8**C. If there are entries in the call forwarding table **27**, block **622** in FIG. **8**A directs the processor **202** to search the dialing profile table to find a dialing profile record as shown in FIG. **9**, for the user identified by the destination number field **616** of the call forward record shown in FIG. **28**. The processor **202** of FIG. **7** is further directed to store the username and domain for that user and a time to live value in the routing message buffer as shown at **652** in FIG. **32**, to produce a routing message as illustrated. This process is repeated for each call forwarding record associated with the callee identified by the callee id buffer **211** in FIG. **7** to add to the routing message buffer all call forwarding usernames and domains associated with the callee.

Referring back to FIG. **8**A, if at block **612** there are no call forwarding records, then at block **620** in FIG. **8**C the

processor **202** is directed to determine whether or not the user identified by the callee identifier has paid for voicemail service. This is done by checking to see whether or not a flag is set in a voicemail record of the type shown in FIG. **30** in a voicemail table stored in the database **18** shown in FIG. **1**.

Referring to FIG. **30**, voicemail records in this embodiment may include a user name field **624**, a voicemail server field **626**, a seconds to voicemail field **628** and an enable field **630**. The user name field **624** stores the user name of the callee. The voicemail server field **626** holds a code identifying a domain name of a voicemail server associated with the user identified by the user name field **624**. The seconds to voicemail field **628** holds a code identifying the time to wait before engaging voicemail, and the enable field **630** holds a code representing whether or not voicemail is enabled for the user. Referring back to FIG. **8**C, at block **620** if the processor **202** of FIG. **7** finds a voicemail record as shown in FIG. **30** having user name field **624** contents matching the callee identifier, the processor is directed to examine the contents of the enabled field **630** to determine whether or not voicemail is enabled. If voicemail is enabled, then block **640** in FIG. **8**C directs the processor **202** to FIG. **7** to store the contents of the voicemail server field **626** and the contents of the seconds to voicemail field **628** in the routing message buffer, as shown at **654** in FIG. **32**. Block **642** then directs the processor **202** to get time to live values for each path specified by the routing message according to the cost of routing and the user's balance. These time to live values are then appended to corresponding paths already stored in the routing message buffer.

Referring back to FIG. **8**C, block **644** then directs the processor **202** of FIG. **7** to store the IP address of the current node in the routing message buffer as shown at **656** in FIG. **32**. Block **646** then directs the processor **202** to send the routing message shown in FIG. **32** to the call controller **14** in FIG. **1**. Thus in the embodiment described the routing controller will produce a routing message that will cause at least one of the following: forward the call to another party, block the call and direct the caller to a voicemail server.

Referring back to FIG. **1**, the routing message whether of the type shown in FIG. **16**, **25** or **32**, is received at the call controller **14** and the call controller interprets the receipt of the routing message as a request to establish a call.

Referring to FIG. **4**, the program memory **104** of the call controller **14** includes a routing to gateway routine depicted generally at **122**.

Where a routing message of the type shown in FIG. **32** is received by the call controller **14**, the routing to gateway routine **122** shown in FIG. **4** may direct the processor **102** cause a message to be sent back through the internet **13** shown in FIG. **1** to the callee telephone **15**, knowing the IP address of the callee telephone **15** from the user name.

Alternatively, if the routing message is of the type shown in FIG. **16**, which identifies a domain associated with another node in the system, the call controller may send a SIP invite message along the high speed backbone **17** connected to the other node. The other node functions as explained above, in response to receipt of a SIP invite message.

If the routing message is of the type shown in FIG. **25** where there are a plurality of gateway suppliers available, the call controller sends a SIP invite message to the first supplier, in this case Telus, using a dedicated line or an internet connection to determine whether or not Telus is able to handle the call. If the Telus gateway returns a message indicating it is not able to handle the call, the call controller **14** then proceeds to send a SIP invite message to the next supplier, in this case Shaw. The process is repeated until one of the suppliers responds indicating that it is available to carry the call. Once a supplier responds indicating that it is able to carry the call, the supplier sends back to the call controller **14** an IP address for a gateway provided by the supplier through which the call or audio path of the call will be carried. This IP address is sent in a message from the call controller **14** to the media relay **9** which responds with a message indicating an IP address to which the caller telephone should send its audio/video, traffic and an IP address to which the gateway should send its audio/video for the call. The call controller conveys the IP address at which the media relay expects to receive audio/video from the caller telephone, to the caller telephone **12** in a message. The caller telephone replies to the call controller with an IP address at which it would like to receive audio/video and the call controller conveys that IP address to the media relay. The call may then be conducted between the caller and callee through the media relay and gateway.

Referring back to FIG. **1**, if the call controller **14** receives a routing message of the type shown in FIG. **32**, and which has at least one call forwarding number and/or a voicemail number, the call controller attempts to establish a call to the callee telephone **15** by seeking from the callee telephone a message indicating an IP address to which the media relay should send audio/video. If no such message is received from the callee telephone, no call is established. If no call is established within a pre-determined time, the call controller **14** attempts to establish a call with the next user identified in the call routing message in the same manner. This process is repeated until all call forwarding possibilities have been exhausted, in which case the call controller communicates with the voicemail server **19** identified in the routing message to obtain an IP address to which the media relay should send audio/video and the remainder of the process mentioned above for establishing IP addresses at the media relay **9** and the caller telephone is carried out to establish audio/video paths to allowing the caller to leave a voicemail message with the voicemail server.

When an audio/video path through the media relay is established, a call timer maintained by the call controller **14** logs the start date and time of the call and logs the call ID and an identification of the route (i.e., audio/video path IP address) for later use in billing.

Time to Live

Referring to FIGS. **33**A and **33**B, a process for determining a time to live value for any of blocks **642** in FIG. **8**C, **350** in FIG. **8**A or **564** in FIG. **8**D above is described. The process is executed by the processor **202** shown in FIG. **7**. Generally, the process involves calculating a cost per unit time, calculating a first time value as a sum of a free time attributed to a participant in the communication session and the quotient of a funds balance held by the participant to the cost per unit time value and producing a second time value in response to the first time value and a billing pattern associated with the participant, the billing pattern including first and second billing intervals and the second time value being the time to permit a communication session to be conducted.

Referring to FIG. **33**A, in this embodiment, the process begins with a first block **700** that directs the RC processor to determine whether or not the call type set at block **302** in FIG. **8**A indicates the call is a network or cross-domain call. If the call is a network or cross-domain call, block **702** of FIG. **33**A directs the RC processor to set the time to live equal to 99999 and the process is ended. Thus, the network or cross-domain call type has a long time to live. If at block

700 the call type is determined not to be a network or cross-domain type, block 704 directs the RC processor to get a subscriber bundle table record from the database 18 in FIG. 1 and store it locally in the subscriber bundle record buffer at the RC 14.

Referring to FIG. 34, a subscriber bundle table record is shown generally at 706. The record includes a user name field 708 and a services field 710. The user name field 708 holds a code identifying the subscriber user name and the services field 710 holds codes identifying service features assigned to the subscriber, such as free local calling, call blocking and voicemail, for example.

FIG. 35 shows an exemplary subscriber bundle record for the Vancouver caller. In this record the user name field 708 is loaded with the user name 2001 1050 8667 and the services field 710 is loaded with codes 10, 14 and 16 corresponding to free local calling, call blocking and voicemail, respectively. Thus, user 2001 1050 8667 has free local calling, call blocking and voicemail features.

Referring back to FIG. 33A, after having loaded a subscriber bundle record into the subscriber bundle record buffer, block 712 directs the RC processor to search the database (18) determine whether or not there is a bundle override table record for the master list ID value that was determined at block 410 in FIG. 8B. An exemplary bundle override table record is shown at 714 in FIG. 36. The bundle table record includes a master list ID field 716, an override type field 718, an override value field 720 a first interval field 722 and a second interval field 724. The master list ID field 716 holds a master list ID code. The override type field 718 holds an override type code indicating a fixed, percent or cent amount to indicate the amount by which a fee will be increased. The override value field 720 holds a real number representing the value of the override type. The first interval field 722 holds a value indicating the minimum number of seconds for a first level of charging and the second interval field 724 holds a number representing a second level of charging.

Referring to FIG. 37, a bundle override record for the located master list ID code is shown generally at 726 and includes a master list ID field 716 holding the code 1019 which was the code located in block 410 of FIG. 8B. The override type field 718 includes a code indicating the override type is a percentage value and the override value field 720 holds the value 10.0 indicating that the override will be 10.0% of the charged value. The first interval field 722 holds a value representing 30 seconds and the second interval field 724 holds a value representing 6 seconds. The 30 second value in the first interval field 722 indicates that charges for the route will be made at a first rate for 30 seconds and thereafter the charges will be made at a different rate in increments of 6 seconds, as indicated by the contents of the second interval field 724.

Referring back to FIG. 33A, if at block 712 the processor finds a bundle override record of the type shown in FIG. 37, block 728 directs the processor to store the bundle override record in local memory. In the embodiment shown, the bundle override record shown in FIG. 37 is stored in the bundle override record buffer at the RC as shown in FIG. 7. Still referring to FIG. 33A, block 730 then directs the RC processor to determine whether or not the subscriber bundle table record 706 in FIG. 35 has a services field including a code identifying that the user is entitled to free local calling and also directs the processor to determine whether or not the call type is not a cross domain cell, i.e. it is a local or local/national style. If both of these conditions are satisfied, block 732 directs the processor to set the time to live equal to 99999, giving the user a long period of time for the call. The process is then ended. If the conditions associated with block 730 are not satisfied, block 734 of FIG. 33B directs the RC processor to retrieve a subscriber account record associated with a participant in the call. This is done by copying and storing in the subscriber account record buffer a subscriber account record for the caller.

Referring to FIG. 38, an exemplary subscriber account table record is shown generally at 736. The record includes a user name field 738, a funds balance field 740 and a free time field 742. The user name field 738 holds a subscriber user name, the funds balance field 740 holds a real number representing the dollar value of credit available to the subscriber and the free time field 742 holds an integer representing the number of free seconds that the user is entitled to.

An exemplary subscriber account record for the Vancouver caller is shown generally at 744 in FIG. 39, wherein the user name field 738 holds the user name 2001 1050 8667, the funds balance field 740 holds the value $10.00, and the free time field 742 holds the value 100. The funds balance field holding the value of $10.00 indicates the user has $10.00 worth of credit and the free time field having the value of 100 indicates that the user has a balance of 100 free seconds of call time.

Referring back to FIG. 33B, after copying and storing the subscriber account record shown in FIG. 39 from the database to the subscriber account record buffer RC, block 746 directs the processor to determine whether or not the subscriber account record funds balance field 740 or free time field 742 are greater than zero. If they are not greater than zero, block 748 directs the processor to set the time to live equal to zero and the process is ended. The RC then sends a message back to the call controller to cause the call controller to deny the call to the caller. If the conditions associated with block 746 are satisfied, block 750 directs the processor to calculate the call cost per unit time. A procedure for calculating the call cost per unit time is described below in connection with FIG. 41.

Assuming the procedure for calculating the cost per second returns a number representing the call cost per second, block 752 directs the processor 202 in FIG. 7 to determine whether or not the cost per second is equal to zero. If so, block 754 directs the processor to set the time to live to 99999 to give the caller a very long length of call and the process is ended.

If at block 752 the call cost per second is not equal to zero, block 756 directs the processor 202 in FIG. 7 to calculate a first time to live value as a sum of a free time attributed to the participant in the communication session and the quotient of the funds balance held by the participant to the cost per unit time value. To do this, the processor 202 of FIG. 7 is directed to set a first time value or temporary time to live value equal to the sum of the free time provided in the free time field 742 of the subscriber account record shown in FIG. 39 and the quotient of the contents of the funds balance field 740 in the subscriber account record for the call shown in FIG. 39 and the cost per second determined at block 750 of FIG. 33B. Thus, for example, if at block 750 the cost per second is determined to be three cents per second and the funds balance field holds the value $10.00, the quotient of the funds balance and cost per second is 333 seconds and this is added to the contents of the free time field 742, which is 100, resulting in a time to live of 433 seconds.

Block 758 then directs the RC processor to produce a second time value in response to the first time value and the billing pattern associated with the participant as established

by the bundle override record shown in FIG. **37**. This process is shown in greater detail at **760** in FIG. **40** and generally involves producing a remainder value representing a portion of the second billing interval remaining after dividing the second billing interval into a difference between the first time value and the first billing interval.

Referring to FIG. **40**, the process for producing the second time value begins with a first block **762** that directs the processor **202** in FIG. **7** to set a remainder value equal to the difference between the time to live value calculated at block **756** in FIG. **33**B and the contents of the first interval field **722** of the record shown in FIG. **37**, multiplied by the modulus of the contents of the second interval field **724** of FIG. **37**. Thus, in the example given, the difference between the time to live field and the first interval field is 433 minus 30, which is 403 and therefore the remainder produced by the mod of 403 divided by 6 is 0.17. Block **764** then directs the processor to determine whether or not this remainder value is greater than zero and, if so, block **766** directs the processor to subtract the remainder from the first time value and set the difference as the second time value. To do this the processor is directed to set the time to live value equal to the current time to live of 403 minus the remainder of 1, i.e., 402 seconds. The processor is then returned back to block **758** of FIG. **33**B.

Referring back to FIG. **40**, if at block **764** the remainder is not greater than zero, block **768** directs the processor **202** of FIG. **7** to determine whether or not the time to live is less than the contents of the first interval field **722** in the record shown in FIG. **37**. If so, then block **770** of FIG. **40** directs the processor to set the time to live equal to zero. Thus, the second time value is set to zero when the remainder is greater than zero and the first time value is less than the free time associated with the participant in the call. If at block **768** the conditions of that block are not satisfied, the processor returns the first time to live value as the second time to live value.

Thus, referring to FIG. **33**B, after having produced a second time to live value, block **772** directs the processor to set the time to live value for use in blocks **342**, **350** or **564**.

Cost Per Second

Referring back to FIG. **33**B, at block **750** it was explained that a call cost per unit time is calculated. The following explains how that call cost per unit time value is calculated.

Referring to FIG. **41**, a process for calculating a cost per unit time is shown generally at **780**. The process is executed by the processor **202** in FIG. **7** and generally involves locating a record in a database, the record comprising a markup type indicator, a markup value and a billing pattern and setting a reseller rate equal to the sum of the markup value and the buffer rate, locating at least one of an override record specifying a route cost per unit time amount associated with a route associated with the communication session, a reseller record associated with a reseller of the communications session, the reseller record specifying a reseller cost per unit time associated with the reseller for the communication session and a default operator markup record specifying a default cost per unit time and setting as the cost per unit time the sum of the reseller rate and at least one of the route cost per unit time, the reseller cost per unit time and the default cost per unit time.

The process begins with a first set of blocks **782**, **802** and **820** which direct the processor **202** in FIG. **7** to locate at least one of a record associated with a reseller and a route associated with the reseller, a record associated with the reseller, and a default reseller mark-up record. Block **782**, in particular, directs the processor to address the database **18** to look for a record associated with a reseller and a route with the reseller by looking for a special rate record based on the master list ID established at block **410** in FIG. **8**C.

Referring to FIG. **42**, a system operator special rate table record is shown generally at **784**. The record includes a reseller field **786**, a master list ID field **788**, a mark-up type field **790**, a mark-up value field **792**, a first interval field **794** and a second interval field **796**. The reseller field **786** holds a reseller ID code and the master list ID field **788** holds a master list ID code. The mark-up type field **790** holds a mark-up type such as fixed percent or cents and the mark-up value field **792** holds a real number representing the value corresponding to the mark-up type. The first interval field **794** holds a number representing a first level of charging and the second interval field **796** holds a number representing a second level of charging.

An exemplary system operator special rate table for a reseller known as "Klondike" is shown at **798** in FIG. **43**. In this record, the reseller field **786** holds a code indicating the retailer ID is Klondike, the master list ID field **788** holds the code 1019 to associate the record with the master list ID code 1019. The mark-up type field **790** holds a code indicating the mark-up type is cents and the mark-up value field **792** holds a mark-up value indicating 1/10 of one cent. The first interval field **794** holds the value 30 and the second interval field **796** holds the value 6, these two fields indicating that the operator allows 30 seconds for free and then billing is done in increments of 6 seconds after that.

Referring back to FIG. **41**, if at block **782** a record such as the one shown in FIG. **43** is located in the system operator special rates table, the processor is directed to block **800** in FIG. **41**. If such a record is not found in the system operator special rates table, block **802** directs the processor to address the database **18** to look in a system operator mark-up table for a mark-up record associated with the reseller.

Referring to FIG. **44**, an exemplary system operator mark-up table record is shown generally at **804**. The record includes a reseller field **806**, a mark-up type field **808**, a mark-up value field **810**, a first interval field **812** and a second interval field **814**. The reseller mark-up type, mark-up value, first interval and second interval fields are as described in connection with the fields by the same names in the system operator special rates table shown in FIG. **42**.

FIG. **45** provides an exemplary system operator mark-up table record for the reseller known as Klondike and therefore the reseller field **806** holds the value "Klondike", the mark-up type field **808** holds the value cents, the mark-up value field holds the value 0.01, the first interval field **812** holds the value 30 and the second interval field **814** holds the value 6. This indicates that the reseller "Klondike" charges by the cent at a rate of one cent per minute. The first 30 seconds of the call are free and billing is charged at the rate of one cent per minute in increments of 6 seconds.

FIG. **46** provides an exemplary system operator mark-up table record for cases where no specific system operator mark-up table record exists for a particular reseller, i.e., a default reseller mark-up record. This record is similar to the record shown in FIG. **45** and the reseller field **806** holds the value "all", the mark-up type field **808** is loaded with a code indicating mark-up is based on a percentage, the mark-up value field **810** holds the percentage by which the cost is marked up, and the first and second interval fields **812** and **814** identify first and second billing levels.

Referring back to FIG. **41**, if at block **802** a specific mark-up record for the reseller identified at block **782** is not located, block **820** directs the processor to get the mark-up

record shown in FIG. **46**, having the "all" code in the reseller field **806**. The processor is then directed to block **800**.

Referring back to FIG. **41**, at block **800**, the processor **202** of FIG. **7** is directed to set a reseller rate equal to the sum of the mark-up value of the record located by blocks **782**, **802** or **820** and the buffer rate specified by the contents of the buffer rate field **516** of the master list record shown in FIG. **20**. To do this, the RC processor sets a variable entitled "reseller cost per second" to a value equal to the sum of the contents of the mark-up value field (**792**, **810**) of the associated record, plus the contents of the buffer rate field (**516**) from the master list record associated with the master list ID. Then, block **822** directs the processor to set a system operator cost per second variable equal to the contents of the buffer rate field (**516**) from the master list record. Block **824** then directs the processor to determine whether the call type flag indicates the call is local or national/local style and whether the caller has free local calling. If both these conditions are met, then block **826** sets the user cost per second variable equal to zero and sets two increment variables equal to one, for use in later processing. The cost per second has thus be calculated and the process shown in FIG. **41** is ended.

If at block **824** the conditions of that block are not met, the processor **202** of FIG. **7** is directed to locate at least one of a bundle override table record specifying a route cost per unit time associated with a route associated with the communication session, a reseller special destinations table record associated with a reseller of the communications session, the reseller record specifying a reseller cost per unit time associated with the reseller for the communication session and a default reseller global markup record specifying a default cost per unit time.

To do this block **828** directs the processor **202** of FIG. **7** to determine whether or not the bundle override record **726** in FIG. **37** located at block **712** in FIG. **33**A has a master list ID equal to the stored master list ID that was determined at block **410** in FIG. **8**B. If not, block **830** directs the processor to find a reseller special destinations table record in a reseller special destinations table in the database (**18**), having a master list ID code equal to the master list ID code of the master list ID that was determined at block **410** in FIG. **8**B. An exemplary reseller special destinations table record is shown in FIG. **47** at **832**. The reseller special destinations table record includes a reseller field **834**, a master list ID field **836**, a mark-up type field **838**, a mark-up value field **840**, a first interval field **842** and a second interval field **844**. This record has the same format as the system operator special rates table record shown in FIG. **42**, but is stored in a different table to allow for different mark-up types and values and time intervals to be set according to resellers' preferences. Thus, for example, an exemplary reseller special destinations table record for the reseller "Klondike" is shown at **846** in FIG. **48**. The reseller field **834** holds a value indicating the reseller as the reseller "Klondike" and the master list ID field holds the code 1019. The mark-up type field **838** holds a code indicating the mark-up type is percent and the mark-up value field **840** holds a number representing the mark-up value as 5%. The first and second interval fields identify different billing levels used as described earlier.

Referring back to FIG. **41**, the record shown in FIG. **48** may be located at block **830**, for example. If at block **830** such a record is not found, then block **832** directs the processor to get a default operator global mark-up record based on the reseller ID.

Referring to FIG. **49**, an exemplary default reseller global mark-up table record is shown generally at **848**. This record includes a reseller field **850**, a mark-up type field **852**, a mark-up value field **854**, a first interval field **856** and a second interval field **858**. The reseller field **850** holds a code identifying the reseller. The mark-up type field **852**, the mark-up value field **854** and the first and second interval fields **856** and **858** are of the same type as described in connection with fields of the same name in FIG. **47**, for example. The contents of the fields of this record **860** may be set according to system operator preferences, for example.

Referring to FIG. **50**, an exemplary reseller global mark-up table record is shown generally at **860**. In this record, the reseller field **850** holds a code indicating the reseller is "Klondike", the mark-up type field **852** holds a code indicating the mark-up type is percent, the mark-up value field **854** holds a value representing 10% as the mark-up value, the first interval field **856** holds the value 30 and the second interval field **858** holds the values 30 and 6 respectively to indicate the first 30 seconds are free and billing is to be done in 6 second increments after that.

Referring back to FIG. **41**, should the processor get to block **832**, the reseller global mark-up table record as shown in FIG. **50** is retrieved from the database and stored locally at the RC. As seen in FIG. **41**, it will be appreciated that if the conditions are met in blocks **828** or **830**, or if the processor executes block **832**, the processor is then directed to block **862** which causes it to set an override value equal to the contents of the mark-up value field of the located record, to set the first increment variable equal to the contents of the first interval field of the located record and to set the second increment variable equal to the contents of the second interval field of the located record. (The increment variables were alternatively set to specific values at block **826** in FIG. **41**.)

It will be appreciated that the located record could be a bundle override record of the type shown in FIG. **37** or the located record could be a reseller special destination record of the type shown in FIG. **48** or the record could be a reseller global mark-up table record of the type shown in FIG. **50**. After the override and first and second increment variables have been set at block **862**, the processor **202** if FIG. **7** is directed to set as the cost per unit time the sum of the reseller rate and at least one of the route cost per unit time, the reseller cost per unit time and the default cost per unit time, depending on which record was located. To do this, block **864** directs the processor to set the cost per unit time equal to the sum of the reseller cost set at block **800** in FIG. **41**, plus the contents of the override variable calculated in block **862** in FIG. **41**. The cost per unit time has thus been calculated and it is this cost per unit time that is used in block **752** of FIG. **33**B, for example.

Terminating the Call

In the event that either the caller or the callee terminates a call, the telephone of the terminating party sends a SIP bye message to the controller **14**. An exemplary SIP bye message is shown at **900** in FIG. **51** and includes a caller field **902**, a callee field **904** and a call ID field **906**. The caller field **902** holds a twelve digit user name, the callee field **904** holds a PSTN compatible number or user name, and the call ID field **906** holds a unique call identifier field of the type shown in the call ID field **65** of the SIP invite message shown in FIG. **3**.

Thus, for example, referring to FIG. **52**, a SIP bye message for the Calgary callee is shown generally at **908** and the caller field **902** holds a user name identifying the caller, in this case 2001 1050 8667, the callee field **904** holds a user name identifying the Calgary callee, in this case 2001 1050

2222, and the call ID field **906** holds the code FA10 @ 192.168.0.20, which is the call ID for the call.

The SIP bye message shown in FIG. **52** is received at the call controller **14** and the call controller executes a process as shown generally at **910** in FIG. **53**. The process includes a first block **912** that directs the call controller processor **202** of FIG. **7** to copy the caller, callee and call ID field contents from the SIP bye message received from the terminating party to corresponding fields of an RC stop message buffer (not shown). Block **914** then directs the processor to copy the call start time from the call timer and to obtain a call stop time from the call timer. Block **916** then directs the call controller to calculate a communication session time by determining the difference in time between the call start time and the call stop time. This session time is then stored in a corresponding field of the RC call stop message buffer. Block **917** then directs the processor to decrement the contents of the current concurrent call field **277** of the dialing profile for the caller as shown in FIG. **10**, to indicate that there is one less concurrent call in progress. A copy of the amended dialing profile for the caller is then stored in the database **18** of FIG. **1**. Block **918** then directs the processor to copy the route from the call log. An RC call stop message produced as described above is shown generally at **1000** in FIG. **54**. An RC call stop message specifically associated with the call made to the Calgary callee is shown generally at **1020** in FIG. **55**.

Referring to FIG. **54**, the RC stop call message includes a caller field **1002**, callee field **1004**, a call ID field **1006**, an account start time field **1008**, an account stop time field **1010**, a communication session time **1012** and a route field **1014**. The caller field **1002** holds a username, the callee field **1004** holds a PSTN-compatible number or system number, the call ID field **1006** hold the unique call identifier received from the SIP invite message shown in FIG. **3**, the account start time field **1008** holds the date and start time of the call, the account stop time field **1010** holds the date and time the call ended, the communication session time field **1012** holds a value representing the difference between the start time and the stop time, in seconds, and the route field **1014** holds the IP address for the communications link that was established.

Referring to FIG. **55**, an exemplary RC stop call message for the Calgary callee is shown generally at **1020**. In this example the caller field **1002** holds the user name 2001 1050 8667 identifying the Vancouver-based caller and the callee field **1004** holds the user name 2001 1050 2222 identifying the Calgary callee. The contents of the call ID field **1006** are FA10@ 192.168.0.20. The contents of the account start time field **1008** are 2006-12-30 12:12:12 and the contents of the account stop time field are 2006-12-30 12:12:14. The contents of the communication session time field **1012** are 2 to indicate 2 seconds call duration and the contents of the route field are 72.64.39.58.

Referring back to FIG. **53**, after having produced an RC call stop message, block **920** directs the processor **202** in FIG. **7** to send the RC stop message compiled in the RC call stop message buffer to the RC **16** of FIG. **1**. Block **922** directs the call controller **14** to send a "bye" message back to the party that did not terminate the call.

The RC **16** of FIG. **1** receives the call stop message and an RC call stop message process is invoked at the RC, the process being shown at **950** in FIGS. **56**A, **56**B and **56**C. Referring to FIG. **56**A, the RC stop message process **950** begins with a first block **952** that directs the processor **202** in FIG. **7** to determine whether or not the communication session time is less than or equal to the first increment value set by the cost calculation routine shown in FIG. **41**, specifically blocks **826** or **862** thereof. If this condition is met, then block **954** of FIG. **56**A directs the RC processor to set a chargeable time variable equal to the first increment value set at block **826** or **862** of FIG. **41**. If at block **952** of FIG. **56**A the condition is not met, block **956** directs the RC processor to set a remainder variable equal to the difference between the communication session time and the first increment value mod the second increment value produced at block **826** or **862** of FIG. **41**. Then, the processor is directed to block **958** of FIG. **56**A which directs it to determine whether or not the remainder is greater than zero. If so, block **960** directs the RC processor to set the chargeable time variable equal to the difference between the communication session time and the remainder value. If at block **958** the remainder is not greater than zero, block **962** directs the RC processor to set the chargeable time variable equal to the contents of the communication session time from the RC stop message. The processor is then directed to block **964**. In addition, after executing block **954** or block **960**, the processor is directed to block **964**.

Block **964** directs the processor **202** of FIG. **7** to determine whether or not the chargeable time variable is greater than or equal to the free time balance as determined from the free time field **742** of the subscriber account record shown in FIG. **39**. If this condition is satisfied, block **966** of FIG. **56**A directs the processor to set the free time field **742** in the record shown in FIG. **39**, to zero. If the chargeable time variable is not greater than or equal to the free time balance, block **968** directs the RC processor to set a user cost variable to zero and Block **970** then decrements the free time field **742** of the subscriber account record for the caller by the chargeable time amount determined by block **954**, **960** or **962**.

If at Block **964** the processor **202** of FIG. **7** was directed to Block **966** which causes the free time field (**742** of FIG. **39**) to be set to zero, referring to FIG. **56**B, Block **972** directs the processor to set a remaining chargeable time variable equal to the difference between the chargeable time and the contents of the free time field (**742** of FIG. **39**). Block **974** then directs the processor to set the user cost variable equal to the product of the remaining chargeable time and the cost per second calculated at Block **750** in FIG. **33**B. Block **976** then directs the processor to decrement the funds balance field (**740**) of the subscriber account record shown in FIG. **39** by the contents of the user cost variable calculated at Block **974**.

After completing Block **976** or after completing Block **970** in FIG. **56**A, block **978** of FIG. **56**B directs the processor **202** of FIG. **7** to calculate a reseller cost variable as the product of the reseller rate as indicated in the mark-up value field **810** of the system operator mark-up table record shown in FIG. **45** and the communication session time determined at Block **916** in FIG. **53**. Then, Block **980** of FIG. **56**B directs the processor to add the reseller cost to the reseller balance field **986** of a reseller account record of the type shown in FIG. **57** at **982**.

The reseller account record includes a reseller ID field **984** and the aforementioned reseller balance field **986**. The reseller ID field **984** holds a reseller ID code, and the reseller balance field **986** holds an accumulated balance of charges.

Referring to FIG. **58**, a specific reseller accounts record for the reseller "Klondike" is shown generally at **988**. In this record the reseller ID field **984** holds a code representing the reseller "Klondike" and the reseller balance field **986** holds a balance of $100.02. Thus, the contents of the reseller

balance field **986** in FIG. **58** are incremented by the reseller cost calculated at block **978** of FIG. **56**B.

Still referring to FIG. **56**B, after adding the reseller cost to the reseller balance field as indicated by Block **980**, Block **990** directs the processor to **202** of FIG. **7** calculate a system operator cost as the product of the system operator cost per second, as set at block **822** in FIG. **41**, and the communication session time as determined at Block **916** in FIG. **53**. Block **992** then directs the processor to add the system operator cost value calculated at Block **990** to a system operator accounts table record of the type shown at **994** in FIG. **59**. This record includes a system operator balance field **996** holding an accumulated charges balance. Referring to FIG. **60** in the embodiment described, the system operator balance field **996** may hold the value $1,000.02 for example, and to this value the system operator cost calculated at Block **990** is added when the processor executes Block **992** of FIG. **56**B.

Ultimately, the final reseller balance **986** in FIG. **58** holds a number representing an amount owed to the reseller by the system operator and the system operator balance **996** of FIG. **59** holds a number representing an amount of profit for the system operator.

While specific embodiments of the invention have been described and illustrated, such embodiments should be considered illustrative of the invention only and not as limiting the invention as construed in accordance with the accompanying claims.

What is claimed is:

1. A method for routing communications in a packet switched communication system between a first participant device associated with a first participant and a second participant device associated with a second participant, the first and second participant devices being associated with first and second network elements of the communication system, respectively, the method comprising:

receiving, by at least one processor, a second participant identifier associated with the second participant device, in response to initiation of a communication from the first participant device to the second participant device, the first participant device being associated with a first participant identifier;

causing the at least one processor to access at least one memory storing a first participant profile identifying at least one first participant attribute;

processing the second participant identifier and the at least one first participant attribute, using the at least one processor, to produce a new second participant identifier based on at least one match between the second participant identifier and the at least one first participant attribute;

processing the new second participant identifier, using the at least one processor, to determine whether the second network element is the same as the first network element;

when the second network element is determined to be the same as the first network element, producing a routing message identifying a first network address associated with the first network element, using the at least one processor; and

when the second network element is determined not to be the same as the first network element, producing a routing message identifying a second network address associated with the second network element, using the at least one processor;

wherein the packet switched communication system attempts to establish the communication from the first participant device to the second participant device based on at least one network address identified in the routing message.

2. The method of claim **1** wherein processing the new second participant identifier comprises comparing at least a portion of the second participant identifier with an identifier associated with the first network element.

3. The method of claim **1** further comprising processing a user-specific attribute associated with the first participant profile, using the at least one processor, to determine whether the communication is allowed to proceed.

4. The method of claim **1** further comprising:

causing the at least one processor to access a database to locate communication forwarding information associated with the second participant; and

processing the communication forwarding information, using the at least one processor, to determine whether the forwarding information identifies a communication device associated with a node that is associated with the first network element.

5. The method of claim **4** wherein the communication forwarding information associated with the second participant comprises a plurality of communication destination identifiers, and wherein the method further comprises causing the communication system to attempt to forward the communication to a plurality of communication destinations corresponding to the plurality of communication destination identifiers.

6. The method of claim **1**, further comprising:

in response to initiation of a further communication from a third participant device to the second participant device, receiving a third participant identifier and the second participant identifier;

causing the at least one processor to access a database to locate communication blocking information associated with the second participant; and

blocking the further communication when the communication blocking information identifies the third participant identifier.

7. The method of claim **4**, wherein processing the second participant identifier further comprises:

causing the at least one processor to access a database to locate communication blocking information associated with the second participant.

8. The method of claim **1** further comprising:

(a) updating a database to cause at least one user-specific first participant attribute to be modified,

(b) wherein the second participant identifier identifies a device in communication with a public switched telephone network (PSTN),

(c) wherein the communication comprises a video or audio call,

(d) wherein the packet switched communication system, including the first and second network elements, form a private network operably configured to provide communication services to subscribers thereof, and

(e) wherein the at least one network element of the communication system comprises a call controller operable to establish the video or audio call to the second participant device in response to the routing message.

9. The method of claim **1** wherein processing the new second participant identifier comprises determining whether a location associated with the first participant device is the same as a location associated with the new second participant identifier.

10. The method of claim 9 wherein the new second participant identifier is associated with a second participant profile identifying a domain name or IP address of a communication system node comprising the second network element.

11. The method of claim 1 wherein processing the second participant identifier comprises locating the new second participant identifier in a database based on the second participant identifier, and causing the packet switched communication system to establish the communication to the second participant device based on the new second participant identifier.

12. The method of claim 1 further comprising locating the second network address associated with the second network element in a database based on the second participant identifier, and causing the packet switched communication system to establish the communication to the second participant device based on the second network address.

13. The method of claim 1 wherein processing the second participant identifier comprises modifying the second participant identifier based on the first participant profile.

14. The method of claim 1, wherein the packet switched communication system is controlled by a system operator, the method further comprising:

receiving a third participant identifier associated with a third participant device, wherein the third participant device is not associated with either the first network element or the second network element; and

producing a routing message identifying a gateway to an external communication system that is not controlled by the system operator, using the at least one processor, to cause a further communication to be established to the third participant device.

15. The method of claim 14 wherein at least a portion of the external communication system is a public switched telephone network (PSTN) communication system, and wherein the third participant identifier comprises a public switched telephone network (PSTN) number.

16. The method of claim 14 wherein the packet switched communication system is connected to a plurality of gateways to the external communication system, the method further comprising:

using the at least one processor to select the gateway from among the plurality of gateways.

17. The method of claim 1 further comprising:

receiving communication forwarding information associated with the second participant, the communication forwarding information comprising a plurality of communication destination identifiers;

processing one or more of the communication destination identifiers, using the at least one processor, to attempt to establish the communication with the second participant device until the communication is established or all communication destination identifiers have been exhausted.

18. The method of claim 1 further comprising, if the communication cannot be established to the second participant device, causing communication to be routed to a server operable to store the communication and facilitate delivery of the communication to the second participant device at a later time.

19. A method for routing communications in an Internet Protocol (IP) based communication system between a first participant device associated with a first participant and a second participant device associated with a second participant, the first and second participant devices being associated with first and second network elements of the communication system, respectively, first and second network elements being operably configured to provide communication services to users associated with first and second geographical areas, respectively, the method comprising:

receiving, by at least one processor, a second participant identifier associated with the second participant device, in response to the first participant device initiating a communication to the second participant device, the first participant device being associated with a first participant identifier;

causing the at least one processor to access at least one memory storing a first participant profile identifying at least one first participant attribute;

producing a new second participant identifier based on determining at least one match of the at least one first participant attribute and at least a portion of the second participant identifier, using the at least one processor;

processing the new second participant identifier, using the at least one processor, to determine whether the second network element is the same as the first network element;

when the second network element is determined to be the same as the first network element, producing a routing message identifying a first network address associated with the first network element, using the at least one processor; and

when the second network element is determined not to be the same as the first network element, producing a routing message identifying a second network address associated with the second network element, using the at least one processor;

wherein at least one network node is provided in geographical proximity to at least one of the first and second network elements to provide load sharing of the communication services provided to users associated with at least one of the first and second geographical areas, the at least one network node providing the load sharing to the at least one of the first and second network elements, to establish the communication to the second participant device in response to the routing message.

20. The method of claim 19 wherein the communication system comprises at least one database for storing user profiles including the first participant profile, each user profile identifying a respective address associated with a network element at which the respective user of the communication system is registered to access communication services.

21. An apparatus for routing communications in an Internet Protocol (IP) based communication system between a first participant device associated with a first participant and a second participant device associated with a second participant, the communication system comprising a plurality of network elements, the first participant device being associated with a first network element and the second participant device being associated with a second network element of the communication system, the apparatus comprising:

a controller comprising at least one processor in communication with at least one memory storing processor readable instructions, the at least one processor being operably configured by the processor readable instructions to:

in response to initiation of a communication to the second participant device, receive a second participant identifier;

access at least one first participant profile in the at least one memory to locate at least one first participant attribute associated with the first participant;

process the second participant identifier and the at least one first participant attribute to determine at least one match between the second participant identifier and the at least one first participant attribute;

determine whether the second network element is the same as the first network element based at least in part on the at least one match;

when the second network element is determined to be the same as the first network element, produce a routing message identifying a first Internet Protocol (IP) network address associated with the first network element; and

when the second network element is determined to be not the same as the first network element, produce a routing message identifying a second Internet Protocol (IP) network address associated with the second network element; and

causing the communication to be established to a destination communication device using one of the first network element and the second network element based on the routing message.

22. The apparatus of claim **21**, wherein the at least one processor is further operably configured to:

in response to initiation of a further communication to a third participant device, receive a third participant identifier associated with the third participant device;

access at least one database to locate at least one of: (i) blocking information associated with the third participant device; and (ii) forwarding information associated with the third participant device;

determine whether the further communication should be blocked from being established to the third participant device based on the communication blocking information; and

determine whether the communication should be forwarded to at least one other communication device based on the forwarding information associated with the third participant device.

23. The apparatus of claim **21** wherein the at least one processor is further operably configured to cause the communication to be established to the destination communication device:

(a) using the first IP network address, if the second network element is determined to be the same as the first network element; and

(b) using the second IP network address, if the second network element is determined to be not the same as the first network element.

24. The apparatus of claim **21**,

(a) wherein the communication system comprises a plurality of nodes including at least a first communication node and a second communication node in communication with each other, the first and second communication nodes comprising the first and second network elements, respectively;

(b) wherein the first and second communication nodes are operably configured to provide communications services to communication devices associated with first and second geographical areas, respectively; and

(c) wherein at least one communication node is provided in geographical proximity to at least one of the first and second communication nodes to provide load sharing of the communication services provided by the at least one of the first and second communication nodes.

25. The apparatus of claim **21**, wherein the at least one processor is further operably configured to:

(a) process an attribute associated with the first participant profile to determine whether the communication is allowed to proceed; and

(b) if the communication is allowed to proceed, cause at least one attribute associated with the first participant profile to be modified.

26. The apparatus of claim **21**, wherein the at least one processor is further operably configured to cause a routing message identifying a gateway to a public network to be produced, to cause at least one communication to be routed through the gateway over the public network.

27. The apparatus of claim **21**, wherein the at least one processor is further operably configured to determine a network element with which the second participant device is associated based on a geographical area associated with the second participant identifier and to identify the network element with which the second participant device is associated in the routing message.

28. The apparatus of claim **21** wherein the at least one processor is further operably configured to:

(a) in response to initiation of a further communication to a third participant device, receive a third participant identifier associated with the third participant device; and

(b) cause a query to be sent to a plurality of gateways to determine whether at least one gateway from the plurality of gateways is available to carry the further communication to the third participant device.

29. The apparatus of claim **21** wherein the at least one processor is further operably configured to cause a message to be sent through at least one Internet-connected server to an IP address of the second participant device.

30. A non-transitory computer readable medium storing instructions for directing the at least one processor to execute the method of claim **1**.

31. The method of claim **1** wherein the routing message causes a communication controller to establish the communication to the second participant device:

(a) using the first network address, if the second network element is determined to be the same as the first network element; and

(b) using the second network address, if the second network element is determined to be not the same as the first network element;

(c) wherein the first participant identifier comprises a first public switched telephone network (PSTN) number and the new second participant identifier comprises a second public switched telephone network (PSTN) number.

32. The method of claim **1** wherein the communication system comprises a plurality of nodes including at least a first communication node and a second communication node in communication with each other, the first and second communication nodes comprising the first and second network elements, respectively, the first and second communication nodes being operably configured to provide communications services to communication devices associated with first and second geographical areas, respectively, the method further comprising:

determining a particular communication node with which the second participant device is associated based on a geographical area associated with the second participant identifier, and identifying the particular commu-

nication node in the routing message, to cause the communication to be established through the particular communication node.

33. The method of claim **1** wherein the communication comprises a video or audio call, and wherein a call controller causes the communication to be routed to the second participant device in response to the routing message.

34. The method of claim **1** further comprising, in response to initiation of a further communication from the first participant device to a third participant device accessible within the communication system, the third participant device being associated with a public switched telephone network (PSTN) number:

receiving a third participant identifier associated with the third participant device;

processing an attribute associated with the first participant profile, using the at least one processor, to determine whether the further communication from the first participant device is allowed to proceed, and if the further communication is not allowed to proceed, causing a communication controller to block the further communication; and

identifying the public switched telephone network (PSTN) telephone number associated with the third participant device based on receiving the third participant identifier, to produce a further routing message and cause the communication controller to establish the communication to the third participant device.

35. A non-transitory computer readable medium storing instructions for directing the at least one processor to execute the method of claim **6**.

36. A non-transitory computer readable medium storing instructions for directing the at least one processor to execute the method of claim **8**.

37. A non-transitory computer readable medium storing instructions for directing the at least one processor to execute the method of claim **20**.

38. A non-transitory computer readable medium storing instructions for directing the at least one processor to execute the method of claim **31**.

39. A non-transitory computer readable medium storing instructions for directing the at least one processor to execute the method of claim **34**.

40. The apparatus of claim **21**, wherein the at least one processor is further operably configured to locate communication forwarding information associated with the second participant, the communication forwarding information comprising a plurality of communication destination identifiers, and to cause a communication controller to attempt to forward the communication to a plurality of communication destinations corresponding to the plurality of communication destination identifiers.

41. The apparatus of claim **21**, wherein the at least one processor is further operably configured to:

(a) in response to initiation of a further communication from a third participant device to the second participant device, receive a third participant identifier and the second participant identifier;

(b) locate communication blocking information associated with the second participant identifier in a database; and

(c) block the further communication when the communication blocking information identifies the third participant identifier, wherein at least one of the second and third participant identifiers comprises a public switched telephone network (PSTN) number.

42. The apparatus of claim **21** wherein the at least one processor is further operably configured to:

(a) in response to initiation of a further communication from a third participant device to the second participant device, receive a third participant identifier and the second participant identifier;

(b) process a user-specific attribute associated with a third participant profile to determine whether the further communication is allowed to proceed; and

(c) block the further communication when it is determined that the further communication is not allowed to proceed.

43. The apparatus of claim **21**, wherein the at least one processor is further operably configured to:

(a) locate a new second participant identifier associated with the second participant identifier; and

(b) cause a communication controller to establish the communication to the second participant device based on the new second participant identifier;

(c) wherein at least one of the second participant identifier and the new second participant identifier comprises a public switched telephone network (PSTN) number.

44. The apparatus of claim **21**, wherein the at least one processor is further operably configured to:

(a) modify the second participant identifier based on the first participant profile; and

(b) cause a communication controller to establish the communication to the second participant device based on the modified second participant identifier;

(c) wherein the modified second participant identifier comprises a public switched telephone network (PSTN) number.

45. The apparatus of claim **21**, wherein the communication system is controlled by a system operator and wherein the at least one processor is further operably configured to:

(a) receive a third participant identifier associated with a third participant device, wherein the third participant device is not associated with either the first network element or the second network element; and

(b) produce a routing message identifying a gateway to an external communication system that is not controlled by the system operator, to cause a communication controller to establish a further communication through the gateway to the third participant device.

46. The apparatus of claim **21**, wherein the at least one processor is further operably configured to:

(a) produce a new second participant identifier associated with the second participant device, in response to receiving the second participant identifier; and

(b) cause a communication controller to establish the communication to the second participant device based on the new second participant identifier.

47. The apparatus of claim **46** wherein the new second participant identifier comprises a public switched telephone network (PSTN) number.

48. The apparatus of claim **21** wherein the at least one processor is further operably configured to produce a routing message causing at least one communication initiated from the first participant device to a particular destination device, to be routed to a server operable to store the at least one communication and to provide access to the stored at least one communication to the particular destination device at a later time.

49. The apparatus of claim **21**, wherein the communication system comprises at least one database for storing user profiles including the first participant profile, each user profile identifying a respective IP address associated with a

network element at which the respective user of the communication system is registered to access communication services, wherein the at least one processor is further operably configured to locate, in the at least one database, an IP network address of a particular network element associated with a second participant profile, and to cause the communication to be established to the second participant device using the particular network element associated with the second participant profile.

* * * * *